
Percona Distribution for MongoDB Operator Documentation

Release 1.9.0

Percona LLC and/or its affiliates 2009-2021

Jun 29, 2021

CONTENTS

I	Requirements	3
II	Quickstart guides	9
III	Advanced Installation Guides	23
IV	Configuration	39
V	Management	67
VI	Reference	95

The [Percona Distribution for MongoDB Kubernetes Operator](#) automates the creation, modification, or deletion of items in your Percona Server for MongoDB environment. The Operator contains the necessary Kubernetes settings to maintain a consistent Percona Server for MongoDB instance. modification, or deletion of items in your Percona Server for MongoDB environment. The Operator contains the necessary Kubernetes settings to maintain a consistent Percona Server for MongoDB instance.

The Percona Kubernetes Operators are based on best practices for the configuration of a Percona Server for MongoDB replica set. The Operator provides many benefits but saving time, a consistent environment are the most important.

Part I

Requirements

SYSTEM REQUIREMENTS

The Operator was developed and tested with Percona Server for MongoDB 4.0, 4.2, and 4.4. Other options may also work but have not been tested.

Note: The [MMAPv1 storage engine](#) is no longer supported for all MongoDB versions starting from the Operator version 1.6. MMAPv1 was already deprecated by MongoDB for a long time. WiredTiger is the default storage engine since MongoDB 3.2, and MMAPv1 was completely removed in MongoDB 4.2.

1.1 Officially supported platforms

The following platforms were tested and are officially supported by the Operator 1.9.0:

- OpenShift 4.7
- Google Kubernetes Engine (GKE) 1.17 - 1.21
- Amazon Elastic Container Service for Kubernetes (EKS) 1.16-1.20
- Minikube 1.20
- VMWare Tanzu

Other Kubernetes platforms may also work but have not been tested.

1.2 Resource Limits

A cluster running an officially supported platform contains at least 3 Nodes and the following resources (if [sharding](#) is turned off):

- 2GB of RAM,
- 2 CPU threads per Node for Pods provisioning,
- at least 60GB of available storage for Private Volumes provisioning.

Consider using 4 CPU and 6 GB of RAM if [sharding](#) is turned on (the default behavior).

Also, the number of Replica Set Nodes should not be odd if [Arbiter](#) is not enabled.

Note: Use Storage Class with XFS as the default filesystem if possible to achieve better MongoDB performance.


1.3 Platform-specific limitations

The Operator is subsequent to specific platform limitations.

- Minikube doesn't support multi-node cluster configurations because of its local nature, which is in collision with the default affinity requirements of the Operator. To arrange this, the *Install Percona Server for MongoDB on Minikube* instruction includes an additional step which turns off the requirement of having not less than three Nodes.

DESIGN OVERVIEW

The design of the Operator is tightly bound to the Percona Server for MongoDB replica set, which is briefly described in the following diagram.




A replica set consists of one primary server and several secondary ones (two in the picture), and the client application accesses the servers via a driver.

To provide high availability the Operator uses [node affinity](#) to run MongoDB instances on separate worker nodes if possible, and the database cluster is deployed as a single Replica Set with at least three nodes. If a node fails, the pod with the mongod process is automatically re-created on another node. If the failed node was hosting the primary server, the replica set initiates elections to select a new primary. If the failed node was running the Operator, Kubernetes will restart the Operator on another node, so normal operation will not be interrupted.

Client applications should use a `mongo+srv` URI for the connection. This allows the drivers (4.0 and up) to retrieve the list of replica set members from DNS SRV entries without having to list hostnames for the dynamically assigned nodes.

Note: The Operator uses security settings which are more secure than the default Percona Server for MongoDB setup. The initial configuration contains default passwords for all needed user accounts, which should be changed in the production environment, as stated in the [installation instructions](#).



To provide data storage for stateful applications, Kubernetes uses Persistent Volumes. A *PersistentVolumeClaim* (PVC) is used to implement the automatic storage provisioning to pods. If a failure occurs, the Container Storage Interface (CSI) should be able to re-mount storage on a different node. The PVC StorageClass must support this feature (Kubernetes and OpenShift support this in versions 1.9 and 3.9 respectively).

The Operator functionality extends the Kubernetes API with *PerconaServerMongoDB* object, and it is implemented as a golang application. Each *PerconaServerMongoDB* object maps to one separate Percona Server for MongoDB setup. The Operator listens to all events on the created objects. When a new *PerconaServerMongoDB* object is created, or an existing one undergoes some changes or deletion, the operator automatically creates/changes/deletes all needed Kubernetes objects with the appropriate settings to provide a properly operating replica set.

Part II

Quickstart guides

INSTALL PERCONA SERVER FOR MONGODB ON MINIKUBE

Installing the Percona Distribution for MongoDB Operator on [Minikube](#) is the easiest way to try it locally without a cloud provider. Minikube runs Kubernetes on GNU/Linux, Windows, or macOS system using a system-wide hypervisor, such as VirtualBox, KVM/QEMU, VMware Fusion or Hyper-V. Using it is a popular way to test Kubernetes application locally prior to deploying it on a cloud.

The following steps are needed to run Percona Distribution for MongoDB Operator on minikube:

0. [Install minikube](#), using a way recommended for your system. This includes the installation of the following three components:
 1. kubectl tool,
 2. a hypervisor, if it is not already installed,
 3. actual minikube package

After the installation, run `minikube start --memory=5120 --cpus=4 --disk-size=30g` (parameters increase the virtual machine limits for the CPU cores, memory, and disk, to ensure stable work of the Operator). Being executed, this command will download needed virtualized images, then initialize and run the cluster. After Minikube is successfully started, you can optionally run the Kubernetes dashboard, which visually represents the state of your cluster. Executing `minikube dashboard` will start the dashboard and open it in your default web browser.

1. Clone the `percona-server-mongodb-operator` repository:

```
git clone -b v1.9.0 https://github.com/percona/percona-server-mongodb-operator
cd percona-server-mongodb-operator
```

2. Deploy the operator with the following command:

```
kubectl apply -f deploy/bundle.yaml
```

3. Because minikube runs locally, the default `deploy/cr.yaml` file should be edited to adapt the Operator for the local installation with limited resources. Change the following keys in the `replsets` section:
 1. comment **all occurrences** of the `resources.requests.memory` and `resources.requests.cpu` keys (this will fit the Operator in minikube default limitations)
 2. set **all occurrences** of the `affinity.antiAffinityTopologyKey` key to "none" (the Operator will be unable to spread the cluster on several nodes)

Also, switch `allowUnsafeConfigurations` key to `true` (this option turns off the Operator's control over the cluster configuration, making it possible to deploy Percona Server for MongoDB as a one-node cluster).

4. Now apply the `deploy/cr.yaml` file with the following command:

```
kubectl apply -f deploy/cr.yaml
```

The creation process may take some time. The process is over when all Pods have reached their Running status. You can check it with the following command:

```
kubectl get pods
```

The result should look as follows:

NAME	READY	STATUS	RESTARTS	AGE
my-cluster-name-cfg-0	2/2	Running	0	11m
my-cluster-name-cfg-1	2/2	Running	1	10m
my-cluster-name-cfg-2	2/2	Running	1	9m
my-cluster-name-mongos-55659468f7-2kvc2	1/1	Running	0	11m
my-cluster-name-mongos-55659468f7-7jfqc	1/1	Running	0	11m
my-cluster-name-mongos-55659468f7-dfwcj	1/1	Running	0	11m
my-cluster-name-rs0-0	2/2	Running	0	11m
my-cluster-name-rs0-1	2/2	Running	0	10m
my-cluster-name-rs0-2	2/2	Running	0	9m
percona-server-mongodb-operator-6fc78d686d-26hdz	1/1	Running	0	37m

- During previous steps, the Operator has generated several `secrets`, including the password for the admin user, which you will need to access the cluster. Use `kubectl get secrets` to see the list of Secrets objects (by default Secrets object you are interested in has `my-cluster-name-secrets` name). Then `kubectl get secret my-cluster-name-secrets -o yaml` will return the YAML file with generated secrets, including the `MONGODB_USER_ADMIN` and `MONGODB_USER_ADMIN_PASSWORD` strings, which should look as follows:

```
...
data:
  ...
  MONGODB_USER_ADMIN_PASSWORD: aDAzQ0pCY3NSWEZ2ZUIzS1I=
  MONGODB_USER_ADMIN_USER: dXNlckFkbWlu
```

Here the actual login name and password are base64-encoded, and `echo 'aDAzQ0pCY3NSWEZ2ZUIzS1I=' | base64 --decode` will bring it back to a human-readable form.

- Check connectivity to a newly created cluster.

First of all, run a container with a MongoDB client and connect its console output to your terminal. The following command will do this, naming the new Pod `percona-client`:

```
kubectl run -i --rm --tty percona-client --image=percona/percona-server-mongodb:4.4.
↵6-8 --restart=Never -- bash -il
```

Executing it may require some time to deploy the correspondent Pod. Now run `mongo` tool in the `percona-client` command shell using the login (which is `userAdmin`) and password obtained from the secret:

```
mongo "mongodb://userAdmin:userAdminPassword@my-cluster-name-mongos.default.svc.
↵cluster.local/admin?ssl=false"
```


INSTALL PERCONA SERVER FOR MONGODB ON GOOGLE KUBERNETES ENGINE (GKE)

This quickstart shows you how to configure a Percona Distribution for MongoDB Operator with the Google Kubernetes Engine. The document assumes some experience with Google Kubernetes Engine (GKE). For more information on the GKE, see the [Kubernetes Engine Quickstart](#).

4.1 Prerequisites

All commands from this quickstart can be run either in the **Google Cloud shell** or in **your local shell**.

To use *Google Cloud shell*, you need nothing but a modern web browser.

If you would like to use *your local shell*, install the following:

1. **gcloud**. This tool is part of the Google Cloud SDK. To install it, select your operating system on the [official Google Cloud SDK documentation page](#) and then follow the instructions.
2. **kubect**l. It is the Kubernetes command-line tool you will use to manage and deploy applications. To install the tool, run the following command:

```
$ gcloud auth login
$ gcloud components install kubectl
```


4.2 Configuring default settings for the cluster

You can configure the settings using the **gcloud** tool. You can run it either in the [Cloud Shell](#) or in your local shell (if you have installed Google Cloud SDK locally on the previous step). The following command will create a cluster named `my-cluster-name`:

```
$ gcloud container clusters create my-cluster-name --project <project name> --zone us-
central1-a --cluster-version 1.20 --machine-type n1-standard-4 --num-nodes=3
```

Note: You must edit the following command and other command-line statements to replace the `<project name>` placeholder with your project name. You may also be required to edit the *zone location*, which is set to `us-central1` in the above example. Other parameters specify that we are creating a cluster with 3 nodes and with machine type of 4 vCPUs and 45 GB memory.

You may wait a few minutes for the cluster to be generated, and then you will see it listed in the Google Cloud console (select *Kubernetes Engine* → *Clusters* in the left menu panel):



Now you should configure the command-line access to your newly created cluster to make `kubectl` be able to use it.

In the Google Cloud Console, select your cluster and then click the *Connect* shown on the above image. You will see the connect statement configures command-line access. After you have edited the statement, you may run the command in your local shell:

```
$ gcloud container clusters get-credentials my-cluster-name --zone us-central1-a --
↪project <project name>
```

4.3 Installing the Operator

1. First of all, use your [Cloud Identity and Access Management \(Cloud IAM\)](#) to control access to the cluster. The following command will give you the ability to create Roles and RoleBindings:

```
$ kubectl create clusterrolebinding cluster-admin-binding --clusterrole cluster-
↪admin --user $(gcloud config get-value core/account)
```

The return statement confirms the creation:

```
clusterrolebinding.rbac.authorization.k8s.io/cluster-admin-binding created
```

2. Create a namespace and set the context for the namespace. The resource names must be unique within the namespace and provide a way to divide cluster resources between users spread across multiple projects.

So, create the namespace and save it in the namespace context for subsequent commands as follows (replace the `<namespace name>` placeholder with some descriptive name):

```
$ kubectl create namespace <namespace name>
$ kubectl config set-context $(kubectl config current-context) --namespace=
↪<namespace name>
```

At success, you will see the message that `namespace/<namespace name>` was created, and the context `(gke_<project name>_<zone location>_<cluster name>)` was modified.

3. Use the following `git clone` command to download the correct branch of the `percona-server-mongodb-operator` repository:

```
git clone -b v1.9.0 https://github.com/percona/percona-server-mongodb-operator
```

After the repository is downloaded, change the directory to run the rest of the commands in this document:

```
cd percona-server-mongodb-operator
```

4. Deploy the Operator with the following command:

```
kubectl apply -f deploy/bundle.yaml
```

The following confirmation is returned:

```

customresourcedefinition.apiextensions.k8s.io/perconaservermongodbbs.psmdb.percona.
↪com created
customresourcedefinition.apiextensions.k8s.io/perconaservermongodbbackups.psmdb.
↪percona.com created
customresourcedefinition.apiextensions.k8s.io/perconaservermongodbrestores.psmdb.
↪percona.com created
role.rbac.authorization.k8s.io/percona-server-mongodb-operator created
serviceaccount/percona-server-mongodb-operator created
rolebinding.rbac.authorization.k8s.io/service-account-percona-server-mongodb-
↪operator created
deployment.apps/percona-server-mongodb-operator created

```

5. The operator has been started, and you can create the Percona Server for MongoDB:

```
$ kubectl apply -f deploy/cr.yaml
```

The process could take some time. The return statement confirms the creation:

```
perconaservermongodb.psmdb.percona.com/my-cluster-name created
```

6. During previous steps, the Operator has generated several [secrets](#), including the password for the root user, which you will need to access the cluster.

Use `kubectl get secrets` command to see the list of Secrets objects (by default Secrets object you are interested in has `my-cluster-secrets` name). Then `kubectl get secret my-cluster-secrets -o yaml` will return the YAML file with generated secrets, including the `MONGODB_USER_ADMIN` and `MONGODB_USER_ADMIN_PASSWORD` strings, which should look as follows:

```

...
data:
  ...
  MONGODB_USER_ADMIN_PASSWORD: aDAzQ0pCY3NSWEZ2ZUIzS1I=
  MONGODB_USER_ADMIN_USER: dXNlckFkbWlu

```

Here the actual password is base64-encoded, and `echo 'aDAzQ0pCY3NSWEZ2ZUIzS1I=' | base64 --decode` will bring it back to a human-readable form.

4.4 Verifying the cluster operation

It may take ten minutes to get the cluster started. You can verify its creation with the `kubectl get pods` command:

```
$ kubectl get pods
```

The result should look as follows:

NAME	READY	STATUS	RESTARTS	AGE
my-cluster-name-cfg-0	2/2	Running	0	11m
my-cluster-name-cfg-1	2/2	Running	1	10m
my-cluster-name-cfg-2	2/2	Running	1	9m
my-cluster-name-mongos-55659468f7-2kvc2	1/1	Running	0	11m
my-cluster-name-mongos-55659468f7-7jfqc	1/1	Running	0	11m
my-cluster-name-mongos-55659468f7-dfwcj	1/1	Running	0	11m

(continues on next page)

(continued from previous page)

my-cluster-name-rs0-0	2/2	Running	0	11m
my-cluster-name-rs0-1	2/2	Running	0	10m
my-cluster-name-rs0-2	2/2	Running	0	9m
percona-server-mongodb-operator-6fc78d686d-26hdz	1/1	Running	0	37m

Also, you can see the same information when browsing Pods of your cluster in Google Cloud console via the *Object Browser*:

Name	Status	Type	Namespace	Cluster
▼ core		API Group		
▼ Pod		Kind		
my-cluster-name-cfg-0	✓ Running	Pod	default	my-cluster-name
my-cluster-name-cfg-1	✓ Running	Pod	default	my-cluster-name
my-cluster-name-cfg-2	✓ Running	Pod	default	my-cluster-name
my-cluster-name-mongos-55659468f7-2kvc2	✓ Running	Pod	default	my-cluster-name
my-cluster-name-mongos-55659468f7-7jfqc	✓ Running	Pod	default	my-cluster-name
my-cluster-name-mongos-55659468f7-dlwci	✓ Running	Pod	default	my-cluster-name
my-cluster-name-rs0-0	✓ Running	Pod	default	my-cluster-name
my-cluster-name-rs0-1	✓ Running	Pod	default	my-cluster-name
my-cluster-name-rs0-2	✓ Running	Pod	default	my-cluster-name
percona-server-mongodb-operator-6fc78d686d-26hdz	✓ Running	Pod	default	my-cluster-name

If all nodes are up and running, you can try to connect to the cluster.

First of all, run a container with a MongoDB client and connect its console output to your terminal. The following command will do this, naming the new Pod `percona-client`:

```
kubectl run -i --rm --tty percona-client --image=percona/percona-server-mongodb:4.4.6-8 -
↪-restart=Never -- bash -il
```

Executing it may require some time to deploy the correspondent Pod. Now run `mongo` tool in the `percona-client` command shell using the login (which is `userAdmin`) and password obtained from the secret:

```
mongo "mongodb://userAdmin:userAdminPassword@my-cluster-name-mongos.<namespace name>.svc.
↪cluster.local/admin?ssl=false"
```

4.5 Troubleshooting

If `kubectl get pods` command had shown some errors, you can examine the problematic Pod with the `kubectl describe <pod name>` command. For example, this command returns information for the selected Pod:

```
kubectl describe pod my-cluster-name-rs0-2
```

Review the detailed information for Warning statements and then correct the configuration. An example of a warning is as follows:

Warning FailedScheduling 68s (x4 over 2m22s) default-scheduler 0/1 nodes are available: 1 node(s) didn't match pod affinity/anti-affinity, 1 node(s) didn't satisfy existing pods anti-affinity rules.

Alternatively, you can examine your Pods via the *object browser*. Errors will look as follows:

Name	Status	Type	Namespace	Cluster
▼ core		API Group		
▼ Pod		Kind		
my-cluster-name-cfg-0	✓ Running	Pod	default	my-cluster-name
my-cluster-name-cfg-1	✓ Running	Pod	default	my-cluster-name
my-cluster-name-cfg-2	✓ Running	Pod	default	my-cluster-name
my-cluster-name-mongos-55659468f7-2kvc2	✓ Running	Pod	default	my-cluster-name
my-cluster-name-mongos-55659468f7-7jfqc	✓ Running	Pod	default	my-cluster-name
my-cluster-name-mongos-55659468f7-dlwci	✓ Running	Pod	default	my-cluster-name
my-cluster-name-rs0-0	✓ Running	Pod	default	my-cluster-name
my-cluster-name-rs0-1	✓ Running	Pod	default	my-cluster-name
my-cluster-name-rs0-2	! Unschedulable	Pod	default	my-cluster-name
percona-server-mongodb-operator-6fc78d686d-26hdz	✓ Running	Pod	default	my-cluster-name

Clicking the problematic Pod will bring you to the details page with the same warning:

! my-cluster-name-rs0-2

! 0/2 nodes are available: 2 node(s) didn't match pod affinity/anti-affinity, 2 node(s) didn't satisfy existing pods anti-affinity rules. [Show Details](#)

[Details](#)
[Events](#)
[Logs](#)
[YAML](#)

[1h](#)
[6h](#)
[1d](#)
[7d](#)
[30d](#)

4.6 Removing the GKE cluster

There are several ways that you can delete the cluster.

You can clean up the cluster with the `gcloud` command as follows:

```
gcloud container clusters delete <cluster name>
```

The return statement requests your confirmation of the deletion. Type `y` to confirm.

Also, you can delete your cluster via the GKE console. Just click the **Delete** popup menu item in the clusters list:

☐	✓	my-cluster-name	us-central1-a	3	12	45 GB	—	⋮
								Edit Connect Delete

The cluster deletion may take time.

INSTALL PERCONA SERVER FOR MONGODB ON AMAZON ELASTIC KUBERNETES SERVICE (EKS)

This quickstart shows you how to deploy Percona Distribution for MongoDB Operator on Amazon Elastic Kubernetes Service (EKS). The document assumes some experience with Amazon EKS. For more information on the EKS, see the [Amazon EKS official documentation](#).

5.1 Prerequisites

The following tools are used in this guide and therefore should be preinstalled:

1. **AWS Command Line Interface (AWS CLI)** for interacting with the different parts of AWS. You can install it following the [official installation instructions for your system](#).
2. **eksctl** to simplify cluster creation on EKS. It can be installed along its [installation notes on GitHub](#).
3. **kubectl** to manage and deploy applications on Kubernetes. Install it [following the official installation instructions](#).

Also, you need to configure AWS CLI with your credentials according to the [official guide](#).

5.2 Create the EKS cluster

To create your cluster, you will need the following data:

- name of your EKS cluster,
- AWS region in which you wish to deploy your cluster,
- the amount of nodes you would like to have,
- the desired ratio between [on-demand](#) and [spot](#) instances in the total number of nodes.

Note: [spot](#) instances are not recommended for production environment, but may be useful e.g. for testing purposes.

The most easy and visually clear way is to describe the desired cluster in YAML and to pass this configuration to the `eksctl` command.

The following example configures a EKS cluster with one [managed node group](#):

```
apiVersion: eksctl.io/v1alpha5
kind: ClusterConfig
```

(continues on next page)

(continued from previous page)

```

metadata:
  name: test-cluster
  region: eu-west-2

nodeGroups:
- name: ng-1
  minSize: 3
  maxSize: 5
  instancesDistribution:
    maxPrice: 0.15
    instanceTypes: ["m5.xlarge", "m5.2xlarge"] # At least two instance types should
↪ be specified
    onDemandBaseCapacity: 0
    onDemandPercentageAboveBaseCapacity: 50
    spotInstancePools: 2
  tags:
    'iit-billing-tag': 'cloud'
  preBootstrapCommands:
    - "echo 'OPTIONS=\"--default-ulimit nfile=1048576:1048576\"' >> /etc/
↪ sysconfig/docker"
    - "systemctl restart docker"

```

Note: preBootstrapCommands section is used in the above example to increase the limits for the amount of opened files: this is important and shouldn't be omitted, taking into account the default EKS soft limit of 65536 files.

When the cluster configuration file is ready, you can actually create your cluster by the following command:

```
$ eksctl create cluster -f ~/cluster.yaml
```

5.3 Install the Operator

1. Create a namespace and set the context for the namespace. The resource names must be unique within the namespace and provide a way to divide cluster resources between users spread across multiple projects.

So, create the namespace and save it in the namespace context for subsequent commands as follows (replace the <namespace name> placeholder with some descriptive name):

```

$ kubectl create namespace <namespace name>
$ kubectl config set-context $(kubectl config current-context) --namespace=
↪ <namespace name>

```

At success, you will see the message that namespace/<namespace name> was created, and the context was modified.

2. Use the following `git clone` command to download the correct branch of the percona-server-mongodb-operator repository:

```
git clone -b v1.9.0 https://github.com/percona/percona-server-mongodb-operator
```

After the repository is downloaded, change the directory to run the rest of the commands in this document:


```
cd percona-server-mongodb-operator
```

3. Deploy the Operator with the following command:

```
kubectl apply -f deploy/bundle.yaml
```

The following confirmation is returned:

```
customresourcedefinition.apiextensions.k8s.io/perconaservermongodbbs.psmdb.percona.
↪com created
customresourcedefinition.apiextensions.k8s.io/perconaservermongodbbackups.psmdb.
↪percona.com created
customresourcedefinition.apiextensions.k8s.io/perconaservermongodbrestores.psmdb.
↪percona.com created
role.rbac.authorization.k8s.io/percona-server-mongodb-operator created
serviceaccount/percona-server-mongodb-operator created
rolebinding.rbac.authorization.k8s.io/service-account-percona-server-mongodb-
↪operator created
deployment.apps/percona-server-mongodb-operator created
```

4. The Operator has been started, and you can create the Percona Server for MongoDB:

```
$ kubectl apply -f deploy/cr.yaml
```

The creation process may take some time. The process is over when all Pods have reached their Running status. You can check it with the following command:

```
kubectl get pods
```

The result should look as follows:

NAME	READY	STATUS	RESTARTS	AGE
my-cluster-name-cfg-0	2/2	Running	0	11m
my-cluster-name-cfg-1	2/2	Running	1	10m
my-cluster-name-cfg-2	2/2	Running	1	9m
my-cluster-name-mongos-55659468f7-2kvc2	1/1	Running	0	11m
my-cluster-name-mongos-55659468f7-7jfqc	1/1	Running	0	11m
my-cluster-name-mongos-55659468f7-dfwcj	1/1	Running	0	11m
my-cluster-name-rs0-0	2/2	Running	0	11m
my-cluster-name-rs0-1	2/2	Running	0	10m
my-cluster-name-rs0-2	2/2	Running	0	9m
percona-server-mongodb-operator-6fc78d686d-26hdz	1/1	Running	0	37m

5. During previous steps, the Operator has generated several [secrets](#), including the password for the root user, which you will need to access the cluster.

Use `kubectl get secrets` command to see the list of Secrets objects (by default Secrets object you are interested in has `my-cluster-secrets` name). Then `kubectl get secret my-cluster-secrets -o yaml` will return the YAML file with generated secrets, including the `MONGODB_USER_ADMIN` and `MONGODB_USER_ADMIN_PASSWORD` strings, which should look as follows:

```
...
data:
  ...
```

(continues on next page)

(continued from previous page)

```
MONGODB_USER_ADMIN_PASSWORD: aDAzQ0pCY3NSWEZ2ZUIzS1I=  
MONGODB_USER_ADMIN_USER: dXNlckFkbWlu
```

Here the actual password is base64-encoded, and `echo 'aDAzQ0pCY3NSWEZ2ZUIzS1I=' | base64 --decode` will bring it back to a human-readable form.

6. Check connectivity to a newly created cluster.

First of all, run a container with a MongoDB client and connect its console output to your terminal. The following command will do this, naming the new Pod `percona-client`:

```
kubectl run -i --rm --tty percona-client --image=percona/percona-server-mongodb:4.4.  
↪6-8 --restart=Never -- bash -il
```

Executing it may require some time to deploy the correspondent Pod. Now run `mongo` tool in the `percona-client` command shell using the login (which is `userAdmin`) and password obtained from the secret:

```
mongo "mongodb://userAdmin:userAdminPassword@my-cluster-name-mongos.<namespace name>  
↪.svc.cluster.local/admin?ssl=false"
```

Part III

Advanced Installation Guides

INSTALL PERCONA SERVER FOR MONGODB ON KUBERNETES

1. Clone the percona-server-mongodb-operator repository:

```
git clone -b v1.9.0 https://github.com/percona/percona-server-mongodb-operator
cd percona-server-mongodb-operator
```

Note: It is crucial to specify the right branch with `-b` option while cloning the code on this step. Please be careful.

2. The Custom Resource Definition for Percona Server for MongoDB should be created from the `deploy/crd.yaml` file. The Custom Resource Definition extends the standard set of resources which Kubernetes “knows” about with the new items, in our case these items are the core of the operator.

```
$ kubectl apply -f deploy/crd.yaml
```

This step should be done only once; the step does not need to be repeated with any other Operator deployments.

3. Create a namespace and set the context for the namespace. The resource names must be unique within the namespace and provide a way to divide cluster resources between users spread across multiple projects.

So, create the namespace and save it in the namespace context for subsequent commands as follows (replace the `<namespace name>` placeholder with some descriptive name):

```
$ kubectl create namespace <namespace name>
$ kubectl config set-context $(kubectl config current-context) --namespace=
↪ <namespace name>
```

At success, you will see the message that namespace/`<namespace name>` was created, and the context was modified.

4. The role-based access control (RBAC) for Percona Server for MongoDB is configured with the `deploy/rbac.yaml` file. Role-based access is based on defined roles and the available actions which correspond to each role. The role and actions are defined for Kubernetes resources in the yaml file. Further details about users and roles can be found in [Kubernetes documentation](#).

```
$ kubectl apply -f deploy/rbac.yaml
```

Note: Setting RBAC requires your user to have cluster-admin role privileges. For example, those using Google Kubernetes Engine can grant user needed privileges with the following command:

```
$ kubectl create clusterrolebinding cluster-admin-binding --clusterrole=cluster-
↪ admin --user=$(gcloud config get-value core/account)
```

5. Start the operator within Kubernetes:

```
$ kubectl apply -f deploy/operator.yaml
```

6. Add the MongoDB Users secrets to Kubernetes. These secrets should be placed as plain text in the stringData section of the deploy/secrets.yaml file as login name and passwords for the user accounts (see [Kubernetes documentation](#) for details).

After editing the yaml file, MongoDB Users secrets should be created using the following command:

```
$ kubectl create -f deploy/secrets.yaml
```

More details about secrets can be found in [Users](#).

7. Now certificates should be generated. By default, the Operator generates certificates automatically, and no actions are required at this step. Still, you can generate and apply your own certificates as secrets according to the [TLS instructions](#).
8. After the operator is started, Percona Server for MongoDB cluster can be created with the following command:

```
$ kubectl apply -f deploy/cr.yaml
```

The creation process may take some time. The process is over when all Pods have reached their Running status. You can check it with the following command:

```
$ kubectl get pods
```

The result should look as follows:

NAME	READY	STATUS	RESTARTS	AGE
my-cluster-name-cfg-0	2/2	Running	0	11m
my-cluster-name-cfg-1	2/2	Running	1	10m
my-cluster-name-cfg-2	2/2	Running	1	9m
my-cluster-name-mongos-55659468f7-2kvc2	1/1	Running	0	11m
my-cluster-name-mongos-55659468f7-7jfqc	1/1	Running	0	11m
my-cluster-name-mongos-55659468f7-dfwcj	1/1	Running	0	11m
my-cluster-name-rs0-0	2/2	Running	0	11m
my-cluster-name-rs0-1	2/2	Running	0	10m
my-cluster-name-rs0-2	2/2	Running	0	9m
percona-server-mongodb-operator-6fc78d686d-26hdz	1/1	Running	0	37m

9. Check connectivity to newly created cluster, using the login (which is userAdmin) and corresponding password from the secret:

```
$ kubectl run -i --rm --tty percona-client --image=percona/percona-server-mongodb:4.
→4.6-8 --restart=Never -- bash -il
percona-client:/$ mongo "mongodb://userAdmin:userAdmin123456@my-cluster-name-mongos.
→<namespace>.svc.cluster.local/admin?ssl=false"
```

INSTALL PERCONA SERVER FOR MONGODB ON OPENSIFT

Installing Percona Server for MongoDB on OpenShift includes two steps:

- Installing the Percona Distribution for MongoDB Operator,
- Install Percona Server for MongoDB using the Operator.

7.1 Install the Operator

You can install Percona Distribution for MongoDB Operator on OpenShift using the [Red Hat Marketplace](#) web interface or using the command line interface.

7.1.1 Install the Operator via the Red Hat Marketplace

1. login to the Red Hat Marketplace and register your cluster [following the official instructions](#).
2. Go to the [Percona Distribution for MongoDB Operator](#) page and click the *Free trial* button:

Percona Kubernetes Operator for Percona Server for MongoDB

By Percona

The Kubernetes Operator for MongoDB automates the creation, modification, or deletion of items in your Percona Server for MongoDB environment. The Operator is Red Hat OpenShift Certified.

Software version
1.4.0

Runs on
OpenShift 4.3

Delivery method
Operator

Rating
☆☆☆☆☆ Not rated

Free trial

*Requires [OpenShift](#) to install

Overview

Documentation


Pricing

Help

Based on our best practices for deployment and configuration, Percona Kubernetes Operator contains everything you need to quickly and consistently deploy and scale Percona Server for MongoDB into a Kubernetes cluster. The Operator enables you to: Improve time to market with the ability to quickly deploy standardized and repeatable database environments. Deploy your database with a consistent and idempotent result no matter where they are used.

Here you can “purchase” the Operator for 0.0 USD.

3. When finished, chose Workspace->Software in the system menu on the top and choose the Operator:



Click the Install Operator button.

7.1.2 Install the Operator via the command-line interface

1. Clone the percona-server-mongodb-operator repository:

```
git clone -b v1.9.0 https://github.com/percona/percona-server-mongodb-operator
cd percona-server-mongodb-operator
```

Note: It is crucial to specify the right branch with `-b` option while cloning the code on this step. Please be careful.

2. The Custom Resource Definition for Percona Server for MongoDB should be created from the `deploy/crd.yaml` file. The Custom Resource Definition extends the standard set of resources which Kubernetes “knows” about with the new items, in our case these items are the core of the operator.

This step should be done only once; it does not need to be repeated with other deployments.


```
$ oc apply -f deploy/crd.yaml
```

Note: Setting Custom Resource Definition requires your user to have cluster-admin role privileges.

If you want to manage Percona Server for MongoDB cluster with a non-privileged user, the necessary permissions can be granted by applying the next clusterrole:

```
$ oc create clusterrole psmdb-admin --verb="*" --resource=perconaservermongodbs.
↪psmdb.percona.com,perconaservermongodbs.psmdb.percona.com/status,
↪perconaservermongoddbackups.psmdb.percona.com,perconaservermongoddbackups.psmdb.
↪percona.com/status,perconaservermongoddbrestores.psmdb.percona.com,
↪perconaservermongoddbrestores.psmdb.percona.com/status
$ oc adm policy add-cluster-role-to-user psmdb-admin <some-user>
```

If you have a [cert-manager](#) installed, then you have to execute two more commands to be able to manage certificates with a non-privileged user:

```
$ oc create clusterrole cert-admin --verb="*" --resource=iissuers.certmanager.k8s.
↪io,certificates.certmanager.k8s.io
$ oc adm policy add-cluster-role-to-user cert-admin <some-user>
```

3. Create a new psmdb project:

```
$ oc new-project psmdb
```

4. Add role-based access control (RBAC) for Percona Server for MongoDB is configured with the `deploy/rbac.yaml` file. RBAC is based on clearly defined roles and corresponding allowed actions. These actions are allowed on specific Kubernetes resources. The details about users and roles can be found in [OpenShift documentation](#).

```
$ oc apply -f deploy/rbac.yaml
```

5. Start the Operator within OpenShift:

```
$ oc apply -f deploy/operator.yaml
```

7.2 Install Percona Server for MongoDB

1. Add the MongoDB Users secrets to OpenShift. These secrets should be placed as plain text in the `stringData` section of the `deploy/secrets.yaml` file as login name and passwords for the user accounts (see [Kubernetes documentation](#) for details).

After editing the `yaml` file, the secrets should be created with the following command:

```
$ oc create -f deploy/secrets.yaml
```

More details about secrets can be found in [Users](#).

2. Now certificates should be generated. By default, the Operator generates certificates automatically, and no actions are required at this step. Still, you can generate and apply your own certificates as secrets according to the [TLS instructions](#).
3. Percona Server for MongoDB cluster can be created at any time with the following two steps:

- a. Uncomment the `deploy/cr.yaml` field `#platform:` and edit the field to `platform: openshift`. The result should be like this:

```
apiVersion: psmdb.percona.com/v1alpha1
kind: PerconaServerMongoDB
metadata:
  name: my-cluster-name
spec:
  platform: openshift
...
```

- b. (optional) In you're using minishift, please adjust antiaffinity policy to none

```
affinity:
  antiAffinityTopologyKey: "none"
...
```

- c. Create/apply the CR file:

```
$ oc apply -f deploy/cr.yaml
```

The creation process will take time. The process is complete when all Pods have reached their Running status. You can check it with the following command:

```
$ oc get pods
```

The result should look as follows:

NAME	READY	STATUS	RESTARTS	AGE
my-cluster-name-cfg-0	2/2	Running	0	11m
my-cluster-name-cfg-1	2/2	Running	1	10m
my-cluster-name-cfg-2	2/2	Running	1	9m
my-cluster-name-mongos-55659468f7-2kvc2	1/1	Running	0	11m
my-cluster-name-mongos-55659468f7-7jfqc	1/1	Running	0	11m
my-cluster-name-mongos-55659468f7-dfwcj	1/1	Running	0	11m
my-cluster-name-rs0-0	2/2	Running	0	11m
my-cluster-name-rs0-1	2/2	Running	0	10m
my-cluster-name-rs0-2	2/2	Running	0	9m
percona-server-mongodb-operator-6fc78d686d-26hdz	1/1	Running	0	37m

4. Check connectivity to newly created cluster. Please note that mongo client command shall be executed inside the container manually.

```
$ oc run -i --rm --tty percona-client --image=percona/percona-server-mongodb:4.4.6-
↪8 --restart=Never -- bash -il
percona-client:/$ mongo "mongodb://userAdmin:userAdmin123456@my-cluster-name-mongos.
↪psmdb.svc.cluster.local/admin?ssl=false"
```

USE DOCKER IMAGES FROM A CUSTOM REGISTRY

Using images from a private Docker registry may required for privacy, security or other reasons. In these cases, Percona Distribution for MongoDB Operator allows the use of a custom registry. This following example of the Operator deployed in the OpenShift environment demonstrates the process:

1. Log into the OpenShift and create a project.

```
$ oc login
Authentication required for https://192.168.1.100:8443 (openshift)
Username: admin
Password:
Login successful.
$ oc new-project psmdb
Now using project "psmdb" on server "https://192.168.1.100:8443".
```

2. You need obtain the following objects to configure your custom registry access:

- A user token
- the registry IP address

You can view the token with the following command:

```
$ oc whoami -t
AD08CqCDappWR4hxjFDqwiJEHei31yXAvWg61Jg210s
```

The following command returns the registry IP address:

```
$ kubectl get services/docker-registry -n default
```

NAME	TYPE	CLUSTER-IP	EXTERNAL-IP	PORT(S)	AGE
docker-registry	ClusterIP	172.30.162.173	<none>	5000/TCP	1d

3. Use the user token and the registry IP address to login to the registry:

```
$ docker login -u admin -p AD08CqCDappWR4hxjFDqwiJEHei31yXAvWg61Jg210s 172.30.162.
↪173:5000
Login Succeeded
```

4. Use the Docker commands to pull the needed image by its SHA digest:

```
$ docker pull docker.io/perconalab/percona-server-
↪mongodb@sha256:991d6049059e5eb1a74981290d829a5fb4ab0554993748fde1e67b2f46f26bf0
Trying to pull repository docker.io/perconalab/percona-server-mongodb ...
sha256:991d6049059e5eb1a74981290d829a5fb4ab0554993748fde1e67b2f46f26bf0: Pulling
↪from docker.io/perconalab/percona-server-mongodb
```

(continues on next page)

(continued from previous page)

```
Digest: sha256:991d6049059e5eb1a74981290d829a5fb4ab0554993748fde1e67b2f46f26bf0
Status: Image is up to date for docker.io/perconalab/percona-server-
➔mongodb@sha256:991d6049059e5eb1a74981290d829a5fb4ab0554993748fde1e67b2f46f26bf0
```

You can find correct names and SHA digests in the *current list of the Operator-related images officially certified by Percona*.

- The following method can push an image to the custom registry for the example OpenShift psmdb project:

```
$ docker tag \
  docker.io/perconalab/percona-server-
  ➔mongodb@sha256:991d6049059e5eb1a74981290d829a5fb4ab0554993748fde1e67b2f46f26bf0 \
  172.30.162.173:5000/psmdb/percona-server-mongodb:4.4.6-8
$ docker push 172.30.162.173:5000/psmdb/percona-server-mongodb:4.4.6-8
```

- Verify the image is available in the OpenShift registry with the following command:

```
$ oc get is
NAME                                DOCKER REPO
➔                                TAGS                UPDATED
percona-server-mongodb             docker-registry.default.svc:5000/psmdb/percona-
➔server-mongodb 4.4.6-8 2 hours ago
```

- When the custom registry image is available, edit the the `image:` option in `deploy/operator.yaml` configuration file with a Docker Repo + Tag string (it should look like ``docker-registry.default.svc:5000/psmdb/percona-server-mongodb:4.4.6-8``)

Note: If the registry requires authentication, you can specify the `imagePullSecrets` option for all images.

- Repeat steps 3-5 for other images, and update corresponding options in the `deploy/cr.yaml` file.
- Now follow the standard [Percona Distribution for MongoDB Operator installation instruction](#)

DEPLOY PERCONA SERVER FOR MONGODB WITH SERVICE BROKER

Percona Service Broker provides the [Open Service Broker](#) object to facilitate the operator deployment within high-level visual tools. Following steps are needed to use it while installing the Percona Server for MongoDB on the OpenShift platform:

1. The Percona Service Broker is to be deployed based on the `percona-broker.yaml` file. To use it you should first enable the [Service Catalog](#), which can be done as follows:


```
$ oc patch servicecatalogapiservers cluster --patch '{"spec":{"managementState":  
↪ "Managed"}}' --type=merge  
$ oc patch servicecatalogcontrollermanagers cluster --patch '{"spec":{"  
↪ "managementState":"Managed"}}' --type=merge
```

When Service Catalog is enabled, download and install the Percona Service Broker in a typical OpenShift way:

```
$ oc apply -f https://raw.githubusercontent.com/Percona-Lab/percona-dbaas-cli/  
↪ broker/deploy/percona-broker.yaml
```

Note: This step should be done only once; the step does not need to be repeated with any other Operator deployments. It will automatically create and setup the needed service and projects catalog with all necessary objects.

2. Now login to your [OpenShift Console Web UI](#) and switch to the `percona-service-broker` project. You can check its Pod running on a correspondent page:



Red Hat OpenShift Container Platform

You are logged in as a temporary administrative user. Update the [cluster OAuth configuration](#) to allow others to log in.

Project: percona-service-broker

Pods

Create Pod


Filter Pods by name...

2 Running 0 Pending 0 Terminating 0 CrashLoopBackOff 0 Completed 0 Failed 0 Unknown

Select All Filters 2 of 2 Items

NAME	NAMESPACE	POD LABELS	NODE	STATUS
percona-service-broker-7bbf9599d8-dvqhw	percona-service-broker	app=percona-service-broker, pod-template-hash=7bbf9599d8	ip-10-0-145-63.eu-west-2.compute.internal	Running

Now switch to the Developer Catalog and select Percona Kubernetes Operator for MongoDB:



Developer Catalog

Add shared apps, services, or source-to-image builders to your project from the Developer Catalog. Cluster admins can install additional apps which will show up here automatically.

All Items

12 items

Filter by keyword...

TYPE

☐ Service Class (2)

☐ Source-to-Image (10)

☐ Installed Operators (0)

.NET

.NET Core

Build and run .NET Core 2.2 applications on RHEL 7. For more information about using this builder image, including OpenShift considerations,

Apache HTTP Server (httpd)

Build and serve static content via Apache HTTP Server (httpd) 2.4 on RHEL 7. For more information about using this builder image, including OpenShift considerations,

NGINX

Nginx HTTP server and a reverse proxy (nginx)

Build and serve static content via Nginx HTTP server and a reverse proxy (nginx) on RHEL 7. For more information about using this builder image, including OpenShift considerations,

node

Node.js

Build and run Node.js 10 applications on RHEL 7. For more information about using this builder image, including OpenShift considerations,

PERCONA

Percona Kubernetes Operator for Percona Server for MongoDB

provided by percona

database

PERCONA

Percona XtraDB Cluster Operator

provided by percona

database

Choose Percona Kubernetes Operator for Percona Server for MongoDB item. This will lead you to the Operator page with the *Create Service Instance* button.

3. Clicking the *Create Service Instance* button guides you to the next page:

Create Service Instance

Namespace *

PR percona-service-broker

Service Instance Name *

percona-server-for-mongodb

Plans

standard

percona server for mongodbr

cluster_name *

replicas

size

topology_key

Create

Cancel

**Percona Kubernetes Operator for Percona Server for MongoDB**
Provided by percona
PSMDB
[View Documentation](#)

database
Percona is Cloud Native

The two necessary fields are *Service Instance Name* and *Cluster Name*, which should be unique for your project.

4. Clicking the *Create* button gets you to the *Overview* page, which reflects the process of the cluster creation process:

Project: percona-service-broker ▾
⊕ Add ▾

SI percona-server-for-mongodb1
Actions ▾

Overview
YAML
Events
Service Bindings

Create Service Binding

Service bindings create a secret containing the necessary information for a workload to use SI percona-server-for-mongodb1. Once the binding is ready, add the secret to your workload's environment variables or volumes.

Create Service Binding

Service Instance Overview

NAME	SERVICE CLASS
percona-server-for-mongodb1	CSC percona-server-for-mongodb
NAMESPACE	STATUS
NS percona-service-broker	⌛ NotReady
LABELS	PLAN
No labels	percona-server-for-mongodb
ANNOTATIONS	
0 Annotations ✎	
CREATED AT	
🕒 2 minutes ago	

Conditions

TYPE	STATUS	UPDATED	REASON	MESSAGE
Ready	False	🕒 2 minutes ago	Provisioning	The instance is being provisioned asynchronously (creating service instance...)

You can also track Pods to see when they are deployed and track any errors.

INSTALL PERCONA SERVER FOR MONGODB USING HELM

Helm is the package manager for Kubernetes.

10.1 Pre-requisites

Install Helm following its [official installation instructions](#).

Note: Helm v3 is needed to run the following steps.

10.2 Installation

1. Add the Percona's Helm charts repository and make your Helm client up to date with it:

```
helm repo add percona https://percona.github.io/percona-helm-charts/  
helm repo update
```

2. Install Percona Distribution for MongoDB Operator:

```
helm install my-op percona/psmdb-operator
```

The `my-op` parameter in the above example is the name of a [new release object](#) which is created for the Operator when you install its Helm chart (use any name you like).

Note: If nothing explicitly specified, `helm install` command will work with default namespace. To use different namespace, provide it with the following additional parameter: `--namespace my-namespace`.

3. Install Percona Server for MongoDB:

```
helm install my-db percona/psmdb-db
```

The `my-db` parameter in the above example is the name of a [new release object](#) which is created for the Percona Server for MongoDB when you install its Helm chart (use any name you like).

10.3 Installing Percona Server for MongoDB with customized parameters

The command above installs Percona Server for MongoDB with *default parameters*. Custom options can be passed to a `helm install` command as a `--set key=value[,key=value]` argument. The options passed with a chart can be any of the Operator's *Custom Resource options*.

The following example will deploy a Percona Server for MongoDB Cluster in the `psmdb` namespace, with disabled backups and 20 Gi storage:

```
helm install my-db percona/psmdb-db --namespace psmdb \
  --set replset.volumeSpec.pvc.resources.requests.storage=20Gi \
  --set backup.enabled=false
```

Part IV

Configuration

USERS

MongoDB user accounts within the Cluster can be divided into two different groups:

- *application-level users*: the unprivileged user accounts,
- *system-level users*: the accounts needed to automate the cluster deployment and management tasks, such as MongoDB Health checks.

As these two groups of user accounts serve different purposes, they are considered separately in the following sections.

- *Unprivileged users*
- *System Users*
 - *YAML Object Format*
 - *Password Rotation Policies and Timing*
- *Development Mode*
- *MongoDB Internal Authentication Key (optional)*

11.1 Unprivileged users

There are no unprivileged (general purpose) user accounts created by default. If you need general purpose users, please run commands below:

```
$ kubectl run -i --rm --tty percona-client --image=percona/percona-server-mongodb:4.4.6-
↪8 --restart=Never -- bash -il
mongodb@percona-client:/$ mongo "mongodb+srv://userAdmin:userAdmin123456@my-cluster-name-
↪rs0.psmdb.svc.cluster.local/admin?replicaSet=rs0&ssl=false"
rs0:PRIMARY> db.createUser({
  user: "myApp",
  pwd: "myAppPassword",
  roles: [
    { db: "myApp", role: "readWrite" }
  ],
  mechanisms: [
    "SCRAM-SHA-1"
  ]
})
```

Now check the newly created user:

```
$ kubectl run -i --rm --tty percona-client --image=percona/percona-server-mongodb:4.4.6-
↪8 --restart=Never -- bash -il
mongodb@percona-client:/$ mongo "mongodb+srv://myApp:myAppPassword@my-cluster-name-rs0.
↪psmdb.svc.cluster.local/admin?replicaSet=rs0&ssl=false"
rs0:PRIMARY> use myApp
rs0:PRIMARY> db.test.insert({ x: 1 })
rs0:PRIMARY> db.test.findOne()
```

11.2 System Users

To automate the deployment and management of the cluster components, the Operator requires system-level MongoDB users.

During installation, the Operator requires Kubernetes Secrets to be deployed before the Operator is started. The name of the required secrets can be set in `deploy/cr.yaml` under the `spec.secrets` section.

Default Secret name: `my-cluster-name-secrets`

Secret name field: `spec.secrets.users`

Warning: These users should not be used to run an application.

User Purpose	Username Secret Key	Password Secret Key
Backup/Restore	MONGODB_BACKUP_USER	MONGODB_BACKUP_PASSWORD
Cluster Admin	MONGODB_CLUSTER_ADMIN_USER	MONGODB_CLUSTER_ADMIN_PASSWORD
Cluster Monitor	MONGODB_CLUSTER_MONITOR_USER	MONGODB_CLUSTER_MONITOR_PASSWORD
User Admin	MONGODB_USER_ADMIN_USER	MONGODB_USER_ADMIN_PASSWORD
PMM Server	PMM_SERVER_USER	PMM_SERVER_PASSWORD

Backup/Restore - MongoDB Role: `backup`, `clusterMonitor`, `restore`

Cluster Admin - MongoDB Role: `clusterAdmin`

Cluster Monitor - MongoDB Role: `clusterMonitor`

User Admin - MongoDB Role: `userAdmin`

Note: If you change credentials for the `MONGODB_CLUSTER_MONITOR` user, the cluster Pods will go into restart cycle, and the cluster can be not accessible through the `mongos` service until this cycle finishes.

11.2.1 YAML Object Format

The default name of the Secrets object for these users is `my-cluster-name-secrets` and can be set in the CR for your cluster in `spec.secrets.users` to something different. When you create the object yourself, the corresponding YAML file should match the following simple format:

```
apiVersion: v1
kind: Secret
metadata:
  name: my-cluster-name-secrets
type: Opaque
stringData:
  MONGODB_BACKUP_USER: backup
  MONGODB_BACKUP_PASSWORD: backup123456
  MONGODB_CLUSTER_ADMIN_USER: clusterAdmin
  MONGODB_CLUSTER_ADMIN_PASSWORD: clusterAdmin123456
  MONGODB_CLUSTER_MONITOR_USER: clusterMonitor
  MONGODB_CLUSTER_MONITOR_PASSWORD: clusterMonitor123456
  MONGODB_USER_ADMIN_USER: userAdmin
  MONGODB_USER_ADMIN_PASSWORD: userAdmin123456
  PMM_SERVER_USER: pmm
  PMM_SERVER_PASSWORD: supa|^|pazz
```

The example above matches *what is shipped in `deploy/secrets.yaml`* which contains default passwords. You should NOT use these in production, but they are present to assist in automated testing or simple use in a development environment.

As you can see, because we use the `stringData` type when creating the Secrets object, all values for each key/value pair are stated in plain text format convenient from the user's point of view. But the resulting Secrets object contains passwords stored as data - i.e., base64-encoded strings. If you want to update any field, you'll need to encode the value into base64 format. To do this, you can run `echo -n "password" | base64` in your local shell to get valid values. For example, setting the PMM Server user's password to `new_password` in the `my-cluster-name-secrets` object can be done with the following command:

```
kubectl patch secret/my-cluster-name-secrets -p '{"data":{"PMM_SERVER_PASSWORD": "'
↪$(echo -n new_password | base64)'"}}'
```

Note: The operator creates and updates an additional Secrets object named based on the cluster name, like `internal-my-cluster-name-users`. It is used only by the Operator and should undergo no manual changes by the user. This object contains secrets with the same passwords as the one specified in `spec.secrets.users` (e.g. `my-cluster-name-secrets`). When the user updates `my-cluster-name-secrets`, the Operator propagates these changes to the internal `internal-my-cluster-name-users` Secrets object.

11.2.2 Password Rotation Policies and Timing

When there is a change in user secrets, the Operator creates the necessary transaction to change passwords. This rotation happens almost instantly (the delay can be up to a few seconds), and it's not needed to take any action beyond changing the password.

Note: Please don't change `secrets.users` option in CR, make changes inside the secrets object itself.

11.3 Development Mode

To make development and testing easier, `deploy/secrets.yaml` secrets file contains default passwords for MongoDB system users.

These development-mode credentials from `deploy/secrets.yaml` are:

Secret Key	Secret Value
MONGODB_BACKUP_USER	backup
MONGODB_BACKUP_PASSWORD	backup123456
MONGODB_CLUSTER_ADMIN_USER	clusterAdmin
MONGODB_CLUSTER_ADMIN_PASSWORD	clusterAdmin123456
MONGODB_CLUSTER_MONITOR_USER	clusterMonitor
MONGODB_CLUSTER_MONITOR_PASSWORD	clusterMonitor123456
MONGODB_USER_ADMIN_USER	userAdmin
MONGODB_USER_ADMIN_PASSWORD	userAdmin123456
PMM_SERVER_USER	pmm
PMM_SERVER_PASSWORD	supa ^ pazz

Warning: Do not use the default MongoDB Users in production!

11.4 MongoDB Internal Authentication Key (optional)

Default Secret name: `my-cluster-name-mongodb-key`

Secret name field: `spec.secrets.key`

By default, the operator will create a random, 1024-byte key for [MongoDB Internal Authentication](#) if it does not already exist. If you would like to deploy a different key, create the secret manually before starting the operator.

LOCAL STORAGE SUPPORT FOR THE PERCONA DISTRIBUTION FOR MONGODB OPERATOR

Among the wide range of volume types, supported by Kubernetes, there are two volume types which allow Pod containers to access part of the local filesystem on the node the *emptyDir* and *hostPath*.

12.1 emptyDir

A Pod *emptyDir* volume is created when the Pod is assigned to a Node. The volume is initially empty and is erased when the Pod is removed from the Node. The containers in the Pod can read and write the files in the emptyDir volume.

The emptyDir options in the *deploy/cr.yaml* file can be used to turn the emptyDir volume on by setting the directory name.

The emptyDir is useful when you use *Percona Memory Engine*.

12.2 hostPath

A *hostPath* volume mounts an existing file or directory from the host node's filesystem into the Pod. If the pod is removed, the data persists in the host node's filesystem.

The *volumeSpec.hostPath* subsection in the *deploy/cr.yaml* file may include *path* and *type* keys to set the node's filesystem object path and to specify whether it is a file, a directory, or something else (e.g. a socket):

```
volumeSpec:
  hostPath:
    path: /data
    type: Directory
```

Please note, you must create the hostPath manually and should have the following attributes:

- access permissions
- ownership
- SELinux security context

The *hostPath* volume is useful when you perform manual actions during the first run and require improved disk performance. Consider using the tolerations settings to avoid a cluster migration to different hardware in case of a reboot or a hardware failure.

More details can be found in the [official hostPath Kubernetes documentation](#).

BINDING PERCONA SERVER FOR MONGODB COMPONENTS TO SPECIFIC KUBERNETES/OPENSIFT NODES

The operator does a good job of automatically assigning new pods to nodes to achieve balanced distribution across the cluster. There are situations when you must ensure that pods land on specific nodes: for example, for the advantage of speed on an SSD-equipped machine, or reduce costs by choosing nodes in the same availability zone.

The appropriate (sub)sections (`replsets`, `replsets.arbiter`, `backup`, etc.) of the `deploy/cr.yaml` file contain the keys which can be used to do assign pods to nodes.

13.1 Node selector

The `nodeSelector` contains one or more key-value pairs. If the node is not labeled with each key-value pair from the Pod's `nodeSelector`, the Pod will not be able to land on it.

The following example binds the Pod to any node having a self-explanatory `disktype: ssd` label:

```
nodeSelector:
  disktype: ssd
```

13.2 Affinity and anti-affinity

Affinity defines eligible pods that can be scheduled on the node which already has pods with specific labels. Anti-affinity defines pods that are not eligible. This approach is reduces costs by ensuring several pods with intensive data exchange occupy the same availability zone or even the same node or, on the contrary, to spread the pods on different nodes or even different availability zones for high availability and balancing purposes.

Percona Distribution for MongoDB Operator provides two approaches for doing this:

- simple way to set anti-affinity for Pods, built-in into the Operator,
- more advanced approach based on using standard Kubernetes constraints.

13.2.1 Simple approach - use antiAffinityTopologyKey of the Percona Distribution for MongoDB Operator

Percona Distribution for MongoDB Operator provides an `antiAffinityTopologyKey` option, which may have one of the following values:

- `kubernetes.io/hostname` - Pods will avoid residing within the same host,
- `failure-domain.beta.kubernetes.io/zone` - Pods will avoid residing within the same zone,
- `failure-domain.beta.kubernetes.io/region` - Pods will avoid residing within the same region,
- `none` - no constraints are applied.

The following example forces Percona Server for MongoDB Pods to avoid occupying the same node:

```
affinity:
  antiAffinityTopologyKey: "kubernetes.io/hostname"
```

13.2.2 Advanced approach - use standard Kubernetes constraints

The previous method can be used without special knowledge of the Kubernetes way of assigning Pods to specific nodes. Still, in some cases, more complex tuning may be needed. In this case, the advanced option placed in the `deploy/cr.yaml` file turns off the effect of the `antiAffinityTopologyKey` and allows the use of the standard Kubernetes affinity constraints of any complexity:

```
affinity:
  advanced:
    podAffinity:
      requiredDuringSchedulingIgnoredDuringExecution:
        - labelSelector:
            matchExpressions:
              - key: security
                operator: In
                values:
                  - S1
            topologyKey: failure-domain.beta.kubernetes.io/zone
    podAntiAffinity:
      preferredDuringSchedulingIgnoredDuringExecution:
        - weight: 100
          podAffinityTerm:
            labelSelector:
              matchExpressions:
                - key: security
                  operator: In
                  values:
                    - S2
            topologyKey: kubernetes.io/hostname
    nodeAffinity:
      requiredDuringSchedulingIgnoredDuringExecution:
        nodeSelectorTerms:
          - matchExpressions:
              - key: kubernetes.io/e2e-az-name
                operator: In
```

(continues on next page)

(continued from previous page)

```

      values:
      - e2e-az1
      - e2e-az2
    preferredDuringSchedulingIgnoredDuringExecution:
    - weight: 1
      preference:
        matchExpressions:
        - key: another-node-label-key
          operator: In
          values:
          - another-node-label-value

```

See explanation of the advanced affinity options in [Kubernetes documentation](#).

13.3 Tolerations

Tolerations allow Pods having them to be able to land onto nodes with matching *taints*. Tolerations are expressed as a key with an operator, which is either `exists` or `equal` (the `equal` variant requires a corresponding value for comparison).

Tolerations should have a specified effect, such as the following:

- `NoSchedule` - less strict
- `PreferNoSchedule`
- `NoExecute`

When a *taint* with the `NoExecute` effect is assigned to a node, any pod configured to not tolerating this *taint* is removed from the node. This removal can be immediate or after the `tolerationSeconds` interval. The following example defines this effect and the removal interval:

```

tolerations:
- key: "node.alpha.kubernetes.io/unreachable"
  operator: "Exists"
  effect: "NoExecute"
  tolerationSeconds: 6000

```

The [Kubernetes Taints and Tolerations](#) contains more examples on this topic.

13.4 Priority Classes

Pods may belong to some *priority classes*. This flexibility allows the scheduler to distinguish more and less important Pods when needed, such as the situation when a higher priority Pod cannot be scheduled without evicting a lower priority one. This ability can be accomplished by adding one or more `PriorityClasses` in your Kubernetes cluster, and specifying the `PriorityClassName` in the `deploy/cr.yaml` file:

```
priorityClassName: high-priority
```

See the [Kubernetes Pods Priority and Preemption](#) documentation to find out how to define and use priority classes in your cluster.

13.5 Pod Disruption Budgets

Creating the [Pod Disruption Budget](#) is the Kubernetes method to limit the number of Pods of an application that can go down simultaneously due to *voluntary disruptions* such as the cluster administrator's actions during a deployment update. Distribution Budgets allow large applications to retain their high availability during maintenance and other administrative activities. The `maxUnavailable` and `minAvailable` options in the `deploy/cr.yaml` file can be used to set these limits. The recommended variant is the following:

```
podDisruptionBudget:  
  maxUnavailable: 1
```

CHANGING MONGODB OPTIONS

You may require a configuration change for your application. MongoDB allows configuring the database with a configuration file, as many other database management systems do. You can pass options to MongoDB instances in the cluster in one of the following ways:

- edit the `deploy/cr.yaml` file,
- use a ConfigMap,
- use a Secret object.

You can pass configuration settings separately for **mongod** Pods, **mongos** Pods, and **Config Server** Pods.

14.1 Edit the `deploy/cr.yaml` file

You can add MongoDB configuration options to the `replsets.configuration`, `sharding.mongos.configuration`, and `sharding-configsvrreplset-configuration` keys of the `deploy/cr.yaml`. Here is an example:

```
spec:
  ...
  replsets:
    - name: rs0
      size: 3
      configuration: |
        operationProfiling:
          mode: slowOp
        systemLog:
          verbosity: 1
    ...
```

See the [official manual](#) for the complete list of options, as well as [specific Percona Server for MongoDB documentation](#) pages.

14.2 Use a ConfigMap

You can use a [ConfigMap](#) and the cluster restart to reset configuration options. A ConfigMap allows Kubernetes to pass or update configuration data inside a containerized application.

You should give the ConfigMap a specific name, which is composed of your cluster name and a specific suffix:

- `my-cluster-name-rs0-mongod` for the Replica Set (mongod) Pods,
- `my-cluster-name-cfg-mongod` for the Config Server Pods,
- `my-cluster-name-mongos` for the mongos Pods,

Note: To find the cluster name, you can use the following command:

```
$ kubectl get psmdb
```

For example, let's define a `mongod.conf` configuration file and put there several MongoDB options we used in the previous example:

```
operationProfiling:
  mode: slowOp
systemLog:
  verbosity: 1
```

You can create a ConfigMap from the `mongod.conf` file with the `kubectl create configmap` command. It has the following syntax:

```
kubectl create configmap <configmap-name> <resource-type=resource-name>
```

The following example defines `my-cluster-name-rs0-mongod` as the ConfigMap name and the `mongod.conf` file as the data source:

```
$ kubectl create configmap my-cluster-name-rs0-mongod --from-file=mongod.conf=mongod.conf
```

To view the created ConfigMap, use the following command:

```
$ kubectl describe configmaps my-cluster-name-rs0-mongod
```

Note: Do not forget to restart Percona Server for MongoDB to ensure the cluster has updated the configuration (see details on how to connect in the [Install Percona Server for MongoDB on Kubernetes](#) page).

14.3 Use a Secret Object

The Operator can also store configuration options in [Kubernetes Secrets](#). This can be useful if you need additional protection for some sensitive data.

You should create a Secret object with a specific name, composed of your cluster name and a specific suffix:

- `my-cluster-name-rs0-mongod` for the Replica Set Pods,
- `my-cluster-name-cfg-mongod` for the Config Server Pods,

- `my-cluster-name-mongos` for the mongos Pods,

Note: To find the cluster name, you can use the following command:

```
$ kubectl get psmdb
```

Configuration options should be put inside a specific key:

- `data.mongod` key for Replica Set (mongod) and Config Server Pods,
- `data.mongos` key for mongos Pods.

Actual options should be encoded with [Base64](#).

For example, let's define a `mongod.conf` configuration file and put there several MongoDB options we used in the previous example:

```
operationProfiling:
  mode: slowOp
systemLog:
  verbosity: 1
```

You can get a Base64 encoded string from your options via the command line as follows:

```
$ cat mongod.conf | base64
```

Note: Similarly, you can read the list of options from a Base64 encoded string:

```
$ echo "ICAgICAgb3BlcmF0aW9uUHJvZmlsaW5nOgogICAgICAgIG1vZGU6IHNSb3dPc\
AogICAgICBzeXN0ZW1Mb2c6CiAgICAgICAgdmVyYm9zaXR5OXAxCg==" | base64 --decode
```

Finally, use a yaml file to create the Secret object. For example, you can create a `deploy/my-mongod-secret.yaml` file with the following contents:

```
apiVersion: v1
kind: Secret
metadata:
  name: my-cluster-name-rs0-mongod
data:
  mongod.conf: "ICAgICAgb3BlcmF0aW9uUHJvZmlsaW5nOgogICAgICAgIG1vZGU6IHNSb3dPc\
AogICAgICBzeXN0ZW1Mb2c6CiAgICAgICAgdmVyYm9zaXR5OXAxCg=="
```

When ready, apply it with the following command:

```
$ kubectl create -f deploy/my-mongod-secret.yaml
```


Note: Do not forget to restart Percona Server for MongoDB to ensure the cluster has updated the configuration (see details on how to connect in the [Install Percona Server for MongoDB on Kubernetes](#) page).

EXPOSING CLUSTER NODES WITH DEDICATED IP ADDRESSES


15.1 Using single entry point vs. accessing MongoDB Instances

Percona Distribution for MongoDB Operator provides two scenarios for accessing the database.

1. If *Percona Server for MongoDB Sharding* mode is turned **on** (default behaviour), then database cluster runs special mongos Pods - query routers, which acts as an entry point for client applications,



2. If *Percona Server for MongoDB Sharding* mode is turned **off**, the application needs access to all MongoDB Pods of the replica set:



You can find more on sharding in the [official MongoDB documentation](#).

15.2 Accessing the Pod

When Kubernetes creates Pods, each Pod has an IP address in the internal virtual network of the cluster. Creating and destroying Pods is a dynamic process, therefore binding communication between Pods to specific IP addresses would cause problems as things change over time as a result of the cluster scaling, maintenance, etc. Due to this changing environment, you should connect to Percona Server for MongoDB via Kubernetes internal DNS names in URI (e.g. using `mongodb+srv://userAdmin:userAdmin123456@<cluster-name>-rs0.<namespace>.svc.cluster.local/admin?replicaSet=rs0&ssl=false` to access one of the Replica Set Pods). URI-based access is strictly recommended.

Sometimes you cannot communicate with the Pods using the Kubernetes internal DNS names. To make Pods of the Replica Set accessible, Percona Distribution for MongoDB Operator can assign a [Kubernetes Service](#) to each Pod.

This feature can be configured in the `replsets` (for MongoDB instances Pod) and `sharding` (for mongos Pod) sections of the `deploy/cr.yaml` file:

- set 'expose.enabled' option to 'true' to allow exposing Pods via services,
- set 'expose.exposeType' option specifying the IP address type to be used:
 - **ClusterIP** - expose the Pod's service with an internal static IP address. This variant makes MongoDB Pod only reachable from within the Kubernetes cluster.
 - **NodePort** - expose the Pod's service on each Kubernetes node's IP address at a static port. ClusterIP service, to which the node port will be routed, is automatically created in this variant. As an advantage, the service will be reachable from outside the cluster by node address and port number, but the address will be bound to a specific Kubernetes node.
 - **LoadBalancer** - expose the Pod's service externally using a cloud provider's load balancer. Both ClusterIP and NodePort services are automatically created in this variant.

If this feature is enabled, URI looks like `mongodb://userAdmin:userAdmin123456@<ip1>:<port1>,<ip2>:<port2>,<ip3>:<port3>/admin?replicaSet=rs0&ssl=false`. All IP addresses should be *directly* reachable by application.

ENABLING REPLICA SET ARBITER NODES

Percona Server for MongoDB [replication model](#) is based on elections, when nodes of the Replica Set [choose which node](#) becomes the primary node. Elections are the reason to avoid an even number of nodes in the cluster. The cluster should have at least three nodes. Normally, each node stores a complete copy of the data, but there is also a possibility, to reduce disk IO and space used by the database, to add an [arbiter node](#). An arbiter cannot become a primary and does not have a complete copy of the data. The arbiter does have one election vote and can be the odd number for elections. The arbiter does not demand a persistent volume.

Percona Distribution for MongoDB Operator has the ability to create Replica Set Arbiter nodes if needed. This feature can be configured in the Replica Set section of the [deploy/cr.yaml](#) file:

- set `arbiter.enabled` option to `true` to allow Arbiter instances,
- use `arbiter.size` option to set the desired amount of Arbiter instances.

For example, the following keys in `deploy/cr.yaml` will create a cluster with 4 data instances and 1 Arbiter:

```
....
replsets:
  ....
  size: 4
  ....
  arbiter:
    enabled: true
    size: 1
  ....
```


PERCONA SERVER FOR MONGODB SHARDING

17.1 About sharding

Sharding provides horizontal database scaling, distributing data across multiple MongoDB Pods. It is useful for large data sets when a single machine's overall processing speed or storage capacity turns out to be not enough. Sharding allows splitting data across several machines with a special routing of each request to the necessary subset of data (so-called *shard*).

A MongoDB Sharding involves the following components:

- **shard** - a replica set which contains a subset of data stored in the database (similar to a traditional MongoDB replica set),
- **mongos** - a query router, which acts as an entry point for client applications,
- **config servers** - a replica set to store metadata and configuration settings for the sharded database cluster.

Note: Percona Distribution for MongoDB Operator 1.6.0 supported only one shard of a MongoDB cluster; still, this limited sharding support allowed using **mongos** as an entry point instead of provisioning a load-balancer per replica set node. Multiple shards are supported starting from the Operator 1.7.0.

17.2 Turning sharding on and off

Sharding is controlled by the **sharding** section of the `deploy/cr.yaml` configuration file and is turned on by default.

To enable sharding, set the **sharding.enabled** key to **true** (this will turn existing MongoDB replica set nodes into sharded ones). To disable sharding, set the **sharding.enabled** key to **false**.

When sharding is turned on, the Operator runs replica sets with config servers and mongos instances. Their number is controlled by **configsvrRepSet.size** and **mongos.size** keys, respectively.

Note: Config servers for now can properly work only with WiredTiger engine, and sharded MongoDB nodes can use either WiredTiger or InMemory one.

By default **replsets** section of the `deploy/cr.yaml` configuration file contains only one replica set, **rs0**. You can add more replica sets with different names to the **replsets** section in a similar way. Please take into account that having more than one replica set is possible only with the sharding turned on.

17.3 Checking connectivity to sharded and non-sharded cluster

With sharding turned on, you have mongos service as an entry point to access your database. If you do not use sharding, you have to access mongod processes of your replica set.

1. Run percona-client and connect its console output to your terminal (running it may require some time to deploy the corresponding Pod):

```
kubectl run -i --rm --tty percona-client --image=percona/percona-server-mongodb:4.4.
↪6-8 --restart=Never -- bash -il
```

2. Find the password for the admin user, which you will need to access the cluster. Use `kubectl get secrets` to see the list of Secrets objects (by default Secrets object you are interested in has `my-cluster-name-secrets` name). Then `kubectl get secret my-cluster-name-secrets -o yaml` will return the YAML file with generated secrets, including the `MONGODB_USER_ADMIN` and `MONGODB_USER_ADMIN_PASSWORD` strings:

```
...
data:
  ...
  MONGODB_USER_ADMIN_PASSWORD: aDAzQ0pCY3NSWEZ2ZUIzS1I=
  MONGODB_USER_ADMIN_USER: dXNlckFkbWlu
```

Here the actual login name and password are base64-encoded, and `echo 'aDAzQ0pCY3NSWEZ2ZUIzS1I=' | base64 --decode` will bring it back to a human-readable form.

3. Now run mongo tool in the percona-client command shell using the login (which is normally `userAdmin`) and password obtained from the secret.

- If sharding is turned on, the command will look as follows (with your database cluster namespace instead of the `<namespace name>` placeholder).

```
mongo "mongodb://userAdmin:userAdminPassword@my-cluster-name-mongos.<namespace_
↪name>.svc.cluster.local/admin?ssl=false"
```

- If sharding is turned off, the command will look as follows (with your database cluster namespace instead of the `<namespace name>` placeholder).

```
mongo "mongodb+srv://userAdmin:userAdminPassword@my-cluster-name-rs0.<namespace_
↪name>.svc.cluster.local/admin?replicaSet=rs0&ssl=false"
```


TRANSPORT LAYER SECURITY (TLS)

The Percona Distribution for MongoDB Operator uses Transport Layer Security (TLS) cryptographic protocol for the following types of communication:

- Internal - communication between Percona Server for MongoDB instances in the cluster
- External - communication between the client application and the cluster

The internal certificate is also used as an authorization method.

TLS security can be configured in several ways. By default, the Operator generates certificates automatically if there are no certificate secrets available. Other options are the following ones:

- The Operator can use a specifically installed *cert-manager* for the automatic certificates generation,
- Certificates can be generated manually.

You can also use pre-generated certificates available in the `deploy/ssl-secrets.yaml` file for test purposes, but we strongly recommend **avoiding their usage on any production system!**

The following subsections explain how to configure TLS security with the Operator yourself, as well as how to temporarily disable it if needed.

- *Install and use the cert-manager*
 - *About the cert-manager*
 - *Installation of the cert-manager*
- *Generate certificates manually*
- *Run Percona Server for MongoDB without TLS*

18.1 Install and use the *cert-manager*

18.1.1 About the *cert-manager*

A *cert-manager* is a Kubernetes certificate management controller which widely used to automate the management and issuance of TLS certificates. It is community-driven, and open source.

When you have already installed *cert-manager* and deploy the operator, the operator requests a certificate from the *cert-manager*. The *cert-manager* acts as a self-signed issuer and generates certificates. The Percona Operator self-signed issuer is local to the operator namespace. This self-signed issuer is created because Percona Server for MongoDB requires all certificates are issued by the same CA.

The creation of the self-signed issuer allows you to deploy and use the Percona Operator without creating a cluster issuer separately.

18.1.2 Installation of the *cert-manager*

The steps to install the *cert-manager* are the following:

- Create a namespace
- Disable resource validations on the cert-manager namespace
- Install the cert-manager.

The following commands perform all the needed actions:

```
kubectl apply -f https://github.com/jetstack/cert-manager/releases/download/v0.15.1/cert-
manager.yaml --validate=false
```

After the installation, you can verify the *cert-manager* by running the following command:

```
kubectl get pods -n cert-manager
```

The result should display the *cert-manager* and webhook active and running.

18.2 Generate certificates manually

To generate certificates manually, follow these steps:

1. Provision a Certificate Authority (CA) to generate TLS certificates
2. Generate a CA key and certificate file with the server details
3. Create the server TLS certificates using the CA keys, certs, and server details

The set of commands generate certificates with the following attributes:

- `Server-pem` - Certificate
- `Server-key.pem` - the private key
- `ca.pem` - Certificate Authority

You should generate certificates twice: one set is for external communications, and another set is for internal ones. A secret created for the external use must be added to the `spec.secrets.ssl` key of the `deploy/cr.yaml` file. A certificate generated for internal communications must be added to the `spec.secrets.sslInternal` key of the `deploy/cr.yaml` file.

Supposing that your cluster name is `my-cluster-name-rs0`, the instructions to generate certificates manually are as follows:

```
CLUSTER_NAME=my-cluster-name
NAMESPACE=default
cat <<EOF | cfssl gencert -initca - | cfssljson -bare ca
{
  "CN": "Root CA",
  "names": [
    {
      "O": "PSMDB"
```

(continues on next page)

(continued from previous page)

```

    }
  ],
  "key": {
    "algo": "rsa",
    "size": 2048
  }
}
EOF

cat <<EOF > ca-config.json
{
  "signing": {
    "default": {
      "expiry": "87600h",
      "usages": ["signing", "key encipherment", "server auth", "client auth"]
    }
  }
}
EOF

cat <<EOF | cfssl gencert -ca=ca.pem -ca-key=ca-key.pem -config=./ca-config.json - |
↪cfssljson -bare server
{
  "hosts": [
    "localhost",
    "${CLUSTER_NAME}-rs0",
    "${CLUSTER_NAME}-rs0.${NAMESPACE}",
    "${CLUSTER_NAME}-rs0.${NAMESPACE}.svc.cluster.local",
    *.${CLUSTER_NAME}-rs0",
    *.${CLUSTER_NAME}-rs0.${NAMESPACE}",
    *.${CLUSTER_NAME}-rs0.${NAMESPACE}.svc.cluster.local"
  ],
  "names": [
    {
      "O": "PSMDB"
    }
  ],
  "CN": "${CLUSTER_NAME}/-rs0",
  "key": {
    "algo": "rsa",
    "size": 2048
  }
}
EOF
cfssl bundle -ca-bundle=ca.pem -cert=server.pem | cfssljson -bare server

kubectl create secret generic my-cluster-name-ssl-internal --from-file=tls.crt=server.
↪pem --from-file=tls.key=server-key.pem --from-file=ca.crt=ca.pem --type=kubernetes.io/
↪tls

cat <<EOF | cfssl gencert -ca=ca.pem -ca-key=ca-key.pem -config=./ca-config.json - |
↪cfssljson -bare client

```

(continues on next page)

(continued from previous page)

```

{
  "hosts": [
    "${CLUSTER_NAME}-rs0",
    "${CLUSTER_NAME}-rs0.${NAMESPACE}",
    "${CLUSTER_NAME}-rs0.${NAMESPACE}.svc.cluster.local",
    "${CLUSTER_NAME}-rs0",
    "${CLUSTER_NAME}-rs0.${NAMESPACE}",
    "${CLUSTER_NAME}-rs0.${NAMESPACE}.svc.cluster.local"
  ],
  "names": [
    {
      "O": "PSMDB"
    }
  ],
  "CN": "${CLUSTER_NAME}/-rs0",
  "key": {
    "algo": "rsa",
    "size": 2048
  }
}
EOF

kubectl create secret generic my-cluster-name-ssl --from-file=tls.crt=client.pem --from-
↪file=tls.key=client-key.pem --from-file=ca.crt=ca.pem --type=kubernetes.io/tls

```

18.3 Run Percona Server for MongoDB without TLS

Omitting TLS is also possible, but we recommend that you run your cluster with the TLS protocol enabled.

To disable TLS protocol (e.g. for demonstration purposes) set the `spec.allowUnsafeConfigurations` key to `true` in the `deploy/cr.yaml` file and make sure that there are no certificate secrets available.

DATA AT REST ENCRYPTION

Data at rest encryption in Percona Server for MongoDB is supported by the Operator since version 1.1.0.

Note: “Data at rest” means inactive data stored as files, database records, etc.

Following options the `mongod` section of the `deploy/cr.yaml` file should be edited to turn this feature on:

1. The `security.enableEncryption` key should be set to `true` (the default value).
2. The `security.encryptionCipherMode` key should specify proper cipher mode for decryption. The value can be one of the following two variants:
 - AES256-CBC (the default one for the Operator and Percona Server for MongoDB)
 - AES256-GCM
3. `security.encryptionKeySecret` should specify a secret object with the encryption key:

```
mongod:
  ...
  security:
    ...
    encryptionKeySecret: my-cluster-name-mongodb-encryption-key
```


Encryption key secret will be created automatically if it doesn't exist. If you would like to create it yourself, take into account that the key must be a 32 character string encoded in base64.

Part V

Management

PROVIDING BACKUPS

The Operator usually stores Server for MongoDB backups on [Amazon S3](#) or [S3-compatible storage](#) outside the Kubernetes cluster:



The Operator allows doing cluster backup in two ways. *Scheduled backups* are configured in the `deploy/cr.yaml` file to be executed automatically in proper time. *On-demand backups* can be done manually at any moment. Both ways use the [Percona Backup for MongoDB](#) tool.

- *Making scheduled backups*
- *Making on-demand backup*
- *Storing operations logs for point-in-time recovery*
- *Restore the cluster from a previously saved backup*
 - *Restoring without point-in-time recovery*
 - *Restoring backup with point-in-time recovery*
- *Delete the unneeded backup*

20.1 Making scheduled backups

Since backups are stored separately on the Amazon S3, a secret with `AWS_ACCESS_KEY_ID` and `AWS_SECRET_ACCESS_KEY` should be present on the Kubernetes cluster. The secrets file with these base64-encoded keys should be created: for example `deploy/backup-s3.yaml` file with the following contents.

```
apiVersion: v1
kind: Secret
metadata:
  name: my-cluster-name-backup-s3
type: Opaque
data:
  AWS_ACCESS_KEY_ID: UkVQTEFDRS1XSVRILUFxUy1BQ0NFU1MtS0VZ
  AWS_SECRET_ACCESS_KEY: UkVQTEFDRS1XSVRILUFxUy1TRUNSRVQtS0VZ
```

Note: The following command can be used to get a base64-encoded string from a plain text one: `$ echo -n 'plain-text-string' | base64`

The name value is the [Kubernetes secret](#) name which will be used further, and `AWS_ACCESS_KEY_ID` and `AWS_SECRET_ACCESS_KEY` are the keys to access S3 storage (and obviously they should contain proper values to make this access possible). To have effect secrets file should be applied with the appropriate command to create the secret object, e.g. `kubectl apply -f deploy/backup-s3.yaml` (for Kubernetes).

Backups schedule is defined in the backup section of the `deploy/cr.yaml` file. This section contains following subsections:

- `storages` subsection contains data needed to access the S3-compatible cloud to store backups.
- `tasks` subsection allows to actually schedule backups (the schedule is specified in crontab format).

Here is an example of `deploy/cr.yaml` which uses Amazon S3 storage for backups:

```
...
backup:
  enabled: true
  ...
  storages:
    s3-us-west:
      type: s3
      s3:
```

(continues on next page)

(continued from previous page)

```

    bucket: S3-BACKUP-BUCKET-NAME-HERE
    region: us-west-2
    credentialsSecret: my-cluster-name-backup-s3
  ...
  tasks:
  - name: "sat-night-backup"
    schedule: "0 0 * * 6"
    keep: 3
    storageName: s3-us-west
  ...

```

if you use some S3-compatible storage instead of the original Amazon S3, the `endpointURL` is needed in the `s3` subsection which points to the actual cloud used for backups and is specific to the cloud provider. For example, using [Google Cloud](#) involves the following `endpointUrl`:

```
endpointUrl: https://storage.googleapis.com
```

The options within these three subsections are further explained in the *Operator Custom Resource options*.

One option which should be mentioned separately is `credentialsSecret` which is a [Kubernetes secret](#) for backups. Value of this key should be the same as the name used to create the secret object (`my-cluster-name-backup-s3` in the last example).

The schedule is specified in crontab format as explained in *Operator Custom Resource options*.

20.2 Making on-demand backup

To make an on-demand backup, the user should first configure the backup storage in the `backup.storages` subsection of the `deploy/cr.yaml` configuration file in a same way it was done for scheduled backups. When the `deploy/cr.yaml` file contains correctly configured storage and is applied with `kubectl` command, use a *special backup configuration YAML file* with the following contents:

- **backup name** in the `metadata.name` key,
- **Percona Server for MongoDB Cluster name** in the `spec.psmdbCluster` key,
- **storage name** from `deploy/cr.yaml` in the `spec.storageName` key.

The example of such file is

`deploy/backup/backup.yaml`.

When the backup destination is configured and applied with `kubectl apply -f deploy/cr.yaml` command, the actual backup command is executed:

```
kubectl apply -f deploy/backup/backup.yaml
```

Note: Storing backup settings in a separate file can be replaced by passing its content to the `kubectl apply` command as follows:

```

cat <<EOF | kubectl apply -f-
apiVersion: psmdb.percona.com/v1
kind: PerconaServerMongoDBBackup
metadata:

```

(continues on next page)

(continued from previous page)

```
name: backup1
spec:
  psmdbCluster: my-cluster-name
  storageName: s3-us-west
EOF
```

20.3 Storing operations logs for point-in-time recovery

Point-in-time recovery functionality allows users to roll back the cluster to a specific date and time. Technically, this feature involves saving operations log updates to the S3-compatible backup storage.

To be used, it requires setting the `backup.pitr.enabled` key in the `deploy/cr.yaml` configuration file:

```
backup:
  ...
  pitr:
    enabled: true
```

Note: It is necessary to have at least one full backup to use point-in-time recovery. Percona Backup for MongoDB will not upload operations logs if there is no full backup. This is true for new clusters and also true for clusters which have been just recovered from backup.

Percona Backup for MongoDB uploads operations logs to the same bucket where full backup is stored. This makes point-in-time recovery functionality available only if there is a single bucket in `spec.backup.storages`. Otherwise point-in-time recovery will not be enabled and there will be an error message in the operator logs.

Note: Adding a new bucket when point-in-time recovery is enabled will not break it, but put error message about the additional bucket in the operator logs as well.

20.4 Restore the cluster from a previously saved backup

Backup can be restored not only on the Kubernetes cluster where it was made, but also on any Kubernetes-based environment with the installed Operator.

Note: When restoring to a new Kubernetes-based environment, make sure it has a Secrets object with the same user passwords as in the original cluster. More details about secrets can be found in [System Users](#).

Following things are needed to restore a previously saved backup:

- Make sure that the cluster is running.
- Find out correct names for the **backup** and the **cluster**. Available backups can be listed with the following command:

```
kubect1 get psmdb-backup
```

Note: Obviously, you can make this check only on the same cluster on which you have previously made the backup.

And the following command will list available clusters:

```
kubect1 get psmdb
```

20.4.1 Restoring without point-in-time recovery

When the correct names for the backup and the cluster are known, backup restoration can be done in the following way.

1. Set appropriate keys in the `deploy/backup/restore.yaml` file.
 - set `spec.clusterName` key to the name of the target cluster to restore the backup on,
 - **if you are restoring backup on the *same* Kubernetes-based cluster you have** used to save this backup, set `spec.backupName` key to the name of your backup,
 - if you are restoring backup on the Kubernetes-based cluster *different* from one you have used to save this backup, set `spec.backupSource` subsection instead of `spec.backupName` field to point on the appropriate S3-compatible storage. This `backupSource` subsection should contain a `destination` key equal to the s3 bucket with a special `s3://` prefix, followed by necessary S3 configuration keys, same as in `deploy/cr.yaml` file:

```
...
backupSource:
  destination: s3://S3-BUCKET-NAME/BACKUP-NAME
  s3:
    credentialsSecret: my-cluster-name-backup-s3
    region: us-west-2
    endpointUrl: https://URL-OF-THE-S3-COMPATIBLE-STORAGE
```

- you can also use a `storageName` key to specify the exact name of the storage (the actual storage should be already defined in the `backup.storages` subsection of the `deploy/cr.yaml` file):

```
...
storageName: s3-us-west
backupSource:
  destination: s3://S3-BUCKET-NAME/BACKUP-NAME
```

2. After that, the actual restoration process can be started as follows:

```
kubect1 apply -f deploy/backup/restore.yaml
```

Note: Storing backup settings in a separate file can be replaced by passing its content to the `kubect1 apply` command as follows:

```
cat <<EOF | kubect1 apply -f-
apiVersion: psmdb.percona.com/v1
kind: PerconaServerMongoDBRestore
metadata:
  name: restore1
```

(continues on next page)

(continued from previous page)

```
spec:
  clusterName: my-cluster-name
  backupName: backup1
EOF
```

20.4.2 Restoring backup with point-in-time recovery

Following steps are needed to roll back the cluster to a specific date and time:

1. Set appropriate keys in the `deploy/backup/restore.yaml` file.
 - set `spec.clusterName` key to the name of the target cluster to restore the backup on,
 - put additional restoration parameters to the `pitr` section:

```
...
spec:
  clusterName: my-cluster-name
  pitr:
    type: date
    date: YYYY-MM-DD hh:mm:ss
```

- **if you are restoring backup on the *same* Kubernetes-based cluster you have** used to save this backup, set `spec.backupName` key to the name of your backup,
- if you are restoring backup on the Kubernetes-based cluster *different* from one you have used to save this backup, set `spec.backupSource` subsection instead of `spec.backupName` field to point on the appropriate S3-compatible storage. This `backupSource` subsection should contain a `destination` key equal to the S3 bucket with a special `s3://` prefix, followed by necessary S3 configuration keys, same as in `deploy/cr.yaml` file:

```
...
backupSource:
  destination: s3://S3-BUCKET-NAME/BACKUP-NAME
  s3:
    credentialsSecret: my-cluster-name-backup-s3
    region: us-west-2
    endpointUrl: https://URL-OF-THE-S3-COMPATIBLE-STORAGE
```

- you can also use a `storageName` key to specify the exact name of the storage (the actual storage should be already defined in the `backup.storages` subsection of the `deploy/cr.yaml` file):

```
...
storageName: s3-us-west
backupSource:
  destination: s3://S3-BUCKET-NAME/BACKUP-NAME
```

2. Run the actual restoration process:

```
kubectl apply -f deploy/backup/restore.yaml
```

Note: Storing backup settings in a separate file can be replaced by passing its content to the `kubectl apply` command as follows:

```
cat <<EOF | kubectl apply -f-
apiVersion: psmdb.percona.com/v1
kind: PerconaServerMongoDBRestore
metadata:
  name: restore1
spec:
  clusterName: my-cluster-name
  backupName: backup1
  pitr:
    type: date
    date: YYYY-MM-DD hh:mm:ss
EOF
```

20.5 Delete the unneeded backup

The maximum amount of stored backups is controlled by the `backup.tasks.keep` option (only successful backups are counted). Older backups are automatically deleted, so that amount of stored backups do not exceed this number. Setting `keep=0` or removing this option from `deploy/cr.yaml` disables automatic deletion of backups.

Manual deleting of a previously saved backup requires not more than the backup name. This name can be taken from the list of available backups returned by the following command:

```
kubectl get psmdb-backup
```

When the name is known, backup can be deleted as follows:

```
kubectl delete psmdb-backup/<backup-name>
```


PAUSE/RESUME PERCONA SERVER FOR MONGODB

There may be external situations when it is needed to shutdown the cluster for a while and then start it back up (some works related to the maintenance of the enterprise infrastructure, etc.).

The `deploy/cr.yaml` file contains a special `spec.pause` key for this. Setting it to `true` gracefully stops the cluster:

```
spec:
  .....
  pause: true
```

To start the cluster after it was shut down just revert the `spec.pause` key to `false`.

CREATING A PRIVATE S3-COMPATIBLE CLOUD FOR BACKUPS

As it is mentioned in [backups](#) any cloud storage which implements the S3 API can be used for backups. The one way to setup and implement the S3 API storage on Kubernetes or OpenShift is [Minio](#) - the S3-compatible object storage server deployed via Docker on your own infrastructure.

Setting up Minio to be used with Percona Distribution for MongoDB Operator backups involves following steps:

1. Install Minio in your Kubernetes or OpenShift environment and create the correspondent Kubernetes Service as follows:

```
helm install \
  --name minio-service \
  --set accessKey=some-access-key \
  --set secretKey=some-secret-key \
  --set service.type=ClusterIP \
  --set configPath=/tmp/.minio/ \
  --set persistence.size=2G \
  --set environment.MINIO_REGION=us-east-1 \
  stable/minio
```

Don't forget to substitute default `some-access-key` and `some-secret-key` strings in this command with actual unique key values. The values can be used later for access control. The `storageClass` option is needed if you are using the special [Kubernetes Storage Class](#) for backups. Otherwise, this setting may be omitted. You may also notice the `MINIO_REGION` value which is may not be used within a private cloud. Use the same region value here and on later steps (`us-east-1` is a good default choice).

2. Create an S3 bucket for backups:

```
kubectl run -i --rm aws-cli --image=perconalab/awscli --restart=Never -- \
  bash -c 'AWS_ACCESS_KEY_ID=some-access-key \
  AWS_SECRET_ACCESS_KEY=some-secret-key \
  AWS_DEFAULT_REGION=us-east-1 \
  /usr/bin/aws \
  --endpoint-url http://minio-service:9000 \
  s3 mb s3://operator-testing'
```

This command creates the bucket named `operator-testing` with the selected access and secret keys (substitute `some-access-key` and `some-secret-key` with the values used on the previous step).

3. Now edit the backup section of the [deploy/cr.yaml](#) file to set proper values for the bucket (the S3 bucket for backups created on the previous step), `region`, `credentialsSecret` and the `endpointUrl` (which should point to the previously created Minio Service).

```

...
backup:
  enabled: true
  version: 0.3.0
...
storages:
  minio:
    type: s3
    s3:
      bucket: operator-testing
      region: us-east-1
      credentialsSecret: my-cluster-name-backup-minio
      endpointUrl: http://minio-service:9000
...

```

The option which should be specially mentioned is `credentialsSecret` which is a [Kubernetes secret](#) for backups. Sample `backup-s3.yaml` can be used to create this secret object. Check that the object contains the proper name value and is equal to the one specified for `credentialsSecret`, i.e. `my-cluster-name-backup-minio` in the backup to Minio example, and also contains the proper `AWS_ACCESS_KEY_ID` and `AWS_SECRET_ACCESS_KEY` keys. After you have finished editing the file, the secrets object are created or updated when you run the following command:

```
$ kubectl apply -f deploy/backup-s3.yaml
```

- When the setup process is completed, making the backup is based on a script. Following example illustrates how to make an on-demand backup:

```

kubectl run -it --rm pbmctl --image=percona/percona-server-mongodb-operator:0.3.0-
↪ backup-pbmctl --restart=Never -- \
  run backup \
  --server-address=<cluster-name>-backup-coordinator:10001 \
  --storage <storage> \
  --compression-algorithm=gzip \
  --description=my-backup

```

Don't forget to specify the name of your cluster instead of the `<cluster-name>` part of the Backup Coordinator URL (the cluster name is specified in the `deploy/cr.yaml` file). Also substitute `<storage>` with the actual storage name located in a subsection inside of the backups in the `deploy/cr.yaml` file. In the earlier example this value is `minio`.

- To restore a previously saved backup you must specify the backup name. With the proper Backup Coordinator URL and storage name, you can obtain a list of the available backups:

```

kubectl run -it --rm pbmctl --image=percona/percona-server-mongodb-operator:0.3.0-
↪ backup-pbmctl --restart=Never -- list backups --server-address=<cluster-name>-
↪ backup-coordinator:10001

```

Now, restore the backup, using backup name instead of the `backup-name` parameter:

```

kubectl run -it --rm pbmctl --image=percona/percona-server-mongodb-operator:0.3.0-
↪ backup-pbmctl --restart=Never -- \
  run restore \
  --server-address=<cluster-name>-backup-coordinator:10001 \

```

(continues on next page)

(continued from previous page)

```
--storage <storage> \  
backup-name
```


UPDATE PERCONA DISTRIBUTION FOR MONGODB OPERATOR

Starting from the version 1.1.0 the Percona Distribution for MongoDB Operator allows upgrades to newer versions. This includes upgrades of the Operator itself, and upgrades of the Percona Server for MongoDB.

23.1 Upgrading the Operator

This upgrade can be done either in semi-automatic or in manual mode.

Note: Manual update mode is the recommended way for a production cluster.

23.1.1 Semi-automatic upgrade

Note: Only the incremental update to a nearest minor version is supported (for example, update from 1.5.0 to 1.6.0). To update to a newer version, which differs from the current version by more than one, make several incremental updates sequentially.

1. Update the Custom Resource Definition file for the Operator, taking it from the official repository on Github, and do the same for the Role-based access control:

```
kubectl apply -f https://raw.githubusercontent.com/percona/percona-server-mongodb-  
↪operator/v1.9.0/deploy/crd.yaml  
kubectl apply -f https://raw.githubusercontent.com/percona/percona-server-mongodb-  
↪operator/v1.9.0/deploy/rbac.yaml
```

2. Edit the `deploy/cr.yaml` file, setting `updateStrategy` key to `RollingUpdate`.
3. Now you should [apply a patch](#) to your deployment, supplying necessary image names with a newer version tag. This is done with the `kubectl patch deployment` command. For example, updating to the 1.9.0 version should look as follows:

```
kubectl patch deployment percona-server-mongodb-operator \  
-p '{"spec":{"template":{"spec":{"containers":[{"name":"percona-server-mongodb-  
↪operator","image":"percona/percona-server-mongodb-operator:1.9.0"}]}}}}'  
  
kubectl patch psmdb my-cluster-name --type=merge --patch '{  
  "spec": {  
    "crVersion":"1.9.0",
```

(continues on next page)

(continued from previous page)

```

    "image": "percona/percona-server-mongodb:4.4.6-8",
    "backup": { "image": "percona/percona-server-mongodb-operator:1.9.0-backup" }
    ↪,
    "pmm": { "image": "percona/pmm-client:2.18.0" }
  } }'

```

4. The deployment rollout will be automatically triggered by the applied patch. You can track the rollout process in real time using the `kubectl rollout status sts my-cluster-name-rs0` command with the name of your cluster:

```
kubectl rollout status sts my-cluster-name-rs0
```

23.1.2 Manual upgrade

Note: Only the incremental update to a nearest minor version of the Operator is supported (for example, update from 1.5.0 to 1.6.0). To update to a newer version, which differs from the current version by more than one, make several incremental updates sequentially.

1. Update the Custom Resource Definition file for the Operator, taking it from the official repository on Github, and do the same for the Role-based access control:

```

kubectl apply -f https://raw.githubusercontent.com/percona/percona-server-mongodb-
↪operator/v1.9.0/deploy/crd.yaml
kubectl apply -f https://raw.githubusercontent.com/percona/percona-server-mongodb-
↪operator/v1.9.0/deploy/rbac.yaml

```

2. Edit the `deploy/cr.yaml` file, setting `updateStrategy` key to `OnDelete`.
3. Now you should [apply a patch](#) to your deployment, supplying necessary image names with a newer version tag. This is done with the `kubectl patch deployment` command. For example, updating to the 1.9.0 version should look as follows:

```

kubectl patch deployment percona-server-mongodb-operator \
  -p '{"spec":{"template":{"spec":{"containers":[{"name":"percona-server-mongodb-
↪operator","image":"percona/percona-server-mongodb-operator:1.9.0"}]}}}}'

kubectl patch psmdb my-cluster-name --type=merge --patch '{
  "spec": {
    "crVersion":"1.9.0",
    "image": "percona/percona-server-mongodb:4.4.6-8",
    "backup": { "image": "percona/percona-server-mongodb-operator:1.9.0-backup" }
    ↪,
    "pmm": { "image": "percona/pmm-client:2.18.0" }
  } }'

```

4. Pod with the newer Percona Server for MongoDB image will start after you delete it. Delete targeted Pods manually one by one to make them restart in the desired order:
 1. Delete the Pod using its name with the command like the following one:

```
kubectl delete pod my-cluster-name-rs0-2
```

2. Wait until Pod becomes ready:


```
kubectl get pod my-cluster-name-rs0-2
```

The output should be like this:

NAME	READY	STATUS	RESTARTS	AGE
my-cluster-name-rs0-2	1/1	Running	0	3m33s

5. The update process is successfully finished when all Pods have been restarted.

23.2 Upgrading Percona Server for MongoDB

Starting from version 1.5.0, the Operator can do fully automatic upgrades to the newer versions of Percona Server for MongoDB within the method named *Smart Updates*.

To have this upgrade method enabled, make sure that the `updateStrategy` key in the `deploy/cr.yaml` configuration file is set to `SmartUpdate`.

When automatic updates are enabled, the Operator will carry on upgrades according to the following algorithm. It will query a special *Version Service* server at scheduled times to obtain fresh information about version numbers and valid image paths needed for the upgrade. If the current version should be upgraded, the Operator updates the CR to reflect the new image paths and carries on sequential Pods deletion in a safe order, allowing StatefulSet to redeploy the cluster Pods with the new image.

Note: Being enabled, Smart Update will force the Operator to take MongoDB version from Version Service and not from the `mongodb.image` option during the very first start of the cluster.

The upgrade details are set in the `upgradeOptions` section of the `deploy/cr.yaml` configuration file. Make the following edits to configure updates:

1. Set the `apply` option to one of the following values:
 - **Recommended** - automatic upgrade will choose the most recent version of software flagged as Recommended (for clusters created from scratch, the Percona Server for MongoDB 4.4 version will be selected instead of the Percona Server for MongoDB 4.2 or 4.0 version regardless of the image path; for already existing clusters, the 4.4 vs. 4.2 or 4.0 branch choice will be preserved),
 - **4.4-recommended, 4.2-recommended, 4.0-recommended** - same as above, but preserves specific major MongoDB version for newly provisioned clusters (ex. 4.4 will not be automatically used instead of 4.2),
 - **Latest** - automatic upgrade will choose the most recent version of the software available (for clusters created from scratch, the Percona Server for MongoDB 4.4 version will be selected instead of the Percona Server for MongoDB 4.2 or 4.0 version regardless of the image path; for already existing clusters, the 4.4 vs. 4.2 or 4.0 branch choice will be preserved),
 - **4.4-latest, 4.2-latest, 4.0-latest** - same as above, but preserves specific major MongoDB version for newly provisioned clusters (ex. 4.4 will not be automatically used instead of 4.2),
 - **version number** - specify the desired version explicitly (version numbers are specified as 4.4.6-8, 4.2.14-15, etc.),
 - **Never or Disabled** - disable automatic upgrades.

Note: When automatic upgrades are disabled by the `apply` option, Smart Update functionality will continue working for changes triggered by other events, such as rotating a password, or changing resource

values.

2. Make sure the `versionServiceEndpoint` key is set to a valid Version Server URL (otherwise Smart Updates will not occur).
 - A. You can use the URL of the official Percona's Version Service (default). Set `versionServiceEndpoint` to `https://check.percona.com`.
 - B. Alternatively, you can run Version Service inside your cluster. This can be done with the `kubectl` command as follows:

```
kubectl run version-service --image=perconalab/version-service --env="SERVE_
HTTP=true" --port 11000 --expose
```

Note: Version Service is never checked if automatic updates are disabled. If automatic updates are enabled, but Version Service URL can not be reached, upgrades will not occur.

3. Use the `schedule` option to specify the update checks time in CRON format.

The following example sets the midnight update checks with the official Percona's Version Service:

```
spec:
  updateStrategy: SmartUpdate
  upgradeOptions:
    apply: Recommended
    versionServiceEndpoint: https://check.percona.com
    schedule: "0 0 * * *"
  ...
```

23.2.1 Percona Server for MongoDB major version upgrades

Normally automatic upgrade takes place within minor versions (for example, from 4.2.11-12 to 4.2.12-13) of MongoDB. Major versions upgrade (for example moving from 4.2-recommended to 4.4-recommended) is more complicated task which might potentially affect how data is stored and how applications interacts with the database (in case of some API changes).

Such upgrade is supported by the Operator within one major version at a time: for example, to change Percona Server for MongoDB major version from 4.0 to 4.4, you should first upgrade it to 4.2, and later make a separate upgrade from 4.2 to 4.4. The same is true for major version downgrades.

Note: It is recommended to take a backup before upgrade, as well as to perform upgrade on staging environment.

Major version upgrade can be initiated using the `upgradeOptions.apply` key in the `deploy/cr.yaml` configuration file:

```
spec:
  upgradeOptions:
    apply: 4.4-recommended
```

Note: When making downgrades (e.g. changing version from 4.4 to 4.2), make sure to remove incompatible features that are persisted and/or update incompatible configuration settings. Compatibility issues between major MongoDB

versions can be found in [upstream documentation](#).

By default the Operator doesn't set `FeatureCompatibilityVersion (FCV)` to match the new version, thus making sure that backwards-incompatible features are not automatically enabled with the major version upgrade (which is recommended and safe behavior). You can turn this backward compatibility off at any moment (after the upgrade or even before it) by setting the `upgradeOptions.setFCV` flag in the `deploy/cr.yaml` configuration file to `true`.

Note: With `setFeatureCompatibilityVersion` set major version rollback is not currently supported by the Operator. Therefore it is recommended to stay without enabling this flag for some time after the major upgrade to ensure the likelihood of downgrade is minimal. Setting `setFCV` flag to `true` simultaneously with the `apply` flag should be done only if the whole procedure is tested on staging and you are 100% sure about it.

SCALE PERCONA SERVER FOR MONGODB ON KUBERNETES AND OPENSHIFT

One of the great advantages brought by Kubernetes and the OpenShift platform is the ease of an application scaling. Scaling a Deployment up or down ensures new Pods are created and set to available Kubernetes nodes.

The size of the cluster is controlled by the `size` key in the *Custom Resource options* configuration.

Note: The Operator will not allow to scale Percona Server for MongoDB with the `kubectl scale statefulset <StatefulSet name>` command as it puts `size` configuration options out of sync.

You can change size separately for different components of your cluster by setting this option in the appropriate sub-sections:

- *replsets.size* allows to set the size of the MongoDB Replica Set,
- *replsets.arbiter.size* allows to set the number of *Replica Set Arbiter instances*,
- *sharding.configsvrReplSet.size* allows to set the number of *Config Server instances*,
- *sharding.mongos.size* allows to set the number of *mongos* instances.

For example, the following update in `deploy/cr.yaml` will set the size of the MongoDB Replica Set to 5 nodes:

```
....
replsets:
  ....
  size: 5
  ....
```

Don't forget to apply changes as usual, running the `kubectl apply -f deploy/cr.yaml` command.

MONITORING

Percona Monitoring and Management (PMM) [provides an excellent solution](#) of monitoring Percona Server for MongoDB.

Note: Only PMM 2.x versions are supported by the Operator.

PMM is a client/server application. *PMM Client* runs on each node with the database you wish to monitor: it collects needed metrics and sends gathered data to *PMM Server*. As a user, you connect to PMM Server to see database metrics on a number of dashboards.

That's why PMM Server and PMM Client need to be installed separately.

25.1 Installing PMM Server

PMM Server runs as a *Docker image*, a *virtual appliance*, or on an *AWS instance*. Please refer to the [official PMM documentation](#) for the installation instructions.

25.2 Installing PMM Client

The following steps are needed for the PMM client installation in your Kubernetes-based environment:

1. The PMM client installation is initiated by updating the `pmm` section in the `deploy/cr.yaml` file.
 - set `pmm.enabled=true`
 - set the `pmm.serverHost` key to your PMM Server hostname.
 - check that the `PMM_SERVER_USER` key in the `deploy/secrets.yaml` secrets file contains your PMM Server user name (`admin` by default).
 - make sure the `PMM_SERVER_PASSWORD` key in the `deploy/secrets.yaml` secrets file contains the password specified for the PMM Server during its installation.

Note: You use `deploy/secrets.yaml` file to *create* Secrets Object. The file contains all values for each key/value pair in a convenient plain text format. But the resulting Secrets contain passwords stored as base64-encoded strings. If you want to *update* password field, you'll need to encode the value into base64 format. To do this, you can run `echo -n "password" | base64` in your local shell to get valid values. For example, setting the PMM Server user's password to `new_password` in the `my-cluster-name-secrets` object can be done with the following command:

```
kubectl patch secret/my-cluster-name-secrets -p '{"data":{"PMM_SERVER_PASSWORD": "$(echo -n new_password | base64)"}}'
```

- you can also use `pmm.mongodParams` and `pmm.mongosParams` keys to specify additional parameters for the `pmm-admin add mongodb` command for `mongod` and `mongos` Pods respectively, if needed.

Note: Please take into account that Operator automatically manages common MongoDB Service Monitoring parameters mentioned in the official `pmm-admin add mongodb` [documentation](#), such like username, password, service-name, host, etc. Assigning values to these parameters is not recommended and can negatively affect the functionality of the PMM setup carried out by the Operator.

Apply changes with the `kubectl apply -f deploy/secrets.yaml` command.

When done, apply the edited `deploy/cr.yaml` file:

```
$ kubectl apply -f deploy/cr.yaml
```

2. Check that corresponding Pods are not in a cycle of stopping and restarting. This cycle occurs if there are errors on the previous steps:

```
$ kubectl get pods
$ kubectl logs my-cluster-name-rs0-0 -c pmm-client
```

3. Run the following command:

```
kubectl get service/monitoring-service -o wide
```

In the results, locate the `EXTERNAL-IP` field. The external-ip address can be used to access PMM via `https` in a web browser, with the login/password authentication, and the browser is configured to show Percona Server for MongoDB metrics.

DEBUG

For the cases when Pods are failing for some reason or just show abnormal behavior, the Operator can be used with a special *debug image* of the Percona Server for MongoDB, which has the following specifics:

- it avoids restarting on fail,
- it contains additional tools useful for debugging (sudo, telnet, gdb, mongodb-debuginfo package, etc.),
- extra verbosity is added to the mongodb daemon.

Particularly, using this image is useful if the container entry point fails (mongod crashes). In such a situation, Pod is continuously restarting. Continuous restarts prevent to get console access to the container, and so a special approach is needed to make fixes.

To use the debug image instead of the normal one, set the following image name for the `image` key in the `deploy/cr.yaml` configuration file:

```
percona/percona-server-mongodb:4.4.6-8-debug
```

The Pod should be restarted to get the new image.

Note: When the Pod is continuously restarting, you may have to delete it to apply image changes.

Part VI

Reference

CUSTOM RESOURCE OPTIONS

The operator is configured via the spec section of the `deploy/cr.yaml` file.

The metadata part of this file contains the following keys:

- `name` (`my-cluster-name` by default) sets the name of your Percona Server for MongoDB Cluster; it should include only [URL-compatible characters](#), not exceed 22 characters, start with an alphabetic character, and end with an alphanumeric character;
- `finalizers.delete-psmdb-pvc`, if present, activates the [Finalizer](#) which deletes appropriate [Persistent Volume Claims](#) after the cluster deletion event (off by default).

The spec part of the `deploy/cr.yaml` file contains the following sections:

Key	Value type	Default	Description
platform	string	kubernetes	Override/set the Kubernetes platform: <i>kubernetes</i> or <i>open-shift</i> . Set openshift on OpenShift 3.11+
pause	boolean	false	Pause/resume: setting it to <code>true</code> gracefully stops the cluster, and setting it to <code>false</code> after shut down starts the cluster back.
crVersion	string	1.9.0	Version of the Operator the Custom Resource belongs to
image	string	percona/percona-server-mongodb:4.4.6-8	The Docker image of Percona Server for MongoDB to deploy (actual image names can be found <i>in the list of certified images</i>)
imagePullPolicy	string	Always	The policy used to update images
imagePullSecrets.name	string	private-registry-credentials	The Kubernetes ImagePullSecret to access the <i>custom registry</i>
ClusterServiceDNSSuffix	string	svc.cluster.local	The (non-standard) cluster domain to be used as a suffix of the Service name
runUid	int	1001	The (non-standard) user ID
allowUnsafeConfigurations	boolean	false	Prevents users from configuring a cluster with unsafe parameters: starting it with less than 3 replica set instances, with an <i>even number of replica set instances without additional arbiter</i> , or without TLS/SSL certificates, or running a sharded cluster with less than 3 config server Pods or less than 2 mongos Pods (if <code>false</code> , the Operator will automatically change unsafe parameters to safe defaults)
updateStrategy	string	SmartUpdate	A strategy the Operator uses for <i>upgrades</i> . Possible values are <i>SmartUpdate</i> , <i>RollingUpdate</i> and <i>OnDelete</i> .
upgradeOptions	<i>subdoc</i>		Upgrade configuration section
secrets	<i>subdoc</i>		Operator secrets section
replsets	<i>subdoc</i>		Operator MongoDB Replica Set section
pmm	<i>subdoc</i>		Percona Monitoring and Management section
sharding	<i>subdoc</i>		MongoDB sharding configuration section
mongod	<i>subdoc</i>		Operator MongoDB Mongod configuration section
backup	<i>subdoc</i>		Percona Server for MongoDB backups section

27.1 Upgrade Options Section

The `upgradeOptions` section in the `deploy/cr.yaml` file contains various configuration options to control Percona Server for MongoDB upgrades.

Key	<code>upgradeOptions.versionServiceEndpoint</code>
Value	string
Example	<code>https://check.percona.com</code>
Description	The Version Service URL used to check versions compatibility for upgrade
Key	<code>upgradeOptions.apply</code>
Value	string
Example	<code>4.4-recommended</code>
Description	Specifies how <i>updates are processed</i> by the Operator. <code>Never</code> or <code>Disabled</code> will completely disable automatic upgrades, otherwise it can be set to <code>Latest</code> or <code>Recommended</code> or to a specific version string of Percona Server for MongoDB (e.g. <code>4.4.2-4</code>) that is wished to be version-locked (so that the user can control the version running, but use automatic upgrades to move between them).
Key	<code>upgradeOptions.schedule</code>
Value	string
Example	<code>0 2 * * *</code>
Description	Scheduled time to check for updates, specified in the <code>crontab</code> format
Key	<code>upgradeOptions.setFCV</code>
Value	boolean
Example	<code>false</code>
Description	If enabled, <code>FeatureCompatibilityVersion (FCV)</code> will be set to match the version during major version upgrade

27.2 Secrets section

Each spec in its turn may contain some key-value pairs. The secrets one has only two of them:

Key	<code>secrets.key</code>
Value Type	string
Example	<code>my-cluster-name-mongodb-key</code>
Description	The secret name for the MongoDB Internal Auth Key . This secret is auto-created by the operator if it doesn't exist.
Key	<code>secrets.users</code>
Value Type	string
Example	<code>my-cluster-name-mongodb-users</code>
Description	The secret name for the MongoDB users required to run the operator .
Key	<code>secrets.ssl</code>
Value Type	string
Example	<code>my-custom-ssl</code>
Description	A secret with TLS certificate generated for <i>external</i> communications, see Transport Layer Security (TLS) for details
Key	<code>secrets.sslInternal</code>
Value Type	string
Example	<code>my-custom-ssl-internal</code>
Description	A secret with TLS certificate generated for <i>internal</i> communications, see Transport Layer Security (TLS) for details

27.3 Replsets Section

The replsets section controls the MongoDB Replica Set.

Key	<code>replsets.name</code>
Value Type	string
Example	<code>rs 0</code>
Description	The name of the MongoDB Replica Set
Key	<code>replsets.size</code>
Value Type	int
Example	<code>3</code>
Description	The size of the MongoDB Replica Set, must be ≥ 3 for High-Availability
Key	<code>replsets.configuration</code>
Value Type	string
Example	<pre> operationProfiling: mode: slowOp systemLog: verbosity: 1</pre>

continues on next page

Table 1 – continued from previous page

Description	Custom configuration options for mongod. Please refer to the official manual for the full list of options, and specific Percona Server for MongoDB docs .
Key	<code>replsets.affinity.antiAffinityTopologyKey</code>
Value Type	string
Example	<code>kubernetes.io/hostname</code>
Description	The Kubernetes topologyKey node affinity constraint for the Replica Set nodes
Key	<code>replsets.affinity.advanced</code>
Value Type	subdoc
Example	
Description	In cases where the pods require complex tuning the <i>advanced</i> option turns off the <code>topologykey</code> effect. This setting allows the standard Kubernetes affinity constraints of any complexity to be used
Key	<code>replsets.tolerations.key</code>
Value Type	string
Example	<code>node.alpha.kubernetes.io/unreachable</code>
Description	The Kubernetes Pod tolerations key for the Replica Set nodes
Key	<code>replsets.tolerations.operator</code>
Value Type	string
Example	<code>Exists</code>
Description	The Kubernetes Pod tolerations operator for the Replica Set nodes
Key	<code>replsets.tolerations.effect</code>
Value Type	string
Example	<code>NoExecute</code>
Description	The Kubernetes Pod tolerations effect for the Replica Set nodes
Key	<code>replsets.tolerations.tolerationSeconds</code>
Value Type	int
Example	<code>60000</code>
Description	The Kubernetes Pod tolerations time limit for the Replica Set nodes
Key	<code>replsets.priorityClassName</code>
Value Type	string
Example	<code>high priority</code>
Description	The Kuberentes Pod priority class for the Replica Set nodes
Key	<code>replsets.annotations.iam.amazonaws.com/role</code>
Value Type	string
Example	<code>role-arn</code>
Description	The AWS IAM role for the Replica Set nodes
Key	<code>replsets.labels</code>
Value Type	label
Example	<code>rack: rack-22</code>
Description	The Kubernetes affinity labels for the Replica Set nodes

continues on next page

Table 1 – continued from previous page

Key	<code>replsets.nodeSelector</code>
Value Type	label
Example	<code>disktype: ssd</code>
Description	The Kubernetes nodeSelector affinity constraint for the Replica Set nodes
Key	<code>replsets.livenessProbe.failureThreshold</code>
Value Type	int
Example	4
Description	Number of consecutive unsuccessful tries of the liveness probe to be undertaken before giving up.
Key	<code>replsets.livenessProbe.initialDelaySeconds</code>
Value Type	int
Example	60
Description	Number of seconds to wait after the container start before initiating the liveness probe .
Key	<code>replsets.livenessProbe.periodSeconds</code>
Value Type	int
Example	30
Description	How often to perform a liveness probe (in seconds).
Key	<code>replsets.livenessProbe.successThreshold</code>
Value Type	int
Example	1
Description	Minimum consecutive successes for the liveness probe to be considered successful after having failed.
Key	<code>replsets.livenessProbe.timeoutSeconds</code>
Value Type	int
Example	5
Description	Number of seconds after which the liveness probe times out.
Key	<code>replsets.livenessProbe.startupDelaySeconds</code>
Value Type	int
Example	7200
Description	Time after which the liveness probe is failed if the MongoDB instance didn't finish its full startup yet
Key	<code>replsets.runtimeClassName</code>
Value Type	string
Example	<code>image-rc</code>
Description	Name of the Kubernetes Runtime Class for Replica Set Pods
Key	<code>replsets.sidecars.image</code>
Value Type	string
Example	<code>busybox</code>
Description	Image for the <i>custom sidecar container</i> for Replica Set Pods
Key	<code>replsets.sidecars.command</code>
Value Type	array
Example	<code>["/bin/sh"]</code>

continues on next page

Table 1 – continued from previous page

Description	Command for the <i>custom sidecar container</i> for Replica Set Pods
Key	replsets.sidecars.args
Value Type	array
Example	["-c", "while true; do echo echo \$(date -u) 'test' >> /dev/null; sleep 5;done"]
Description	Command arguments for the <i>custom sidecar container</i> for Replica Set Pods
Key	replsets.sidecars.name
Value Type	string
Example	rs-sidecar-1
Description	Name of the <i>custom sidecar container</i> for Replica Set Pods
Key	replsets.podDisruptionBudget.maxUnavailable
Value Type	int
Example	1
Description	The Kubernetes Pod distribution budget limit specifying the maximum value for unavailable Pods
Key	replsets.podDisruptionBudget.minAvailable
Value Type	int
Example	1
Description	The Kubernetes Pod distribution budget limit specifying the minimum value for available Pods
Key	replsets.expose.enabled
Value Type	boolean
Example	false
Description	Enable or disable exposing MongoDB Replica Set nodes with dedicated IP addresses
Key	replsets.expose.exposeType
Value Type	string
Example	ClusterIP
Description	The IP address type to be exposed
Key	replsets.arbiter.enabled
Value Type	boolean
Example	false
Description	Enable or disable creation of Replica Set Arbiter nodes within the cluster
Key	replsets.arbiter.size
Value Type	int
Example	1
Description	The number of Replica Set Arbiter instances within the cluster
Key	replsets.arbiter.affinity.antiAffinityTopologyKey
Value Type	string
Example	kubernetes.io/hostname
Description	The Kubernetes topologyKey node affinity constraint for the Arbiter
Key	replsets.arbiter.affinity.advanced
Value Type	subdoc

continues on next page

Table 1 – continued from previous page

Example	
Description	In cases where the pods require complex tuning the <i>advanced</i> option turns off the <code>topologykey</code> effect. This setting allows the standard Kubernetes affinity constraints of any complexity to be used
Key	<code>replsets.arbiter.tolerations.key</code>
Value Type	string
Example	<code>node.alpha.kubernetes.io/unreachable</code>
Description	The Kubernetes Pod tolerations key for the Arbiter nodes
Key	<code>replsets.arbiter.tolerations.operator</code>
Value Type	string
Example	<code>Exists</code>
Description	The Kubernetes Pod tolerations operator for the Arbiter nodes
Key	<code>replsets.arbiter.tolerations.effect</code>
Value Type	string
Example	<code>NoExecute</code>
Description	The Kubernetes Pod tolerations effect for the Arbiter nodes
Key	<code>replsets.arbiter.tolerations.tolerationSeconds</code>
Value Type	int
Example	<code>60000</code>
Description	The Kubernetes Pod tolerations time limit for the Arbiter nodes
Key	<code>replsets.arbiter.priorityClassName</code>
Value Type	string
Example	<code>high priority</code>
Description	The Kuberentes Pod priority class for the Arbiter nodes
Key	<code>replsets.arbiter.annotations.iam.amazonaws.com/role</code>
Value Type	string
Example	<code>role-arn</code>
Description	The AWS IAM role for the Arbiter nodes
Key	<code>replsets.arbiter.labels</code>
Value Type	label
Example	<code>rack: rack-22</code>
Description	The Kubernetes affinity labels for the Arbiter nodes
Key	<code>replsets.arbiter.nodeSelector</code>
Value Type	label
Example	<code>disktype: ssd</code>
Description	The Kubernetes nodeSelector affinity constraint for the Arbiter nodes
Key	<code>replsets.schedulerName</code>
Value Type	string
Example	<code>default</code>
Description	The Kubernetes Scheduler

continues on next page

Table 1 – continued from previous page

Key	<code>replsets.resources.limits.cpu</code>
Value Type	string
Example	300m
Description	Kubernetes CPU limit for MongoDB container
Key	<code>replsets.resources.limits.memory</code>
Value Type	string
Example	0.5G
Description	Kubernetes Memory limit for MongoDB container
Key	<code>replsets.resources.requests.cpu</code>
Value Type	string
Example	
Description	The Kubernetes CPU requests for MongoDB container
Key	<code>replsets.resources.requests.memory</code>
Value Type	string
Example	
Description	The Kubernetes Memory requests for MongoDB container
Key	<code>replsets.volumeSpec.emptyDir</code>
Value Type	string
Example	{}
Description	The Kubernetes emptyDir volume, i.e. the directory which will be created on a node, and will be accessible to the MongoDB Pod containers
Key	<code>replsets.volumeSpec.hostPath.path</code>
Value Type	string
Example	/data
Description	Kubernetes hostPath volume, i.e. the file or directory of a node that will be accessible to the MongoDB Pod containers
Key	<code>replsets.volumeSpec.hostPath.type</code>
Value Type	string
Example	Directory
Description	The Kubernetes hostPath volume type
Key	<code>replsets.volumeSpec.persistentVolumeClaim.storageClassName</code>
Value Type	string
Example	standard
Description	The Kubernetes Storage Class to use with the MongoDB container Persistent Volume Claim. Use Storage Class with XFS as the default filesystem if possible, for better MongoDB performance
Key	<code>replsets.volumeSpec.persistentVolumeClaim.accessModes</code>
Value Type	array
Example	["ReadWriteOnce"]
Description	The Kubernetes Persistent Volume access modes for the MongoDB container
Key	<code>replsets.volumeSpec.persistentVolumeClaim.resources.requests.storage</code>
Value Type	string

continues on next page

Table 1 – continued from previous page

Example	3Gi
Description	The Kubernetes Persistent Volume size for the MongoDB container

27.4 PMM Section

The `pmm` section in the `deploy/cr.yaml` file contains configuration options for Percona Monitoring and Management.

Key	<code>pmm.enabled</code>
Value Type	boolean
Example	<code>false</code>
Description	Enables or disables monitoring Percona Server for MongoDB with PMM
Key	<code>pmm.image</code>
Value Type	string
Example	<code>percona/pmm-client:2.18.0</code>
Description	PMM Client docker image to use
Key	<code>pmm.serverHost</code>
Value Type	string
Example	<code>monitoring-service</code>
Description	Address of the PMM Server to collect data from the Cluster
Key	<code>pmm.mongodParams</code>
Value Type	string
Example	<code>--environment=DEV-ENV --custom-labels=DEV-ENV</code>
Description	Additional parameters which will be passed to the <code>pmm-admin add mongodb</code> command for mongod Pods
Key	<code>pmm.mongosParams</code>
Value Type	string
Example	<code>--environment=DEV-ENV --custom-labels=DEV-ENV</code>
Description	Additional parameters which will be passed to the <code>pmm-admin add mongodb</code> command for mongos Pods

27.5 Sharding Section

The sharding section in the `deploy/cr.yaml` file contains configuration options for Percona Server for MongoDB *sharding*.

Key	<code>sharding.enabled</code>
Value Type	boolean
Example	<code>true</code>
Description	Enables or disables Percona Server for MongoDB sharding

continues on next page

Table 2 – continued from previous page

Key	<code>sharding.configsvrReplSet.size</code>
Value Type	int
Example	3
Description	The number of Config Server instances within the cluster
Key	<code>sharding.configsvrReplSet.configuration</code>
Value Type	string
Example	<pre> operationProfiling: mode: slowOp systemLog: verbosity: 1</pre>
Description	Custom configuration options for Config Servers. Please refer to the official manual for the full list of options
Key	<code>sharding.configsvrReplSet.runtimeClassName</code>
Value Type	string
Example	image-rc
Description	Name of the Kubernetes Runtime Class for Config Server Pods
Key	<code>sharding.configsvrReplSet.sidecars.image</code>
Value Type	string
Example	busybox
Description	Image for the <i>custom sidecar container</i> for Config Server Pods
Key	<code>sharding.configsvrReplSet.sidecars.command</code>
Value Type	array
Example	<code>["/bin/sh"]</code>
Description	Command for the <i>custom sidecar container</i> for Config Server Pods
Key	<code>sharding.configsvrReplSet.sidecars.args</code>
Value Type	array
Example	<code>["-c", "while true; do echo echo \$(date -u) 'test' >> /dev/null; sleep 5;done"]</code>
Description	Command arguments for the <i>custom sidecar container</i> for Config Server Pods
Key	<code>sharding.configsvrReplSet.sidecars.name</code>
Value Type	string
Example	rs-sidecar-1
Description	Name of the <i>custom sidecar container</i> for Config Server Pods
Key	<code>sharding.configsvrReplSet.volumeSpec.emptyDir</code>
Value Type	string
Example	<code>{}</code>
Description	The Kubernetes emptyDir volume, i.e. the directory which will be created on a node, and will be accessible to the Config Server Pod containers
Key	<code>sharding.configsvrReplSet.volumeSpec.hostPath.path</code>

continues on next page

Table 2 – continued from previous page

Value Type	string
Example	/data
Description	Kubernetes <code>hostPath</code> volume, i.e. the file or directory of a node that will be accessible to the Config Server Pod containers
Key	<code>sharding.configsvrReplSet.volumeSpec.hostPath.type</code>
Value Type	string
Example	Directory
Description	The Kubernetes <code>hostPath</code> volume type
Key	<code>sharding.configsvrReplSet.volumeSpec.persistentVolumeClaim.storageClassName</code>
Value Type	string
Example	standard
Description	The Kubernetes Storage Class to use with the Config Server container Persistent Volume Claim. Use Storage Class with XFS as the default filesystem if possible, for better MongoDB performance
Key	<code>sharding.configsvrReplSet.volumeSpec.persistentVolumeClaim.accessModes</code>
Value Type	array
Example	["ReadWriteOnce"]
Description	The Kubernetes Persistent Volume access modes for the Config Server container
Key	<code>sharding.configsvrReplSet.volumeSpec.persistentVolumeClaim.resources.requests.storage</code>
Value Type	string
Example	3Gi
Description	The Kubernetes Persistent Volume size for the Config Server container
Key	<code>sharding.mongos.size</code>
Value Type	int
Example	3
Description	The number of mongos instances within the cluster
Key	<code>sharding.mongos.configuration</code>
Value Type	string
Example	<pre> systemLog: verbosity: 1</pre>
Description	Custom configuration options for mongos. Please refer to the official manual for the full list of options
Key	<code>sharding.mongos.affinity.antiAffinityTopologyKey</code>
Value Type	string
Example	kubernetes.io/hostname
Description	The Kubernetes <code>topologyKey</code> node affinity constraint for mongos
Key	<code>sharding.mongos.affinity.advanced</code>
Value Type	subdoc
Example	

continues on next page

Table 2 – continued from previous page

Description	In cases where the Pods require complex tuning the <i>advanced</i> option turns off the <code>topologykey</code> effect. This setting allows the standard Kubernetes affinity constraints of any complexity to be used
Key	<code>sharding.mongos.tolerations.key</code>
Value Type	string
Example	<code>node.alpha.kubernetes.io/unreachable</code>
Description	The Kubernetes Pod tolerations key for mongos instances
Key	<code>sharding.mongos.tolerations.operator</code>
Value Type	string
Example	<code>Exists</code>
Description	The Kubernetes Pod tolerations operator for mongos instances
Key	<code>sharding.mongos.tolerations.effect</code>
Value Type	string
Example	<code>NoExecute</code>
Description	The Kubernetes Pod tolerations effect for mongos instances
Key	<code>sharding.mongos.tolerations.tolerationSeconds</code>
Value Type	int
Example	<code>60000</code>
Description	The Kubernetes Pod tolerations time limit for mongos instances
Key	<code>sharding.mongos.priorityClassName</code>
Value Type	string
Example	<code>high priority</code>
Description	The Kubernetes Pod priority class for mongos instances
Key	<code>sharding.mongos.annotations.iam.amazonaws.com/role</code>
Value Type	string
Example	<code>role-arn</code>
Description	The AWS IAM role for mongos instances
Key	<code>sharding.mongos.labels</code>
Value Type	label
Example	<code>rack: rack-22</code>
Description	The Kubernetes affinity labels for mongos instances
Key	<code>sharding.mongos.nodeSelector</code>
Value Type	label
Example	<code>disktype: ssd</code>
Description	The Kubernetes nodeSelector affinity constraint for mongos instances
Key	<code>sharding.mongos.runtimeClassName</code>
Value Type	string
Example	<code>image-rc</code>
Description	Name of the Kubernetes Runtime Class for mongos Pods
Key	<code>sharding.mongos.sidecars.image</code>

continues on next page

Table 2 – continued from previous page

Value Type	string
Example	busybox
Description	Image for the <i>custom sidecar container</i> for mongos Pods
Key	sharding.mongos.sidecars.command
Value Type	array
Example	["/bin/sh"]
Description	Command for the <i>custom sidecar container</i> for mongos Pods
Key	sharding.mongos.sidecars.args
Value Type	array
Example	["-c", "while true; do echo echo \$(date -u) 'test' >> /dev/null; sleep 5;done"]
Description	Command arguments for the <i>custom sidecar container</i> for mongos Pods
Key	sharding.mongos.sidecars.name
Value Type	string
Example	rs-sidecar-1
Description	Name of the <i>custom sidecar container</i> for mongos Pods
Key	sharding.mongos.limits.cpu
Value Type	string
Example	300m
Description	Kubernetes CPU limit for mongos container
Key	sharding.mongos.limits.memory
Value Type	string
Example	0.5G
Description	Kubernetes Memory limit for mongos container
Key	sharding.mongos.resources.requests.cpu
Value Type	string
Example	300m
Description	The Kubernetes CPU requests for mongos container
Key	sharding.mongos.requests.memory
Value Type	string
Example	0.5G
Description	The Kubernetes Memory requests for mongos container
Key	sharding.mongos.expose.exposeType
Value Type	string
Example	ClusterIP
Description	The IP address type to be exposed
Key	sharding.mongos.loadBalancerSourceRanges
Value	string
Example	10.0.0.0/8
Description	The range of client IP addresses from which the load balancer should be reachable (if not set, there is no limitations)

continues on next page

Table 2 – continued from previous page

Key	<code>sharding.mongos.serviceAnnotations</code>
Value	string
Example	<code>service.beta.kubernetes.io/aws-load-balancer-backend-protocol: http</code>
Description	The Kubernetes annotations metadata for the MongoDB mongos daemon
Key	<code>sharding.mongos.auditLog.destination</code>
Value Type	string
Example	
Description	Sets the <code>auditLog.destination</code> option for the MongoDB mongos daemon. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use sharding.mongos.configuration instead
Key	<code>sharding.mongos.auditLog.format</code>
Value Type	string
Example	JSON
Description	Sets the <code>auditLog.format</code> option for the MongoDB mongos daemon. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use sharding.mongos.configuration instead
Key	<code>sharding.mongos.auditLog.filter</code>
Value Type	string
Example	<code>{}</code>
Description	Sets the <code>auditLog.filter</code> option for the MongoDB mongos daemon. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use sharding.mongos.configuration instead

27.6 Mongod Section

This section contains the Mongod configuration options.

Key	<code>mongod.net.port</code>
Value Type	int
Example	27017
Description	Sets the MongoDB <code>net.port</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.net.hostport</code>
Value Type	int
Example	0
Description	Sets the Kubernetes <code>hostPort</code> option
Key	<code>mongod.security.redactClientLogData</code>
Value Type	bool
Example	false
Description	Enables/disables Percona Server for MongoDB Log Redaction . Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead

continues on next page

Table 3 – continued from previous page

Key	<code>mongod.security.enableEncryption</code>
Value Type	bool
Example	true
Description	Enables/disables Percona Server for MongoDB data at rest encryption. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.security.encryptionKeySecret</code>
Value Type	string
Example	my-cluster-name-mongodb-encryption-key
Description	Specifies a secret object with the encryption key
Key	<code>mongod.security.encryptionCipherMode</code>
Value Type	string
Example	AES256-CBC
Description	Sets Percona Server for MongoDB encryption cipher mode. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.setParameter.ttlMonitorSleepSecs</code>
Value Type	int
Example	60
Description	Sets the Percona Server for MongoDB <code>ttlMonitorSleepSecs</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.setParameter.wiredTigerConcurrentReadTransactions</code>
Value Type	int
Example	128
Description	Sets the <code>wiredTigerConcurrentReadTransactions</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.setParameter.wiredTigerConcurrentWriteTransactions</code>
Value Type	int
Example	128
Description	Sets the <code>wiredTigerConcurrentWriteTransactions</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.storage.engine</code>
Value Type	string
Example	wiredTiger
Description	Sets the <code>storage.engine</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.storage.inMemory.engineConfig.inMemorySizeRatio</code>
Value Type	float
Example	0.9
Description	The ratio used to compute the <code>storage.engine.inMemory.inMemorySizeGb</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.storage.mmapv1.nsSize</code>

continues on next page

Table 3 – continued from previous page

Value Type	int
Example	16
Description	Sets the <code>storage.mmapv1.nsSize</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.storage.mmapv1.smallfiles</code>
Value Type	bool
Example	false
Description	Sets the <code>storage.mmapv1.smallfiles</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.storage.wiredTiger.engineConfig.cacheSizeRatio</code>
Value Type	float
Example	0.5
Description	The ratio used to compute the <code>storage.wiredTiger.engineConfig.cacheSizeGB</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.storage.wiredTiger.engineConfig.directoryForIndexes</code>
Value Type	bool
Example	false
Description	Sets the <code>storage.wiredTiger.engineConfig.directoryForIndexes</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.storage.wiredTiger.engineConfig.journalCompressor</code>
Value Type	string
Example	snappy
Description	Sets the <code>storage.wiredTiger.engineConfig.journalCompressor</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.storage.wiredTiger.collectionConfig.blockCompressor</code>
Value Type	string
Example	snappy
Description	Sets the <code>storage.wiredTiger.collectionConfig.blockCompressor</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.storage.wiredTiger.indexConfig.prefixCompression</code>
Value Type	bool
Example	true
Description	Sets the <code>storage.wiredTiger.indexConfig.prefixCompression</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.operationProfiling.mode</code>
Value Type	string
Example	slowOp
Description	Sets the <code>operationProfiling.mode</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead

continues on next page

Table 3 – continued from previous page

Key	<code>mongod.operationProfiling.slowOpThresholdMs</code> . Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Value Type	int
Example	100
Description	Sets the <code>operationProfiling.slowOpThresholdMs</code> option
Key	<code>mongod.operationProfiling.rateLimit</code>
Value Type	int
Example	1
Description	Sets the <code>operationProfiling.rateLimit</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.auditLog.destination</code>
Value Type	string
Example	
Description	Sets the <code>auditLog.destination</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.auditLog.format</code>
Value Type	string
Example	JSON
Description	Sets the <code>auditLog.format</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead
Key	<code>mongod.auditLog.filter</code>
Value Type	string
Example	{}
Description	Sets the <code>auditLog.filter</code> option. Deprecated in Percona Distribution for MongoDB Operator v1.9.0+, unavailable in v1.12.0+; use replsets.configuration instead

27.7 Backup Section

The backup section in the `deploy/cr.yaml` file contains the following configuration options for the regular Percona Server for MongoDB backups.

Key	<code>backup.enabled</code>
Value Type	boolean
Example	true
Description	Enables or disables making backups
Key	<code>backup.debug</code>
Value Type	boolean
Example	true
Description	Enables or disables debug mode for backups
Key	<code>backup.restartOnFailure</code>
Value Type	boolean

continues on next page

Table 4 – continued from previous page

Example	true
Description	Enables or disables restarting the previously failed backup process
Key	backup.image
Value Type	string
Example	percona/percona-server-mongodb-operator:1.9.0-backup
Description	The Percona Server for MongoDB Docker image to use for the backup
Key	backup.serviceAccountName
Value Type	string
Example	percona-server-mongodb-operator
Description	Name of the separate privileged service account used by the Operator
Key	backup.resources.limits.cpu
Value Type	string
Example	100m
Description	Kubernetes CPU limit for backups
Key	backup.resources.limits.memory
Value Type	string
Example	0.2G
Description	Kubernetes Memory limit for backups
Key	backup.resources.requests.cpu
Value Type	string
Example	100m
Description	The Kubernetes CPU requests for backups
Key	backup.resources.requests.memory
Value Type	string
Example	0.1G
Description	The Kubernetes Memory requests for backups
Key	backup.storages.<storage-name>.type
Value	string
Example	s3
Description	The cloud storage type used for backups. Only s3 type is currently supported
Key	backup.storages.<storage-name>.s3.credentialsSecret
Value	string
Example	my-cluster-name-backup-s3
Description	The Kubernetes secret for backups. It should contain AWS_ACCESS_KEY_ID and AWS_SECRET_ACCESS_KEY keys.
Key	backup.storages.<storage-name>.s3.bucket
Value	string
Example	
Description	The Amazon S3 bucket name for backups
Key	backup.storages.s3.<storage-name>.region

continues on next page

Table 4 – continued from previous page

Value	string
Example	us-east-1
Description	The AWS region to use. Please note this option is mandatory for Amazon and all S3-compatible storages
Key	backup.storages.s3.<storage-name>.endpointUrl
Value	string
Example	
Description	The endpoint URL of the S3-compatible storage to be used (not needed for the original Amazon S3 cloud)
Key	backup.pitr.enabled
Value	boolean
Example	false
Description	Enables or disables <i>point-in-time-recovery functionality</i>
Key	backup.tasks.name
Value Type	string
Example	
Description	The name of the backup
Key	backup.tasks.enabled
Value Type	boolean
Example	true
Description	Enables or disables this exact backup
Key	backup.tasks.schedule
Value Type	string
Example	0 0 * * 6
Description	The scheduled time to make a backup, specified in the crontab format
Key	backup.tasks.keep
Value Type	int
Example	3
Description	The amount of most recent backups to store. Older backups are automatically deleted. Set keep to zero or completely remove it to disable automatic deletion of backups
Key	backup.tasks.storageName
Value Type	string
Example	st-us-west
Description	The name of the S3-compatible storage for backups, configured in the <i>storages</i> subsection
Key	backup.tasks.compressionType
Value Type	string
Example	gzip
Description	The backup compression format

PERCONA CERTIFIED IMAGES

Following table presents Percona's certified docker images to be used with the Percona Operator for Percona Server for MongoDB:

Image	Digest
percona/percona-server-mongodb-operator:1.9.0	2daab5999a3a5bc407cc63ce8ae4d18d985f636685273c6678b118d770c3c014
percona/pmm-client:2.18.0	4fd309bf3d9336e9bf853ec5e9b578562c4a69cbc577bf1c2511a3b135922830
percona/percona-server-mongodb-operator:1.9.0-backup	ae0ed563105871da37496667a9a9ae6323c32e0321c3448a9f965f7d54d0bc94
percona/percona-server-mongodb:4.4.6-8	0afd1ae855cd5090d106ba7462b0c1c73e0da7a180b46811b2f3c2149ecb7d4f
percona/percona-server-mongodb:4.4.5-7	14b419b686c0ca5cf856e2439bc213b85070ee2fe30832de0f46d1b602cc65ff
percona/percona-server-mongodb:4.4.3-5	28c137c87dc0ed3530398ee281b6998a902ca5bc39bf766f42de03b1dfc1fc57
percona/percona-server-mongodb:4.4.2-4	991d6049059e5eb1a74981290d829a5fb4ab0554993748fde1e67b2f46f26bf0
percona/percona-server-mongodb:4.2.14-15	255df9d2157eac6d9f452780b918b352da90814af0ab3210ffbe23177e6d4cf8
percona/percona-server-mongodb:4.2.13-14	5419687291e7fa1e3bf2ae1fa0340cbf72f38f8ad70c0800fa7b8c145f5e75ae
percona/percona-server-mongodb:4.2.12-13	dda89e647ea5aa1266055ef465d66a139722d9e3f78a839a90a9f081b09ce26d
percona/percona-server-mongodb:4.2.11-12	1909cb7a6ceca9bf0535b54aa86b9ae74ba2fa303c55cf4a1a54262fb0edbd3c
percona/percona-server-mongodb:4.2.8-8	a66e889d3e986413e41083a9c887f33173da05a41c8bd107cf50eede4588a505
percona/percona-server-mongodb:4.2.7-7	1d8a0859b48a3e9cadf9ad7308ec5aa4b278a64ca32ff5d887156b1b46146b13
percona/percona-server-mongodb:4.0.25-20	49a79b20cb9ae2707324ff88878f0d08747821c9448144baf889f1e80b6ccc72
percona/percona-server-mongodb:4.0.23-18	5f76442ea702633670982aa1059c495cb85d3be2fd4d7c713a832f1ab5a6f1ce
percona/percona-server-mongodb:4.0.22-17	51d8cd31489c5eefed8ed94a477f25176279c7e30b97024f69a0a76a3d55e64e
percona/percona-server-mongodb:4.0.21-15	663f6eb98ae625792d59c6072b5d3a3095112380de67097a411f597d785c423a
percona/percona-server-mongodb:4.0.20-13	badef1eb2807b0b27a2298f697388f1dffa5398d5caa306a65fc41b98f7a72e3
percona/percona-server-mongodb:4.0.19-12	24a8214d84c3a9a4147c12c4c159d4a1aa3dae831859f77b3db1a563a268e2bf
percona/percona-server-mongodb:4.0.18	bf9e69712868f7e93daef22c14c083bbb2a74d3028d78d8597b2aeacda340c69

PERCONA DISTRIBUTION FOR MONGODB OPERATOR API DOCUMENTATION

Percona Distribution for MongoDB Operator provides an [aggregation-layer extension for the Kubernetes API](#). Please refer to the [official Kubernetes API documentation](#) on the API access and usage details. The following subsections describe the Percona XtraDB Cluster API provided by the Operator.

- *Prerequisites*
- *Create new Percona Server for MongoDB cluster*
- *List Percona Server for MongoDB clusters*
- *Get status of Percona Server for MongoDB cluster*
- *Scale up/down Percona Server for MongoDB cluster*
- *Update Percona Server for MongoDB cluster image*
- *Backup Percona Server for MongoDB cluster*
- *Restore Percona Server for MongoDB cluster*

29.1 Prerequisites

1. Create the namespace name you will use, if not exist:

```
kubectl create namespace my-namespace-name
```

Trying to create an already-existing namespace will show you a self-explanatory error message. Also, you can use the default namespace.

Note: In this document `default` namespace is used in all examples. Substitute `default` with your namespace name if you use a different one.

2. Prepare:

```
# set correct API address
KUBE_CLUSTER=$(kubectl config view --minify -o jsonpath='{.clusters[0].name}')
API_SERVER=$(kubectl config view -o jsonpath="{.clusters[?(@.name==\"$KUBE_CLUSTER\
↪\")].cluster.server}" | sed -e 's#https://##')
```

(continues on next page)

(continued from previous page)

```
# create service account and get token
kubectl apply -f deploy/crd.yaml -f deploy/rbac.yaml -n default
KUBE_TOKEN=$(kubectl get secret $(kubectl get serviceaccount percona-server-mongodb-
↪operator -o jsonpath='{.secrets[0].name}' -n default) -o jsonpath='{.data.token}' -
↪-n default | base64 --decode )
```

29.2 Create new Percona Server for MongoDB cluster

Description:

The `command` to create a new Percona Server `for` MongoDB cluster

Kubectl Command:

```
kubectl apply -f percona-server-mongodb-operator/deploy/cr.yaml
```

URL:

```
https://$API_SERVER/apis/psmdb.percona.com/v1-9-0/namespaces/default/
↪perconaservermongodbbs
```

Authentication:

Authorization: Bearer `$KUBE_TOKEN`

cURL Request:

```
curl -k -v -XPOST "https://$API_SERVER/apis/psmdb.percona.com/v1-9-0/namespaces/default/
↪perconaservermongodbbs" \
-H "Content-Type: application/json" \
-H "Accept: application/json" \
-H "Authorization: Bearer $KUBE_TOKEN" \
-d "@cluster.json"
```

Request Body (cluster.json):

JSON:

```
{
  "apiVersion": "psmdb.percona.com/v1-5-0",
  "kind": "PerconaServerMongoDB",
  "metadata": {
    "name": "my-cluster-name"
  },
  "spec": {
    "image": "percona/percona-server-mongodb:4.2.8-8",
    "imagePullPolicy": "Always",
    "allowUnsafeConfigurations": false,
    "updateStrategy": "SmartUpdate",
    "secrets": {
      "users": "my-cluster-name-secrets"
    }
  }
}
```

(continues on next page)

(continued from previous page)

```

    },
    "pmm": {
      "enabled": false,
      "image": "percona/percona-server-mongodb-operator:1.5.0-pmm",
      "serverHost": "monitoring-service"
    },
    "replsets": [
      {
        "name": "rs0",
        "size": 3,
        "affinity": {
          "antiAffinityTopologyKey": "none"
        },
        "podDisruptionBudget": {
          "maxUnavailable": 1
        },
        "expose": {
          "enabled": false,
          "exposeType": "LoadBalancer"
        },
        "arbiter": {
          "enabled": false,
          "size": 1,
          "affinity": {
            "antiAffinityTopologyKey": "none"
          }
        },
        "resources": {
          "limits": null
        },
        "volumeSpec": {
          "persistentVolumeClaim": {
            "storageClassName": "standard",
            "accessModes": [
              "ReadWriteOnce"
            ],
            "resources": {
              "requests": {
                "storage": "3Gi"
              }
            }
          }
        }
      }
    ],
    "mongod": {
      "net": {
        "port": 27017,
        "hostPort": 0
      },
      "security": {
        "redactClientLogData": false,

```

(continues on next page)

(continued from previous page)

```

    "enableEncryption": true,
    "encryptionKeySecret": "my-cluster-name-mongodb-encryption-key",
    "encryptionCipherMode": "AES256-CBC"
  },
  "setParameter": {
    "ttlMonitorSleepSecs": 60,
    "wiredTigerConcurrentReadTransactions": 128,
    "wiredTigerConcurrentWriteTransactions": 128
  },
  "storage": {
    "engine": "wiredTiger",
    "inMemory": {
      "engineConfig": {
        "inMemorySizeRatio": 0.9
      }
    },
  },
  "mmapv1": {
    "nsSize": 16,
    "smallfiles": false
  },
  "wiredTiger": {
    "engineConfig": {
      "cacheSizeRatio": 0.5,
      "directoryForIndexes": false,
      "journalCompressor": "snappy"
    },
    "collectionConfig": {
      "blockCompressor": "snappy"
    },
    "indexConfig": {
      "prefixCompression": true
    }
  },
  "operationProfiling": {
    "mode": "slowOp",
    "slowOpThresholdMs": 100,
    "rateLimit": 100
  },
  "backup": {
    "enabled": true,
    "restartOnFailure": true,
    "image": "percona/percona-server-mongodb-operator:1.5.0-backup",
    "serviceAccountName": "percona-server-mongodb-operator",
    "storages": null,
    "tasks": null
  }
}

```

Inputs:

Metadata:

1. Name (String, min-length: 1) : contains name of cluster

Spec:

1. secrets[users] (String, min-length: 1) : contains name of secret for the users
2. allowUnsafeConfigurations (Boolean, Default: false) : allow unsafe configurations to run
3. image (String, min-length: 1) : name of the Percona Server for MongoDB cluster image

replsets:

1. name (String, min-length: 1) : name of monogo replicaset
2. size (Integer, min-value: 1) : contains size of MongoDB replicaset
3. expose[exposeType] (Integer, min-value: 1) : type of service to expose replicaset
4. arbiter (Object) : configuration for mongo arbiter

mongod:

1. net:
 1. port (Integer, min-value: 0) : contains mongod container port
 2. hostPort (Integer, min-value: 0) : host port to expose mongod on
2. security:
 1. enableEncryption (Boolean, Default: true) : enable encrypting mongod storage
 2. encryptionKeySecret (String, min-length: 1) : name of encryption key secret
 3. encryptionCipherMode (String, min-length: 1) : type of encryption cipher to use
3. setParameter (Object) : configure mongod enginer paramters
4. storage:
 1. engine (String, min-length: 1, default "wiredTiger") : name of mongod storage engine
 2. inMemory (Object) : wiredTiger engine configuration
 3. wiredTiger (Object) : wiredTiger engine configuration

pmm:

1. serverHost (String, min-length: 1) : serivce name for monitoring
2. image (String, min-length: 1) : name of pmm image

backup:

1. image (String, min-length: 1) : name of MngoDB backup docker image
2. serviceAccountName (String, min-length: 1) name of service account to use for backup
3. storages (Object) : storage configuration object for backup

Response:

JSON

```

{
  "apiVersion": "psmdb.percona.com/v1-5-0",
  "kind": "PerconaServerMongoDB",
  "metadata": {
    "annotations": {
      "kubect1.kubernetes.io/last-applied-configuration": "{\"apiVersion\":\"psmdb.
→ percona.com/v1-5-0\", \"kind\":\"PerconaServerMongoDB\", \"metadata\":{\"annotations\":{}}
→ , \"name\":\"my-cluster-name\", \"namespace\":\"default\"}, \"spec\":{\"
→ \"allowUnsafeConfigurations\":false, \"backup\":{\"enabled\":true, \"image\":\"percona/
→ percona-server-mongodb-operator:1.5.0-backup\", \"restartOnFailure\":true,
→ \"serviceName\":\"percona-server-mongodb-operator\", \"storage\":null, \"tasks\
→ :null}, \"image\":\"percona/percona-server-mongodb:4.2.8-8\", \"imagePullPolicy\":\"
→ Always\", \"mongod\":{\"net\":{\"hostPort\":0, \"port\":27017}, \"operationProfiling\":{\"
→ mode\":\"slowOp\", \"rateLimit\":100, \"slowOpThresholdMs\":100}, \"security\":{\"
→ \"enableEncryption\":true, \"encryptionCipherMode\":\"AES256-CBC\", \"encryptionKeySecret\
→ \": \"my-cluster-name-mongodb-encryption-key\", \"redactClientLogData\":false},
→ \"setParameter\":{\"ttlMonitorSleepSecs\":60, \"wiredTigerConcurrentReadTransactions\
→ \":128, \"wiredTigerConcurrentWriteTransactions\":128}, \"storage\":{\"engine\":\"
→ wiredTiger\", \"inMemory\":{\"engineConfig\":{\"inMemorySizeRatio\":0.9}}, \"mmapv1\":{\"
→ nsSize\":16, \"smallfiles\":false}, \"wiredTiger\":{\"collectionConfig\":{\"
→ \"blockCompressor\":\"snappy\", \"engineConfig\":{\"cacheSizeRatio\":0.5,
→ \"directoryForIndexes\":false, \"journalCompressor\":\"snappy\", \"indexConfig\":{\"
→ \"prefixCompression\":true}}}}, \"pmm\":{\"enabled\":false, \"image\":\"percona/percona-
→ server-mongodb-operator:1.5.0-pmm\", \"serverHost\":\"monitoring-service\", \"replsets\
→ \": [{\"affinity\":{\"antiAffinityTopologyKey\":\"none\"}, \"arbiter\":{\"affinity\":{\"
→ \"antiAffinityTopologyKey\":\"none\"}, \"enabled\":false, \"size\":1}, \"expose\":{\"
→ \"enabled\":false, \"exposeType\":\"LoadBalancer\"}, \"name\":\"rs0\",
→ \"podDisruptionBudget\":{\"maxUnavailable\":1}, \"resources\":{\"limits\":null, \"size\
→ \":3, \"volumeSpec\":{\"persistentVolumeClaim\":{\"accessModes\":[\"ReadWriteOnce\"],
→ \"resources\":{\"requests\":{\"storage\":\"3Gi\"}}, \"storageClassName\":\"standard\"}}}}
→ ], \"secrets\":{\"users\":\"my-cluster-name-secrets\"}, \"updateStrategy\":\"SmartUpdate\
→ \"}}}\n"
    },
    "creationTimestamp": "2020-07-24T14:27:58Z",
    "generation": 1,
    "managedFields": [
      {
        "apiVersion": "psmdb.percona.com/v1-5-0",
        "fieldsType": "FieldsV1",
        "fieldsV1": {
          "f:metadata": {
            "f:annotations": {
              ".": {
                "kubect1.kubernetes.io/last-applied-configuration": {
                  "apiVersion": "psmdb.percona.com/v1-5-0",
                  "kind": "PerconaServerMongoDB",
                  "metadata": {
                    "annotations": {
                      "kubect1.kubernetes.io/last-applied-configuration": {
                        "apiVersion": "psmdb.percona.com/v1-5-0",
                        "kind": "PerconaServerMongoDB",
                        "metadata": {
                          "annotations": {
                            "kubect1.kubernetes.io/last-applied-configuration": {
                              "apiVersion": "psmdb.percona.com/v1-5-0",
                              "kind": "PerconaServerMongoDB",
                              "metadata": {
                                "annotations": {
                                  "kubect1.kubernetes.io/last-applied-configuration": {
                                    "apiVersion": "psmdb.percona.com/v1-5-0",
                                    "kind": "PerconaServerMongoDB",
                                    "metadata": {
                                      "annotations": {
                                        "kubect1.kubernetes.io/last-applied-configuration": {
                                          "apiVersion": "psmdb.percona.com/v1-5-0",
                                          "kind": "PerconaServerMongoDB",
                                          "metadata": {
                                            "annotations": {
                                              "kubect1.kubernetes.io/last-applied-configuration": {
                                                "apiVersion": "psmdb.percona.com/v1-5-0",
                                                "kind": "PerconaServerMongoDB",
                                                "metadata": {
                                                  "annotations": {
                                                    "kubect1.kubernetes.io/last-applied-configuration": {
                                                      "apiVersion": "psmdb.percona.com/v1-5-0",
                                                      "kind": "PerconaServerMongoDB",
                                                      "metadata": {
                                                        "annotations": {
                                                          "kubect1.kubernetes.io/last-applied-configuration": {
                                                            "apiVersion": "psmdb.percona.com/v1-5-0",
                                                            "kind": "PerconaServerMongoDB",
                                                            "metadata": {
                                                              "annotations": {
                                                                "kubect1.kubernetes.io/last-applied-configuration": {
                                                                  "apiVersion": "psmdb.percona.com/v1-5-0",
                                                                  "kind": "PerconaServerMongoDB",
                                                                  "metadata": {
                                                                    "annotations": {
                                                                      "kubect1.kubernetes.io/last-applied-configuration": {
                                                                        "apiVersion": "psmdb.percona.com/v1-5-0",
                                                                        "kind": "PerconaServerMongoDB",
                                                                        "metadata": {
                                                                          "annotations": {
                                                                            "kubect1.kubernetes.io/last-applied-configuration": {
                                                                              "apiVersion": "psmdb.percona.com/v1-5-0",
                                                                              "kind": "PerconaServerMongoDB",
                                                                              "metadata": {
                                                                                "annotations": {
                                                                                  "kubect1.kubernetes.io/last-applied-configuration": {
                                                                                    "apiVersion": "psmdb.percona.com/v1-5-0",
                                                                                    "kind": "PerconaServerMongoDB",
                                                                                    "metadata": {
                                                                                      "annotations": {
                                                                                        "kubect1.kubernetes.io/last-applied-configuration": {
                                                                                          "apiVersion": "psmdb.percona.com/v1-5-0",
                                                                                          "kind": "PerconaServerMongoDB",
                                                                                          "metadata": {
                                                                                           ...

```

(continues on next page)

(continued from previous page)

```
    },
    "f:allowUnsafeConfigurations":{
    },
    "f:backup":{
      ".":{
      },
      "f:enabled":{
      },
      "f:image":{
      },
      "f:restartOnFailure":{
      },
      "f:serviceAccountName":{
      },
      "f:storages":{
      },
      "f:tasks":{
      }
    },
    "f:image":{
    },
    "f:imagePullPolicy":{
    },
    "f:mongod":{
      ".":{
      },
      "f:net":{
        ".":{
        },
        "f:hostPort":{
        },
        "f:port":{
        }
      },
      "f:operationProfiling":{
        ".":{
        },
      },
    },
  },
```

(continues on next page)

(continued from previous page)

```

    "f:mode":{
    },
    "f:rateLimit":{
    },
    "f:slowOpThresholdMs":{
    }
  },
  "f:security":{
    ".":{
    },
    "f:enableEncryption":{
    },
    "f:encryptionCipherMode":{
    },
    "f:encryptionKeySecret":{
    },
    "f:redactClientLogData":{
    }
  },
  "f:setParameter":{
    ".":{
    },
    "f:ttlMonitorSleepSecs":{
    },
    "f:wiredTigerConcurrentReadTransactions":{
    },
    "f:wiredTigerConcurrentWriteTransactions":{
    }
  },
  "f:storage":{
    ".":{
    },
    "f:engine":{
    },
    "f:inMemory":{
      ".":{
    },

```

(continues on next page)

(continued from previous page)

```
"f:engineConfig":{
  ".":{

  },
  "f:inMemorySizeRatio":{

  }
},
"f:mmapv1":{
  ".":{

  },
  "f:nsSize":{

  },
  "f:smallfiles":{

  }
},
"f:wiredTiger":{
  ".":{

  },
  "f:collectionConfig":{
    ".":{

    },
    "f:blockCompressor":{

    }
  },
  "f:engineConfig":{
    ".":{

    },
    "f:cacheSizeRatio":{

    },
    "f:directoryForIndexes":{

    },
    "f:journalCompressor":{

    }
  },
  "f:indexConfig":{
    ".":{

    },
    "f:prefixCompression":{
```

(continues on next page)

(continued from previous page)

```

        }
      }
    }
  },
  "f:pmm":{
    ".":{

    },
    "f:enabled":{

    },
    "f:image":{

    },
    "f:serverHost":{

    }
  },
  "f:replsets":{

  },
  "f:secrets":{
    ".":{

    },
    "f:users":{

    }
  },
  "f:updateStrategy":{

  }
},
"manager":"kubectl",
"operation":"Update",
"time":"2020-07-24T14:27:58Z"
},
],
"name":"my-cluster-name",
"namespace":"default",
"resourceVersion":"1268922",
"selfLink":"/apis/psmdb.percona.com/v1-5-0/namespaces/default/
↪perconaservermongodbs/my-cluster-name",
"uid":"5207e71a-c83f-4707-b892-63aa93fb615c"
},
"spec":{
  "allowUnsafeConfigurations":false,
  "backup":{
    "enabled":true,
    "image":"percona/percona-server-mongodb-operator:1.5.0-backup",

```

(continues on next page)

(continued from previous page)

```

    "restartOnFailure": true,
    "serviceAccountName": "percona-server-mongodb-operator",
    "storages": null,
    "tasks": null
  },
  "image": "percona/percona-server-mongodb:4.2.8-8",
  "imagePullPolicy": "Always",
  "mongod": {
    "net": {
      "hostPort": 0,
      "port": 27017
    },
    "operationProfiling": {
      "mode": "slowOp",
      "rateLimit": 100,
      "slowOpThresholdMs": 100
    },
    "security": {
      "enableEncryption": true,
      "encryptionCipherMode": "AES256-CBC",
      "encryptionKeySecret": "my-cluster-name-mongodb-encryption-key",
      "redactClientLogData": false
    },
    "setParameter": {
      "ttlMonitorSleepSecs": 60,
      "wiredTigerConcurrentReadTransactions": 128,
      "wiredTigerConcurrentWriteTransactions": 128
    },
    "storage": {
      "engine": "wiredTiger",
      "inMemory": {
        "engineConfig": {
          "inMemorySizeRatio": 0.9
        }
      },
      "mmapv1": {
        "nsSize": 16,
        "smallfiles": false
      },
      "wiredTiger": {
        "collectionConfig": {
          "blockCompressor": "snappy"
        },
        "engineConfig": {
          "cacheSizeRatio": 0.5,
          "directoryForIndexes": false,
          "journalCompressor": "snappy"
        },
        "indexConfig": {
          "prefixCompression": true
        }
      }
    }
  }
}

```

(continues on next page)

(continued from previous page)

```

    }
  },
  "pmm":{
    "enabled":false,
    "image":"percona/percona-server-mongodb-operator:1.5.0-pmm",
    "serverHost":"monitoring-service"
  },
  "replsets":[
    {
      "affinity":{
        "antiAffinityTopologyKey":"none"
      },
      "arbiter":{
        "affinity":{
          "antiAffinityTopologyKey":"none"
        },
        "enabled":false,
        "size":1
      },
      "expose":{
        "enabled":false,
        "exposeType":"LoadBalancer"
      },
      "name":"rs0",
      "podDisruptionBudget":{
        "maxUnavailable":1
      },
      "resources":{
        "limits":null
      },
      "size":3,
      "volumeSpec":{
        "persistentVolumeClaim":{
          "accessModes":[
            "ReadWriteOnce"
          ],
          "resources":{
            "requests":{
              "storage":"3Gi"
            }
          },
          "storageClassName":"standard"
        }
      }
    }
  ],
  "secrets":{
    "users":"my-cluster-name-secrets"
  },
  "updateStrategy":"SmartUpdate"
}

```

29.3 List Percona Server for MongoDB clusters

Description:

Lists all Percona Server **for** MongoDB clusters that exist **in** your kubernetes cluster

Kubectl Command:

```
kubectl get psmdb
```

URL:

```
https://$API_SERVER/apis/psmdb.percona.com/v1/namespaces/default/perconaservermongodbs?
↳limit=500
```

Authentication:

Authorization: Bearer \$KUBE_TOKEN

cURL Request:

```
curl -k -v -XGET "https://$API_SERVER/apis/psmdb.percona.com/v1/namespaces/default/
↳perconaservermongodbs?limit=500" \
    -H "Accept: application/json;as=Table;v=v1;g=meta.k8s.io,application/json;
↳as=Table;v=v1beta1;g=meta.k8s.io,application/json" \
    -H "Authorization: Bearer $KUBE_TOKEN"
```

Request Body:

None

Response:

JSON:

```
{
  "kind": "Table",
  "apiVersion": "meta.k8s.io/v1",
  "metadata": {
    "selfLink": "/apis/psmdb.percona.com/v1/namespaces/default/perconaservermongodbs",
    "resourceVersion": "1273793"
  },
  "columnDefinitions": [
    {
      "name": "Name",
      "type": "string",
      "format": "name",
      "description": "Name must be unique within a namespace. Is required when
↳creating resources, although some resources may allow a client to request the
↳generation of an appropriate name automatically. Name is primarily intended for
↳creation idempotence and configuration definition. Cannot be updated. More info: http://
↳kubernetes.io/docs/user-guide/identifiers#names",
      "priority": 0
    },
  ],
}
```

(continues on next page)

(continued from previous page)

```

    {
      "name": "Status",
      "type": "string",
      "format": "",
      "description": "Custom resource definition column (in JSONPath format): .status.
↪state",
      "priority": 0
    },
    {
      "name": "Age",
      "type": "date",
      "format": "",
      "description": "Custom resource definition column (in JSONPath format): .
↪metadata.creationTimestamp",
      "priority": 0
    }
  ],
  "rows": [
    {
      "cells": [
        "my-cluster-name",
        "ready",
        "37m"
      ],
      "object": {
        "kind": "PartialObjectMetadata",
        "apiVersion": "meta.k8s.io/v1",
        "metadata": {
          "name": "my-cluster-name",
          "namespace": "default",
          "selfLink": "/apis/psmdb.percona.com/v1/namespaces/default/
↪perconaservermongodb/my-cluster-name",
          "uid": "5207e71a-c83f-4707-b892-63aa93fb615c",
          "resourceVersion": "1273788",
          "generation": 1,
          "creationTimestamp": "2020-07-24T14:27:58Z",
          "annotations": {
            "kubect1.kubernetes.io/last-applied-configuration": "{\n\"apiVersion\":\n
↪\"psmdb.percona.com/v1-5-0\", \"kind\": \"PerconaServerMongoDB\", \"metadata\": {\n
↪\"annotations\": { }, \"name\": \"my-cluster-name\", \"namespace\": \"default\", \"spec\": {\n
↪\"allowUnsafeConfigurations\": false, \"backup\": { \"enabled\": true, \"image\": \"percona/
↪percona-server-mongodb-operator:1.5.0-backup\", \"restartOnFailure\": true, \n
↪\"serviceName\": \"percona-server-mongodb-operator\", \"storages\": null, \"tasks\
↪\": null}, \"image\": \"percona/percona-server-mongodb:4.2.8-8\", \"imagePullPolicy\": \n
↪\"Always\", \"mongod\": { \"net\": { \"hostPort\": 0, \"port\": 27017}, \"operationProfiling\": {\n
↪\"mode\": \"slowOp\", \"rateLimit\": 100, \"slowOpThresholdMs\": 100}, \"security\": {\n
↪\"enableEncryption\": true, \"encryptionCipherMode\": \"AES256-CBC\", \"encryptionKeySecret\
↪\": \"my-cluster-name-mongodb-encryption-key\", \"redactClientLogData\": false}, \n
↪\"setParameter\": { \"ttlMonitorSleepSecs\": 60, \"wiredTigerConcurrentReadTransactions\
↪\": 128, \"wiredTigerConcurrentWriteTransactions\": 128}, \"storage\": { \"engine\": \n
↪\"wiredTiger\", \"inMemory\": { \"engineConfig\": { \"inMemorySizeRatio\": 0.9}}, \"mmapv1\": {\n
↪\"nsSize\": 16, \"smallfiles\": false}, \"wiredTiger\": { \"collectionConfig\": {\n
↪\"blockCompressor\": \"snappy\", \"engineConfig\": { \"cacheSizeRatio\": 0.5, \n
↪\"directoryForIndexes\": false, \"journalCompressor\": \"snappy\", \"indexConfig\": {\n
↪\"prefixCompression\": true}}}, \"pmm\": { \"enabled\": false, \"image\": \"percona/percona-
132 Server-mongodb-operator:1.5.0-pmm\", \"serverHost\": \"monitoring-service\", \"replaces
↪\": [{ \"affinity\": { \"antiAffinityTopologyKey\": \"none\"}, \"arbiter\": { \"affinity\": {\n
↪\"antiAffinityTopologyKey\": \"none\"}, \"enabled\": false, \"size\": 1}, \"expose\": {\n
↪\"enabled\": false, \"exposeType\": \"LoadBalancer\"}, \"name\": \"rs0\", \n

```


(continued from previous page)

```

    },
    "managedFields": [
      {
        "manager": "kubectl",
        "operation": "Update",
        "apiVersion": "psmdb.percona.com/v1-5-0",
        "time": "2020-07-24T14:27:58Z",
        "fieldsType": "FieldsV1",
        "fieldsV1": {
          "f:metadata": {
            "f:annotations": {
              ".": {
                },
                "f:kubectl.kubernetes.io/last-applied-configuration": {
                }
              }
            }
          },
          "f:spec": {
            ".": {
              },
              "f:allowUnsafeConfigurations": {
              },
              "f:backup": {
                ".": {
                },
                "f:enabled": {
                },
                "f:image": {
                },
                "f:serviceAccountName": {
                }
              }
            },
            "f:image": {
            },
            "f:imagePullPolicy": {
            },
            "f:mongod": {
              ".": {
                },
                "f:net": {
                  ".": {

```

(continues on next page)

(continued from previous page)

```
    },
    "f:port":{
    }
  },
  "f:operationProfiling":{
    ".":{
    },
    "f:mode":{
    },
    "f:rateLimit":{
    },
    "f:slowOpThresholdMs":{
    }
  },
  "f:security":{
    ".":{
    },
    "f:enableEncryption":{
    },
    "f:encryptionCipherMode":{
    },
    "f:encryptionKeySecret":{
    }
  },
  "f:setParameter":{
    ".":{
    },
    "f:tTLMonitorSleepSecs":{
    },
    "f:wiredTigerConcurrentReadTransactions":{
    },
    "f:wiredTigerConcurrentWriteTransactions":{
    }
  },
  "f:storage":{
    ".":{
    },
  },
}
```

(continues on next page)

(continued from previous page)

```
"f:engine":{
  },
  "f:inMemory":{
    ".":{

    },
    "f:engineConfig":{
      ".":{

      },
      "f:inMemorySizeRatio":{

      }
    }
  },
  "f:mmapv1":{
    ".":{

    },
    "f:nsSize":{

    }
  },
  "f:wiredTiger":{
    ".":{

    },
    "f:collectionConfig":{
      ".":{

      },
      "f:blockCompressor":{

      }
    },
    "f:engineConfig":{
      ".":{

      },
      "f:cacheSizeRatio":{

      },
      "f:journalCompressor":{

      }
    },
    "f:indexConfig":{
      ".":{

      },
      "f:prefixCompression":{
```

(continues on next page)

(continued from previous page)

```

        }
      }
    }
  },
  "f:pmm":{
    ".":{

    },
    "f:image":{

    },
    "f:serverHost":{

    }
  },
  "f:secrets":{
    ".":{

    },
    "f:users":{

    }
  },
  "f:updateStrategy":{

  }
}
},
{
  "manager":"percona-server-mongodb-operator",
  "operation":"Update",
  "apiVersion":"psmdb.percona.com/v1",
  "time":"2020-07-24T15:04:55Z",
  "fieldsType":"FieldsV1",
  "fieldsV1":{
    "f:spec":{
      "f:backup":{
        "f:containerSecurityContext":{
          ".":{

          },
          "f:runAsNonRoot":{

          },
          "f:runAsUser":{

          }
        },
        "f:podSecurityContext":{

```

(continues on next page)

(continued from previous page)

```

        ".":{
        },
        "f:fsGroup":{
        }
    },
    "f:clusterServiceDNSSuffix":{
    },
    "f:replsets":{
    },
    "f:runUid":{
    },
    "f:secrets":{
        "f:ssl":{
        },
        "f:sslInternal":{
        }
    }
},
"f:status":{
    ".":{
    },
    "f:conditions":{
    },
    "f:observedGeneration":{
    },
    "f:replsets":{
        ".":{
        },
        "f:rs0":{
            ".":{
            },
            "f:ready":{
            },
            "f:size":{
            },
            "f:status":{

```

(continues on next page)

(continued from previous page)

```

    }
  },
  "f:state":{
    }
  }
}
]
}
]
}

```

29.4 Get status of Percona Server for MongoDB cluster

Description:

Gets all information about specified Percona Server **for** MongoDB cluster

Kubectl Command:

```
kubectl get psmdb/my-cluster-name -o json
```

URL:

`https://$API_SERVER/apis/psmdb.percona.com/v1/namespaces/default/perconaservermongodbs/
↪my-cluster-name`

Authentication:

Authorization: Bearer `$KUBE_TOKEN`

cURL Request:

```
curl -k -v -XGET "https://$API_SERVER/apis/psmdb.percona.com/v1/namespaces/default/  
↪perconaservermongodbs/my-cluster-name" \  
-H "Accept: application/json" \  
-H "Authorization: Bearer $KUBE_TOKEN"
```

Request Body:

None

Response:

JSON:

```

{
  "apiVersion": "psmdb.percona.com/v1",
  "kind": "PerconaServerMongoDB",
  "metadata": {
    "annotations": {
      "kubect1.kubernetes.io/last-applied-configuration": "{\"apiVersion\":\"psmdb.\n
→ percona.com/v1-5-0\", \"kind\": \"PerconaServerMongoDB\", \"metadata\": { \"annotations\": { }\n
→ , \"name\": \"my-cluster-name\", \"namespace\": \"default\" }, \"spec\": { \n
→ \"allowUnsafeConfigurations\": false, \"backup\": { \"enabled\": true, \"image\": \"percona/\n
→ percona-server-mongodb-operator:1.5.0-backup\", \"restartOnFailure\": true, \n
→ \"serviceName\": \"percona-server-mongodb-operator\", \"storage\": null, \"tasks\":\n
→ : null }, \"image\": \"percona/percona-server-mongodb:4.2.8-8\", \"imagePullPolicy\": \"\n
→ Always\", \"mongod\": { \"net\": { \"hostPort\": 0, \"port\": 27017 }, \"operationProfiling\": { \n
→ \"mode\": \"slowOp\", \"rateLimit\": 100, \"slowOpThresholdMs\": 100 }, \"security\": { \n
→ \"enableEncryption\": true, \"encryptionCipherMode\": \"AES256-CBC\", \"encryptionKeySecret\":\n
→ : \"my-cluster-name-mongodb-encryption-key\", \"redactClientLogData\": false }, \n
→ \"setParameter\": { \"ttlMonitorSleepSecs\": 60, \"wiredTigerConcurrentReadTransactions\":\n
→ : 128, \"wiredTigerConcurrentWriteTransactions\": 128 }, \"storage\": { \"engine\": \"\n
→ wiredTiger\", \"inMemory\": { \"engineConfig\": { \"inMemorySizeRatio\": 0.9 }, \"mmapv1\": { \n
→ \"nsSize\": 16, \"smallfiles\": false }, \"wiredTiger\": { \"collectionConfig\": { \n
→ \"blockCompressor\": \"snappy\", \"engineConfig\": { \"cacheSizeRatio\": 0.5, \n
→ \"directoryForIndexes\": false, \"journalCompressor\": \"snappy\", \"indexConfig\": { \n
→ \"prefixCompression\": true } } } }, \"pmm\": { \"enabled\": false, \"image\": \"percona/percona-\n
→ server-mongodb-operator:1.5.0-pmm\", \"serverHost\": \"monitoring-service\", \"replsets\":\n
→ : [ { \"affinity\": { \"antiAffinityTopologyKey\": \"none\" }, \"arbiter\": { \"affinity\": { \n
→ \"antiAffinityTopologyKey\": \"none\" }, \"enabled\": false, \"size\": 1 }, \"expose\": { \n
→ \"enabled\": false, \"exposeType\": \"LoadBalancer\" }, \"name\": \"rs0\", \n
→ \"podDisruptionBudget\": { \"maxUnavailable\": 1 }, \"resources\": { \"limits\": null }, \"size\":\n
→ : 3, \"volumeSpec\": { \"persistentVolumeClaim\": { \"accessModes\": [ \"ReadWriteOnce\" ], \n
→ \"resources\": { \"requests\": { \"storage\": \"3Gi\" } } }, \"storageClassName\": \"standard\" } } }\n
→ ], \"secrets\": { \"users\": \"my-cluster-name-secrets\", \"updateStrategy\": \"SmartUpdate\"\n
→ } } } \n\"
    },
    "creationTimestamp": "2020-07-24T14:27:58Z",
    "generation": 1,
    "managedFields": [
      {
        "apiVersion": "psmdb.percona.com/v1-5-0",
        "fieldsType": "FieldsV1",
        "fieldsV1": {
          "f:metadata": {
            "f:annotations": {
              ".": {
                },
                "f:kubect1.kubernetes.io/last-applied-configuration": {
                }
              }
            },
            "f:spec": {
              ".": {

```

(continues on next page)

(continued from previous page)

```
    },
    "f:allowUnsafeConfigurations":{
    },
    "f:backup":{
      ".":{
      },
      "f:enabled":{
      },
      "f:image":{
      },
      "f:serviceAccountName":{
      }
    },
    "f:image":{
    },
    "f:imagePullPolicy":{
    },
    "f:mongod":{
      ".":{
      },
      "f:net":{
        ".":{
        },
        "f:port":{
        }
      },
      "f:operationProfiling":{
        ".":{
        },
        "f:mode":{
        },
        "f:rateLimit":{
        },
        "f:slowOpThresholdMs":{
        }
      },
      "f:security":{
        ".":{

```

(continues on next page)

(continued from previous page)

```

    },
    "f:enableEncryption":{
    },
    "f:encryptionCipherMode":{
    },
    "f:encryptionKeySecret":{
    }
  },
  "f:setParameter":{
    ".":{
    },
    "f:ttlMonitorSleepSecs":{
    },
    "f:wiredTigerConcurrentReadTransactions":{
    },
    "f:wiredTigerConcurrentWriteTransactions":{
    }
  },
  "f:storage":{
    ".":{
    },
    "f:engine":{
    },
    "f:inMemory":{
      ".":{
      },
      "f:engineConfig":{
        ".":{
        },
        "f:inMemorySizeRatio":{
        }
      }
    }
  },
  "f:mmapv1":{
    ".":{
    },
    "f:nsSize":{

```

(continues on next page)

(continued from previous page)

```

    }
  },
  "f:wiredTiger":{
    ".":{

    },
    "f:collectionConfig":{
      ".":{

      },
      "f:blockCompressor":{

      }
    },
    "f:engineConfig":{
      ".":{

      },
      "f:cacheSizeRatio":{

      },
      "f:journalCompressor":{

      }
    },
    "f:indexConfig":{
      ".":{

      },
      "f:prefixCompression":{

      }
    }
  }
},
"f:pmm":{
  ".":{

  },
  "f:image":{

  },
  "f:serverHost":{

  }
},
"f:secrets":{
  ".":{

  },
  "f:users":{

```

(continues on next page)

(continued from previous page)

```

        }
      },
      "f:updateStrategy":{
        }
    },
    "manager":"kubectl",
    "operation":"Update",
    "time":"2020-07-24T14:27:58Z"
  },
  {
    "apiVersion":"psmdb.percona.com/v1",
    "fieldsType":"FieldsV1",
    "fieldsV1":{
      "f:spec":{
        "f:backup":{
          "f:containerSecurityContext":{
            ".":{

            },
            "f:runAsNonRoot":{

            },
            "f:runAsUser":{

            }
          },
          "f:podSecurityContext":{
            ".":{

            },
            "f:fsGroup":{

            }
          }
        },
        "f:clusterServiceDNSSuffix":{

        },
        "f:replsets":{

        },
        "f:runUid":{

        },
        "f:secrets":{
          "f:ssl":{

          },
          "f:sslInternal":{

```

(continues on next page)

(continued from previous page)

```

        }
      },
      "f:status":{
        ".":{

        },
        "f:conditions":{

        },
        "f:observedGeneration":{

        },
        "f:replsets":{
          ".":{

          },
          "f:rs0":{
            ".":{

            },
            "f:ready":{

            },
            "f:size":{

            },
            "f:status":{

            }
          }
        },
        "f:state":{

        }
      },
      "manager":"percona-server-mongodb-operator",
      "operation":"Update",
      "time":"2020-07-24T15:09:40Z"
    }
  ],
  "name":"my-cluster-name",
  "namespace":"default",
  "resourceVersion":"1274523",
  "selfLink":"/apis/psmdb.percona.com/v1/namespaces/default/perconaservermongodbbs/my-
↪cluster-name",
  "uid":"5207e71a-c83f-4707-b892-63aa93fb615c"
},
"spec":{
  "allowUnsafeConfigurations":false,

```

(continues on next page)

(continued from previous page)

```

"backup":{
  "enabled":true,
  "image":"percona/percona-server-mongodb-operator:1.5.0-backup",
  "restartOnFailure":true,
  "serviceAccountName":"percona-server-mongodb-operator",
  "storages":null,
  "tasks":null
},
"image":"percona/percona-server-mongodb:4.2.8-8",
"imagePullPolicy":"Always",
"mongod":{
  "net":{
    "hostPort":0,
    "port":27017
  },
  "operationProfiling":{
    "mode":"slowOp",
    "rateLimit":100,
    "slowOpThresholdMs":100
  },
  "security":{
    "enableEncryption":true,
    "encryptionCipherMode":"AES256-CBC",
    "encryptionKeySecret":"my-cluster-name-mongodb-encryption-key",
    "redactClientLogData":false
  },
  "setParameter":{
    "ttlMonitorSleepSecs":60,
    "wiredTigerConcurrentReadTransactions":128,
    "wiredTigerConcurrentWriteTransactions":128
  },
  "storage":{
    "engine":"wiredTiger",
    "inMemory":{
      "engineConfig":{
        "inMemorySizeRatio":0.9
      }
    },
    "mmapv1":{
      "nsSize":16,
      "smallfiles":false
    },
    "wiredTiger":{
      "collectionConfig":{
        "blockCompressor":"snappy"
      },
      "engineConfig":{
        "cacheSizeRatio":0.5,
        "directoryForIndexes":false,
        "journalCompressor":"snappy"
      },
      "indexConfig":{

```

(continues on next page)

(continued from previous page)

```

        "prefixCompression":true
    }
}
},
"pmm":{
    "enabled":false,
    "image":"percona/percona-server-mongodb-operator:1.5.0-pmm",
    "serverHost":"monitoring-service"
},
"replsets":[
    {
        "affinity":{
            "antiAffinityTopologyKey":"none"
        },
        "arbiter":{
            "affinity":{
                "antiAffinityTopologyKey":"none"
            },
            "enabled":false,
            "size":1
        },
        "expose":{
            "enabled":false,
            "exposeType":"LoadBalancer"
        },
        "name":"rs0",
        "podDisruptionBudget":{
            "maxUnavailable":1
        },
        "resources":{
            "limits":null
        },
        "size":3,
        "volumeSpec":{
            "persistentVolumeClaim":{
                "accessModes":[
                    "ReadWriteOnce"
                ],
                "resources":{
                    "requests":{
                        "storage":"3Gi"
                    }
                },
                "storageClassName":"standard"
            }
        }
    }
],
"secrets":{
    "users":"my-cluster-name-secrets"
},

```

(continues on next page)

(continued from previous page)

```

    "updateStrategy":"SmartUpdate"
  },
  "status":{
    "conditions":[
      {
        "lastTransitionTime":"2020-07-24T14:28:03Z",
        "status":"True",
        "type":"ClusterInitializing"
      },
      {
        "lastTransitionTime":"2020-07-24T14:28:39Z",
        "status":"True",
        "type":"Error"
      },
      {
        "lastTransitionTime":"2020-07-24T14:28:41Z",
        "status":"True",
        "type":"ClusterInitializing"
      },
      {
        "lastTransitionTime":"2020-07-24T14:28:41Z",
        "status":"True",
        "type":"Error"
      },
      {
        "lastTransitionTime":"2020-07-24T14:29:10Z",
        "status":"True",
        "type":"ClusterReady"
      },
      {
        "lastTransitionTime":"2020-07-24T14:49:46Z",
        "status":"True",
        "type":"ClusterInitializing"
      },
      {
        "lastTransitionTime":"2020-07-24T14:50:00Z",
        "status":"True",
        "type":"ClusterInitializing"
      },
      {
        "lastTransitionTime":"2020-07-24T14:52:31Z",
        "status":"True",
        "type":"ClusterInitializing"
      },
      {
        "lastTransitionTime":"2020-07-24T14:52:43Z",
        "status":"True",
        "type":"Error"
      },
      {
        "lastTransitionTime":"2020-07-24T14:53:01Z",
        "status":"True",

```

(continues on next page)

(continued from previous page)

```

        "type": "ClusterInitializing"
      },
      {
        "lastTransitionTime": "2020-07-24T14:53:05Z",
        "status": "True",
        "type": "ClusterInitializing"
      },
      {
        "lastTransitionTime": "2020-07-24T14:53:05Z",
        "status": "True",
        "type": "ClusterReady"
      }
    ],
    "observedGeneration": 1,
    "replsets": {
      "rs0": {
        "ready": 3,
        "size": 3,
        "status": "ready"
      }
    },
    "state": "ready"
  }
}

```

29.5 Scale up/down Percona Server for MongoDB cluster

Description:

Increase or decrease the size of the Percona Server **for** MongoDB cluster nodes to fit the
 ↪ current high availability needs

Kubectl Command:

```

kubectl patch psmdb my-cluster-name --type=merge --patch '{
  "spec": {"replsets":{ "size": "5" }
}'

```

URL:

[https://\\$API_SERVER/apis/psmdb.percona.com/v1/namespaces/default/perconaservermongodbs/
 ↪ my-cluster-name](https://$API_SERVER/apis/psmdb.percona.com/v1/namespaces/default/perconaservermongodbs/$my-cluster-name)

Authentication:

Authorization: Bearer \$KUBE_TOKEN

cURL Request:


```
curl -k -v -XPATCH "https://$API_SERVER/apis/psmdb.percona.com/v1/namespaces/default/
↳perconaservermongodb/my-cluster-name" \
-H "Authorization: Bearer $KUBE_TOKEN" \
-H "Content-Type: application/merge-patch+json"
-H "Accept: application/json" \
-d '{
    "spec": {"replsets":{"size": "5" }}
  }'
```

Request Body:

JSON:

```
{
  "spec": {"replsets":{"size": "5" }}
}
```

Input:

spec:

replsets

1. size (Int or String, Defaults: 3): Specify the size of the replsets cluster to scale up or down to

Response:

JSON:

```
{
  "apiVersion": "psmdb.percona.com/v1",
  "kind": "PerconaServerMongoDB",
  "metadata": {
    "annotations": {
      "kubectl.kubernetes.io/last-applied-configuration": "{\"apiVersion\":\"psmdb.
↳percona.com/v1-5-0\", \"kind\": \"PerconaServerMongoDB\", \"metadata\": {\"annotations\": {}}
↳, \"name\": \"my-cluster-name\", \"namespace\": \"default\", \"spec\": {\"
↳allowUnsafeConfigurations\": false, \"backup\": {\"enabled\": true, \"image\": \"percona/
↳percona-server-mongodb-operator:1.5.0-backup\", \"restartOnFailure\": true, \"
↳serviceName\": \"percona-server-mongodb-operator\", \"storage\": null, \"tasks\"
↳: null}, \"image\": \"percona/percona-server-mongodb:4.2.8-8\", \"imagePullPolicy\": \"
↳Always\", \"mongodb\": {\"net\": {\"hostPort\": 0, \"port\": 27017}, \"operationProfiling\": {\"
↳mode\": \"slowOp\", \"rateLimit\": 100, \"slowOpThresholdMs\": 100}, \"security\": {\"
↳enableEncryption\": true, \"encryptionCipherMode\": \"AES256-CBC\", \"encryptionKeySecret\"
↳: \"my-cluster-name-mongodb-encryption-key\", \"redactClientLogData\": false}, \"
↳setParameter\": {\"ttlMonitorSleepSecs\": 60, \"wiredTigerConcurrentReadTransactions\"
↳: 128, \"wiredTigerConcurrentWriteTransactions\": 128}, \"storage\": {\"engine\": \"
↳wiredTiger\", \"inMemory\": {\"engineConfig\": {\"inMemorySizeRatio\": 0.9}}, \"mmapv1\": {\"
↳nsSize\": 16, \"smallfiles\": false}, \"wiredTiger\": {\"collectionConfig\": {\"
↳blockCompressor\": \"snappy\", \"engineConfig\": {\"cacheSizeRatio\": 0.5, \"
↳directoryForIndexes\": false, \"journalCompressor\": \"snappy\", \"indexConfig\": {\"
↳prefixCompression\": true}}}}, \"pmm\": {\"enabled\": false, \"image\": \"percona/percona-
↳server-mongodb-operator:1.5.0-pmm\", \"serverHost\": \"monitoring-service\", \"replsets\"
↳: [{\"affinity\": {\"antiAffinityTopologyKey\": \"none\"}, \"arbiter\": {\"affinity\": {\"
↳antiAffinityTopologyKey\": \"none\"}, \"enabled\": false, \"size\": 1}, \"expose\": {\"
↳enabled\": false, \"exposeType\": \"LoadBalancer\", \"name\": \"rs0\"}, \"
↳podDisruptionBudget\": {\"maxUnavailable\": 1}, \"resources\": {\"limits\": null, \"size\"
↳: 3, \"volumeSpec\": {\"persistentVolumeClaim\": {\"accessModes\": [\"ReadWriteOnce\"], \"
29.5 Scale up/down Percona Server for MongoDB cluster 149
↳resourceRequirements\": {\"storage\": {\"storageClassName\": \"standard\"}}}}, \"secrets\": {\"users\": \"my-cluster-name-secrets\", \"updateStrategy\": \"SmartUpdate\"
↳}}}\n"
```

(continues on next page)

(continued from previous page)

```

},
"creationTimestamp":"2020-07-24T14:27:58Z",
"generation":4,
"managedFields":[
  {
    "apiVersion":"psmdb.percona.com/v1-5-0",
    "fieldsType":"FieldsV1",
    "fieldsV1":{
      "f:metadata":{
        "f:annotations":{
          ".":{

          },
          "f:kubectrl.kubernetes.io/last-applied-configuration":{

          }
        }
      },
      "f:spec":{
        ".":{

        },
        "f:allowUnsafeConfigurations":{

        },
        "f:backup":{
          ".":{

          },
          "f:enabled":{

          },
          "f:image":{

          },
          "f:serviceAccountName":{

          }
        },
        "f:image":{

        },
        "f:imagePullPolicy":{

        },
        "f:mongod":{
          ".":{

          },
          "f:net":{
            ".":{

            }
          }
        }
      }
    }
  }
],

```

(continues on next page)

(continued from previous page)

```

    },
    "f:port":{
    }
  },
  "f:operationProfiling":{
    ".":{

    },
    "f:mode":{

    },
    "f:rateLimit":{

    },
    "f:slowOpThresholdMs":{

    }
  },
  "f:security":{
    ".":{

    },
    "f:enableEncryption":{

    },
    "f:encryptionCipherMode":{

    },
    "f:encryptionKeySecret":{

    }
  },
  "f:setParameter":{
    ".":{

    },
    "f:ttlMonitorSleepSecs":{

    },
    "f:wiredTigerConcurrentReadTransactions":{

    },
    "f:wiredTigerConcurrentWriteTransactions":{

    }
  },
  "f:storage":{
    ".":{

    },
    "f:engine":{

```

(continues on next page)

(continued from previous page)

```
    },
    "f:inMemory":{
      ".":{

      },
      "f:engineConfig":{
        ".":{

        },
        "f:inMemorySizeRatio":{

        }
      }
    },
    "f:mmapv1":{
      ".":{

      },
      "f:nsSize":{

      }
    },
    "f:wiredTiger":{
      ".":{

      },
      "f:collectionConfig":{
        ".":{

        },
        "f:blockCompressor":{

        }
      },
      "f:engineConfig":{
        ".":{

        },
        "f:cacheSizeRatio":{

        },
        "f:journalCompressor":{

        }
      },
      "f:indexConfig":{
        ".":{

        },
        "f:prefixCompression":{
```

(continues on next page)

(continued from previous page)

```

        }
      }
    }
  },
  "f:pmm":{
    ".":{

    },
    "f:image":{

    },
    "f:serverHost":{

    }
  },
  "f:secrets":{
    ".":{

    },
    "f:users":{

    }
  },
  "f:updateStrategy":{

  }
},
{
  "manager":"kubectl",
  "operation":"Update",
  "time":"2020-07-24T14:27:58Z"
},
{
  "apiVersion":"psmdb.percona.com/v1",
  "fieldsType":"FieldsV1",
  "fieldsV1":{
    "f:spec":{
      "f:backup":{
        "f:containerSecurityContext":{
          ".":{

          },
          "f:runAsNonRoot":{

          },
          "f:runAsUser":{

          }
        },
        "f:podSecurityContext":{
          ".":{

```

(continues on next page)

(continued from previous page)

```
        },
        "f:fsGroup":{
            }
        },
        "f:clusterServiceDNSSuffix":{
            },
        "f:runUid":{
            },
        "f:secrets":{
            "f:ssl":{
                },
            "f:sslInternal":{
                }
            }
        },
        "f:status":{
            ".":{
                },
            "f:conditions":{
                },
            "f:observedGeneration":{
                },
            "f:replsets":{
                ".":{
                    },
                    "f:rs0":{
                        ".":{
                            },
                            "f:ready":{
                                },
                            "f:size":{
                                },
                            "f:status":{
                                }
                            }
                        }
                    }
                }
            },
            "f:state":{
```

(continues on next page)

(continued from previous page)

```

        }
      },
      {
        "manager": "percona-server-mongodb-operator",
        "operation": "Update",
        "time": "2020-07-24T15:35:14Z"
      },
      {
        "apiVersion": "psmdb.percona.com/v1",
        "fieldsType": "FieldsV1",
        "fieldsV1": {
          "f:spec": {
            "f:replsets": {
              ".": {

            },
            "f:size": {

            }
          }
        }
      },
      {
        "manager": "kubect1",
        "operation": "Update",
        "time": "2020-07-24T15:43:19Z"
      }
    ],
    "name": "my-cluster-name",
    "namespace": "default",
    "resourceVersion": "1279009",
    "selfLink": "/apis/psmdb.percona.com/v1/namespaces/default/perconaservermongodbbs/my-
↪cluster-name",
    "uid": "5207e71a-c83f-4707-b892-63aa93fb615c"
  },
  "spec": {
    "allowUnsafeConfigurations": false,
    "backup": {
      "enabled": true,
      "image": "percona/percona-server-mongodb-operator:1.5.0-backup",
      "restartOnFailure": true,
      "serviceAccountName": "percona-server-mongodb-operator",
      "storages": null,
      "tasks": null
    },
    "image": "percona/percona-server-mongodb:4.2.8-8",
    "imagePullPolicy": "Always",
    "mongod": {
      "net": {
        "hostPort": 0,
        "port": 27017
      }
    },
  },

```

(continues on next page)

(continued from previous page)

```

"operationProfiling":{
  "mode":"slowOp",
  "rateLimit":100,
  "slowOpThresholdMs":100
},
"security":{
  "enableEncryption":true,
  "encryptionCipherMode":"AES256-CBC",
  "encryptionKeySecret":"my-cluster-name-mongodb-encryption-key",
  "redactClientLogData":false
},
"setParameter":{
  "ttlMonitorSleepSecs":60,
  "wiredTigerConcurrentReadTransactions":128,
  "wiredTigerConcurrentWriteTransactions":128
},
"storage":{
  "engine":"wiredTiger",
  "inMemory":{
    "engineConfig":{
      "inMemorySizeRatio":0.9
    }
  },
  "mmapv1":{
    "nsSize":16,
    "smallfiles":false
  },
  "wiredTiger":{
    "collectionConfig":{
      "blockCompressor":"snappy"
    },
    "engineConfig":{
      "cacheSizeRatio":0.5,
      "directoryForIndexes":false,
      "journalCompressor":"snappy"
    },
    "indexConfig":{
      "prefixCompression":true
    }
  }
},
"pmm":{
  "enabled":false,
  "image":"percona/percona-server-mongodb-operator:1.5.0-pmm",
  "serverHost":"monitoring-service"
},
"replsets":{
  "size":"5"
},
"secrets":{
  "users":"my-cluster-name-secrets"
}

```

(continues on next page)

(continued from previous page)

```

    },
    "updateStrategy": "SmartUpdate"
  },
  "status": {
    "conditions": [
      {
        "lastTransitionTime": "2020-07-24T14:28:03Z",
        "status": "True",
        "type": "ClusterInitializing"
      },
      {
        "lastTransitionTime": "2020-07-24T14:28:39Z",
        "status": "True",
        "type": "Error"
      },
      {
        "lastTransitionTime": "2020-07-24T14:28:41Z",
        "status": "True",
        "type": "ClusterInitializing"
      },
      {
        "lastTransitionTime": "2020-07-24T14:28:41Z",
        "status": "True",
        "type": "Error"
      },
      {
        "lastTransitionTime": "2020-07-24T14:29:10Z",
        "status": "True",
        "type": "ClusterReady"
      },
      {
        "lastTransitionTime": "2020-07-24T14:49:46Z",
        "status": "True",
        "type": "ClusterInitializing"
      },
      {
        "lastTransitionTime": "2020-07-24T14:50:00Z",
        "status": "True",
        "type": "ClusterInitializing"
      },
      {
        "lastTransitionTime": "2020-07-24T14:52:31Z",
        "status": "True",
        "type": "ClusterInitializing"
      },
      {
        "lastTransitionTime": "2020-07-24T14:52:43Z",
        "status": "True",
        "type": "Error"
      },
      {
        "lastTransitionTime": "2020-07-24T14:53:01Z",

```

(continues on next page)

(continued from previous page)

```

        "status": "True",
        "type": "ClusterInitializing"
      },
      {
        "lastTransitionTime": "2020-07-24T14:53:05Z",
        "status": "True",
        "type": "ClusterInitializing"
      },
      {
        "lastTransitionTime": "2020-07-24T14:53:05Z",
        "status": "True",
        "type": "ClusterReady"
      }
    ],
    "observedGeneration": 1,
    "replsets": {
      "rs0": {
        "ready": 3,
        "size": 3,
        "status": "ready"
      }
    },
    "state": "ready"
  }
}

```

29.6 Update Percona Server for MongoDB cluster image

Description:

Change the image of Percona Server **for** MongoDB containers inside the cluster

Kubectl Command:

```

kubectl patch psmdb my-cluster-name --type=merge --patch '{
"spec": {"psmdb":{ "image": "percona/percona-server-mongodb-operator:1.4.0-mongod4.2" }
}}'

```

URL:

[https://\\$API_SERVER/apis/psmdb.percona.com/v1/namespaces/default/perconaservermongodbs/\\$my-cluster-name](https://$API_SERVER/apis/psmdb.percona.com/v1/namespaces/default/perconaservermongodbs/$my-cluster-name)

Authentication:

Authorization: Bearer \$KUBE_TOKEN

cURL Request:

```
curl -k -v -XPATCH "https://$API_SERVER/apis/psmdb.percona.com/v1/namespaces/default/
↳perconaservermongodb/my-cluster-name" \
-H "Authorization: Bearer $KUBE_TOKEN" \
-H "Accept: application/json" \
-H "Content-Type: application/merge-patch+json"
-d '{
  "spec": {"psmdb":{"image": "percona/percona-server-mongodb-operator:1.4.0-
↳mongod4.2" }
  }
}'
```

Request Body:

JSON:

```
{
  "spec": { "image ": "percona/percona-server-mongodb:4.2.8-8" }
}
```

Input:

spec:

psmdb:

1. image (String, min-length: 1): name of the image to update for Percona Server for MongoDB

Response:

JSON:

```
{
  "apiVersion": "psmdb.percona.com/v1",
  "kind": "PerconaServerMongoDB",
  "metadata": {
    "annotations": {
      "kubect1.kubernetes.io/last-applied-configuration": "{\"apiVersion\":\"psmdb.
↳percona.com/v1-5-0\", \"kind\":\"PerconaServerMongoDB\", \"metadata\":{\"annotations\":{
↳, \"name\":\"my-cluster-name\", \"namespace\":\"default\"}, \"spec\":{\"
↳allowUnsafeConfigurations\":false, \"backup\":{\"enabled\":true, \"image\":\"percona/
↳percona-server-mongodb-operator:1.5.0-backup\", \"restartOnFailure\":true,
↳serviceAccountName\":\"percona-server-mongodb-operator\", \"storage\":null, \"tasks\
↳\":null}, \"image\":\"percona/percona-server-mongodb:4.2.8-8\", \"imagePullPolicy\":\"
↳Always\", \"mongod\":{\"net\":{\"hostPort\":0, \"port\":27017}, \"operationProfiling\":{\"
↳mode\":\"slowOp\", \"rateLimit\":100, \"slowOpThresholdMs\":100}, \"security\":{\"
↳enableEncryption\":true, \"encryptionCipherMode\":\"AES256-CBC\", \"encryptionKeySecret\
↳\":\"my-cluster-name-mongodb-encryption-key\", \"redactClientLogData\":false},
↳setParameter\":{\"ttlMonitorSleepSecs\":60, \"wiredTigerConcurrentReadTransactions\
↳\":128, \"wiredTigerConcurrentWriteTransactions\":128}, \"storage\":{\"engine\":\"
↳wiredTiger\", \"inMemory\":{\"engineConfig\":{\"inMemorySizeRatio\":0.9}}, \"mmapv1\":{\"
↳nsSize\":16, \"smallfiles\":false}, \"wiredTiger\":{\"collectionConfig\":{\"
↳blockCompressor\":\"snappy\", \"engineConfig\":{\"cacheSizeRatio\":0.5,
↳directoryForIndexes\":false, \"journalCompressor\":\"snappy\", \"indexConfig\":{\"
↳prefixCompression\":true}}}, \"pmm\":{\"enabled\":false, \"image\":\"percona/percona-
↳server-mongodb-operator:1.5.0-pmm\", \"serverHost\":\"monitoring-service\", \"replsets\
↳\": [{\"affinity\":{\"antiAffinityTopologyKey\":\"none\"}, \"arbiter\":{\"affinity\":{\"
↳antiAffinityTopologyKey\":\"none\"}, \"enabled\":false, \"size\":1, \"expose\":{\"
↳enabled\":false, \"exposeType\":\"LoadBalancer\"}, \"name\":\"rs0\",
↳podDisruptionBudget\":{\"maxUnavailable\":1}, \"resources\":{\"limits\":{\"size\
↳29.6.3, Update Percona Server for MongoDB cluster image 159
↳resources\":{\"requests\":{\"storage\":\"3Gi\"}}, \"storageClassName\":\"standard\"}}
↳], \"secrets\":{\"users\":\"my-cluster-name-secrets\"}, \"updateStrategy\":\"SmartUpdate\
↳\"}}\n"
```

(continued from previous page)

```

},
"creationTimestamp":"2020-07-24T14:27:58Z",
"generation":5,
"managedFields":[
  {
    "apiVersion":"psmdb.percona.com/v1-5-0",
    "fieldsType":"FieldsV1",
    "fieldsV1":{
      "f:metadata":{
        "f:annotations":{
          ".":{

          },
          "f:kubectrl.kubernetes.io/last-applied-configuration":{

          }
        }
      },
      "f:spec":{
        ".":{

        },
        "f:allowUnsafeConfigurations":{

        },
        "f:backup":{
          ".":{

          },
          "f:enabled":{

          },
          "f:image":{

          },
          "f:serviceAccountName":{

          }
        },
        "f:image":{

        },
        "f:imagePullPolicy":{

        },
        "f:mongod":{
          ".":{

          },
          "f:net":{
            ".":{

            }
          }
        }
      }
    }
  }
],

```

(continues on next page)

(continued from previous page)

```
    },
    "f:port":{
    }
  },
  "f:operationProfiling":{
    ".":{

    },
    "f:mode":{

    },
    "f:rateLimit":{

    },
    "f:slowOpThresholdMs":{

    }
  },
  "f:security":{
    ".":{

    },
    "f:enableEncryption":{

    },
    "f:encryptionCipherMode":{

    },
    "f:encryptionKeySecret":{

    }
  },
  "f:setParameter":{
    ".":{

    },
    "f:ttlMonitorSleepSecs":{

    },
    "f:wiredTigerConcurrentReadTransactions":{

    },
    "f:wiredTigerConcurrentWriteTransactions":{

    }
  },
  "f:storage":{
    ".":{

    },
    "f:engine":{
```

(continues on next page)

(continued from previous page)

```
    },
    "f:inMemory":{
      ".":{

      },
      "f:engineConfig":{
        ".":{

        },
        "f:inMemorySizeRatio":{

        }
      }
    },
    "f:mmapv1":{
      ".":{

      },
      "f:nsSize":{

      }
    },
    "f:wiredTiger":{
      ".":{

      },
      "f:collectionConfig":{
        ".":{

        },
        "f:blockCompressor":{

        }
      },
      "f:engineConfig":{
        ".":{

        },
        "f:cacheSizeRatio":{

        },
        "f:journalCompressor":{

        }
      },
      "f:indexConfig":{
        ".":{

        },
        "f:prefixCompression":{
```

(continues on next page)

(continued from previous page)

```

        }
      }
    }
  },
  "f:pmm":{
    ".":{

    },
    "f:image":{

    },
    "f:serverHost":{

    }
  },
  "f:secrets":{
    ".":{

    },
    "f:users":{

    }
  },
  "f:updateStrategy":{

  }
},
{
  "manager":"kubectl",
  "operation":"Update",
  "time":"2020-07-24T14:27:58Z"
},
{
  "apiVersion":"psmdb.percona.com/v1",
  "fieldsType":"FieldsV1",
  "fieldsV1":{
    "f:spec":{
      "f:backup":{
        "f:containerSecurityContext":{
          ".":{

          },
          "f:runAsNonRoot":{

          },
          "f:runAsUser":{

          }
        },
        "f:podSecurityContext":{
          ".":{

```

(continues on next page)

(continued from previous page)

```
        },
        "f:fsGroup":{
            }
        },
        "f:clusterServiceDNSSuffix":{
            },
        "f:runUid":{
            },
        "f:secrets":{
            "f:ssl":{
                },
            "f:sslInternal":{
                }
            }
        },
        "f:status":{
            ".":{
                },
            "f:conditions":{
                },
            "f:observedGeneration":{
                },
            "f:replsets":{
                ".":{
                    },
                    "f:rs0":{
                        ".":{
                            },
                            "f:ready":{
                                },
                            "f:size":{
                                },
                            "f:status":{
                                }
                            }
                        }
                    }
                }
            },
            "f:state":{
```

(continues on next page)

(continued from previous page)

```

        }
      },
      {
        "manager": "percona-server-mongodb-operator",
        "operation": "Update",
        "time": "2020-07-24T15:35:14Z"
      },
      {
        "apiVersion": "psmdb.percona.com/v1",
        "fieldsType": "FieldsV1",
        "fieldsV1": {
          "f:spec": {
            "f:image ": {

            },
            "f:replsets": {
              ".": {

              },
              "f:size": {

              }
            }
          }
        },
        "manager": "kubect1",
        "operation": "Update",
        "time": "2020-07-27T12:21:39Z"
      }
    ],
    "name": "my-cluster-name",
    "namespace": "default",
    "resourceVersion": "1279853",
    "selfLink": "/apis/psmdb.percona.com/v1/namespaces/default/perconaservermongodbs/my-
↪cluster-name",
    "uid": "5207e71a-c83f-4707-b892-63aa93fb615c"
  },
  "spec": {
    "allowUnsafeConfigurations": false,
    "backup": {
      "enabled": true,
      "image": "percona/percona-server-mongodb-operator:1.5.0-backup",
      "restartOnFailure": true,
      "serviceAccountName": "percona-server-mongodb-operator",
      "storages": null,
      "tasks": null
    },
    "image": "percona/percona-server-mongodb:4.2.8-8",
    "imagePullPolicy": "Always",
    "mongod": {
      "net": {

```

(continues on next page)

(continued from previous page)

```

        "hostPort":0,
        "port":27017
    },
    "operationProfiling":{
        "mode":"slowOp",
        "rateLimit":100,
        "slowOpThresholdMs":100
    },
    "security":{
        "enableEncryption":true,
        "encryptionCipherMode":"AES256-CBC",
        "encryptionKeySecret":"my-cluster-name-mongodb-encryption-key",
        "redactClientLogData":false
    },
    "setParameter":{
        "ttlMonitorSleepSecs":60,
        "wiredTigerConcurrentReadTransactions":128,
        "wiredTigerConcurrentWriteTransactions":128
    },
    "storage":{
        "engine":"wiredTiger",
        "inMemory":{
            "engineConfig":{
                "inMemorySizeRatio":0.9
            }
        },
        "mmapv1":{
            "nsSize":16,
            "smallfiles":false
        },
        "wiredTiger":{
            "collectionConfig":{
                "blockCompressor":"snappy"
            },
            "engineConfig":{
                "cacheSizeRatio":0.5,
                "directoryForIndexes":false,
                "journalCompressor":"snappy"
            },
            "indexConfig":{
                "prefixCompression":true
            }
        }
    },
    "pmm":{
        "enabled":false,
        "image":"percona/percona-server-mongodb-operator:1.5.0-pmm",
        "serverHost":"monitoring-service"
    },
    "replsets":{
        "size":"5"
    }
}

```

(continues on next page)

(continued from previous page)

```

    },
    "secrets":{
      "users":"my-cluster-name-secrets"
    },
    "updateStrategy":"SmartUpdate"
  },
  "status":{
    "conditions":[
      {
        "lastTransitionTime":"2020-07-24T14:28:03Z",
        "status":"True",
        "type":"ClusterInitializing"
      },
      {
        "lastTransitionTime":"2020-07-24T14:28:39Z",
        "status":"True",
        "type":"Error"
      },
      {
        "lastTransitionTime":"2020-07-24T14:28:41Z",
        "status":"True",
        "type":"ClusterInitializing"
      },
      {
        "lastTransitionTime":"2020-07-24T14:28:41Z",
        "status":"True",
        "type":"Error"
      },
      {
        "lastTransitionTime":"2020-07-24T14:29:10Z",
        "status":"True",
        "type":"ClusterReady"
      },
      {
        "lastTransitionTime":"2020-07-24T14:49:46Z",
        "status":"True",
        "type":"ClusterInitializing"
      },
      {
        "lastTransitionTime":"2020-07-24T14:50:00Z",
        "status":"True",
        "type":"ClusterInitializing"
      },
      {
        "lastTransitionTime":"2020-07-24T14:52:31Z",
        "status":"True",
        "type":"ClusterInitializing"
      },
      {
        "lastTransitionTime":"2020-07-24T14:52:43Z",
        "status":"True",
        "type":"Error"
      }
    ]
  }
}

```

(continues on next page)

(continued from previous page)

```

    },
    {
      "lastTransitionTime": "2020-07-24T14:53:01Z",
      "status": "True",
      "type": "ClusterInitializing"
    },
    {
      "lastTransitionTime": "2020-07-24T14:53:05Z",
      "status": "True",
      "type": "ClusterInitializing"
    },
    {
      "lastTransitionTime": "2020-07-24T14:53:05Z",
      "status": "True",
      "type": "ClusterReady"
    }
  ],
  "observedGeneration": 1,
  "replsets": {
    "rs0": {
      "ready": 3,
      "size": 3,
      "status": "ready"
    }
  },
  "state": "ready"
}

```

29.7 Backup Percona Server for MongoDB cluster

Description:

Takes a backup of the Percona Server **for** MongoDB cluster containers data to be able to **recover** from disasters or make a roll-back later

KubectI Command:

```
kubectl apply -f percona-server-mongodb-operator/deploy/backup/backup.yaml
```

URL:

[https://\\$API_SERVER/apis/psmdb.percona.com/v1/namespaces/default/perconaservermongodbbackups](https://$API_SERVER/apis/psmdb.percona.com/v1/namespaces/default/perconaservermongodbbackups)

Authentication:

Authorization: Bearer **\$KUBE_TOKEN**

cURL Request:

```
curl -k -v -XPOST "https://$API_SERVER/apis/psmdb.percona.com/v1/namespaces/default/
↳perconaservermongodbbackups" \
  -H "Accept: application/json" \
  -H "Content-Type: application/json" \
  -d "@backup.json" -H "Authorization: Bearer $KUBE_TOKEN"
```

Request Body (backup.json):

JSON:

```
{
  "apiVersion": "psmdb.percona.com/v1",
  "kind": "PerconaServerMongoDBBackup",
  "metadata": {
    "name": "backup1",
    "namespace": "default"
  },
  "spec": {
    "psmdbCluster": "my-cluster-name",
    "storageName": "s3-us-west"
  }
}
```

Input:1. **metadata:**

name(String, min-length:1): name of backup to create

2. **spec:**

1. psmdbCluster(String, min-length:1): name of Percona Server for MongoDB cluster

2. storageName(String, min-length:1): name of storage claim to use

Response:

JSON:

```
{
  "apiVersion": "psmdb.percona.com/v1",
  "kind": "PerconaServerMongoDBBackup",
  "metadata": {
    "annotations": {
      "kubect1.kubernetes.io/last-applied-configuration": "{\n  \"apiVersion\": \"psmdb.\n  ↳percona.com/v1\", \"kind\": \"PerconaServerMongoDBBackup\", \"metadata\": {\n  ↳\"annotations\": {\n  ↳\"name\": \"backup1\", \"namespace\": \"default\"}, \"spec\": {\n  ↳\"psmdbCluster\": \"my-\n  ↳cluster-name\", \"storageName\": \"s3-us-west\"}}\n}"
    },
    "creationTimestamp": "2020-07-27T13:45:43Z",
    "generation": 1,
    "managedFields": [
      {
        "apiVersion": "psmdb.percona.com/v1",
        "fieldsType": "FieldsV1",
        "fieldsV1": {
          "f:metadata": {
```

(continues on next page)

(continued from previous page)

```

        "f:annotations":{
            ".":{

            },
            "f:kubect1.kubernetes.io/last-applied-configuration":{

            }
        }
    },
    "f:spec":{
        ".":{

        },
        "f:psmdbCluster":{

        },
        "f:storageName":{

        }
    }
},
"manager":"kubect1",
"operation":"Update",
"time":"2020-07-27T13:45:43Z"
}
],
"name":"backup1",
"namespace":"default",
"resourceVersion":"1290243",
"selfLink":"/apis/psmdb.percona.com/v1/namespaces/default/
↪perconaservermongodbbackups/backup1",
"uid":"e695d1c7-898e-44b0-b356-537284f6c046"
},
"spec":{
    "psmdbCluster":"my-cluster-name",
    "storageName":"s3-us-west"
}
}

```

29.8 Restore Percona Server for MongoDB cluster

Description:

Restores Percona Server **for** MongoDB cluster data to an earlier version to recover from a ↪ problem or to make a roll-back

Kubect1 Command:

```
kubect1 apply -f percona-server-mongodb-operator/deploy/backup/restore.yaml
```

URL:

```
https://$API_SERVER/apis/psmdb.percona.com/v1/namespaces/default/
↳perconaservermongodbrestores
```

Authentication:

```
Authorization: Bearer $KUBE_TOKEN
```

cURL Request:

```
curl -k -v -XPOST "https://$API_SERVER/apis/psmdb.percona.com/v1/namespaces/default/
↳perconaservermongodbrestores" \
-H "Accept: application/json" \
-H "Content-Type: application/json" \
-d "@restore.json" \
-H "Authorization: Bearer $KUBE_TOKEN"
```

Request Body (restore.json):

JSON:

```
{
  "apiVersion": "psmdb.percona.com/v1",
  "kind": "PerconaServerMongoDBRestore",
  "metadata": {
    "name": "restore1",
    "namespace": "default"
  },
  "spec": {
    "backupName": "backup1",
    "clusterName": "my-cluster-name"
  }
}
```

Input:1. **metadata:**

name(String, min-length:1): name of restore to create

2. **spec:**

1. clusterName(String, min-length:1): name of Percona Server for MongoDB cluster

2. backupName(String, min-length:1): name of backup to restore from

Response:

JSON:

```
{
  "apiVersion": "psmdb.percona.com/v1",
  "kind": "PerconaServerMongoDBRestore",
  "metadata": {
    "annotations": {
      "kubectl.kubernetes.io/last-applied-configuration": "{\n  \"apiVersion\": \"psmdb.\n↳percona.com/v1\", \"kind\": \"PerconaServerMongoDBRestore\", \"metadata\": {\n  \"annotations\": {\n↳\": {\n  \"name\": \"restore1\", \"namespace\": \"default\"}, \"spec\": {\n  \"backupName\": \"\n↳\"backup1\", \"clusterName\": \"my-cluster-name\"}}\n}"

```

(continues on next page)

(continued from previous page)

```

    },
    "creationTimestamp": "2020-07-27T13:52:56Z",
    "generation": 1,
    "managedFields": [
      {
        "apiVersion": "psmdb.percona.com/v1",
        "fieldsType": "FieldsV1",
        "fieldsV1": {
          "f:metadata": {
            "f:annotations": {
              ".": {
                },
                "f:kubect1.kubernetes.io/last-applied-configuration": {
                }
              }
            }
          },
          "f:spec": {
            ".": {
              },
              "f:backupName": {
              },
              "f:clusterName": {
              }
            }
          }
        },
        "manager": "kubect1",
        "operation": "Update",
        "time": "2020-07-27T13:52:56Z"
      }
    ],
    "name": "restore1",
    "namespace": "default",
    "resourceVersion": "1291198",
    "selfLink": "/apis/psmdb.percona.com/v1/namespaces/default/
    ↪perconaservermongodbrestores/restore1",
    "uid": "17e982fe-ac41-47f4-afba-fea380b0c76e"
  },
  "spec": {
    "backupName": "backup1",
    "clusterName": "my-cluster-name"
  }
}

```


FREQUENTLY ASKED QUESTIONS

- *Why do we need to follow “the Kubernetes way” when Kubernetes was never intended to run databases?*
- *How can I contact the developers?*
- *What is the difference between the Operator quickstart and advanced installation ways?*
- *Which versions of MongoDB the Operator supports?*
- *How can I add custom sidecar containers to my cluster?*
- *How to provoke the initial sync of a Pod*

30.1 Why do we need to follow “the Kubernetes way” when Kubernetes was never intended to run databases?

As it is well known, the Kubernetes approach is targeted at stateless applications but provides ways to store state (in Persistent Volumes, etc.) if the application needs it. Generally, a stateless mode of operation is supposed to provide better safety, sustainability, and scalability, it makes the already-deployed components interchangeable. You can find more about substantial benefits brought by Kubernetes to databases in [this blog post](#).

The architecture of state-centric applications (like databases) should be composed in a right way to avoid crashes, data loss, or data inconsistencies during hardware failure. Percona Distribution for MongoDB Operator provides out-of-the-box functionality to automate provisioning and management of highly available MongoDB database clusters on Kubernetes.

30.2 How can I contact the developers?

The best place to discuss Percona Distribution for MongoDB Operator with developers and other community members is the [community forum](#).

If you would like to report a bug, use the [Percona Distribution for MongoDB Operator project in JIRA](#).

30.3 What is the difference between the Operator quickstart and advanced installation ways?

As you have noticed, the installation section of docs contains both quickstart and advanced installation guides.

The quickstart guide is simpler. It has fewer installation steps in favor of predefined default choices. Particularly, in advanced installation guides, you separately apply the Custom Resource Definition and Role-based Access Control configuration files with possible edits in them. At the same time, quickstart guides rely on the all-inclusive bundle configuration.

At another point, quickstart guides are related to specific platforms you are going to use (Minikube, Google Kubernetes Engine, etc.) and therefore include some additional steps needed for these platforms.

Generally, rely on the quickstart guide if you are a beginner user of the specific platform and/or you are new to the Percona Distribution for MongoDB Operator as a whole.

30.4 Which versions of MongoDB the Operator supports?

Percona Distribution for MongoDB Operator provides a ready-to-use installation of the MongoDB-based database cluster inside your Kubernetes installation. It works with Percona Server for MongoDB 4.0, 4.2, and 4.4, and the exact version is determined by the Docker image in use.

Percona-certified Docker images used by the Operator are listed [here](#). For example, Percona Server for MongoDB 4.4 is supported with the following recommended version: 4.4.6-8. More details on the exact Percona Server for MongoDB version can be found in the release notes (4.4, 4.2, and 4.0).

30.5 How can I add custom sidecar containers to my cluster?

The Operator allows you to deploy additional (so-called *sidecar*) containers to the Pod. You can use this feature to run debugging tools, some specific monitoring solutions, etc. Add such sidecar container to the `deploy/cr.yaml` configuration file, specifying its name and image, and possibly a command to run:

```
spec:
  replsets:
  - name: rs0
    ....
  sidecars:
  - image: busybox
    command: ["/bin/sh"]
    args: ["-c", "while true; do echo echo $(date -u) 'test' >> /dev/null; sleep 5;↵
↵done"]
    name: rs-sidecar-1
    ....
```

You can add `sidecars` subsection to `replsets`, `sharding.configsvrReplSet`, and `sharding.mongos` sections.

Note: Custom sidecar containers can easily access other components of your cluster. Therefore they should be used carefully and by experienced users only.

30.6 How to provoke the initial sync of a Pod

There are certain situations where it might be necessary to delete all MongoDB instance data to force the resync. For example, there may be the following reasons:

- rebuilding the node to defragment the database,
- recreating the member failing to sync due to some bug.

In the case of a “regular” MongoDB, wiping the dbpath would trigger such resync. In the case of a MongoDB cluster controlled by the Operator, you will need to do the following steps:

1. Find out the names of the Persistent Volume Claim and Pod you are going to delete (use `kubect1 get pvc` command for PVC and `kubect1 get pod` one for Pods).
2. Delete the appropriate PVC and Pod. For example, wiping out the `my-cluster-name-rs0-2` Pod should look as follows:

```
kubect1 delete pod/my-cluster-name-rs0-2 pvc/mongod-data-my-cluster-name-rs0-2
```

The Operator will automatically recreate the needed Pod and PVC after deletion.

PERCONA DISTRIBUTION FOR MONGODB OPERATOR RELEASE NOTES

31.1 *Percona Distribution for MongoDB Operator 1.9.0*

Date June 29, 2021

Installation For installation please refer to [the documentation page](#)

31.1.1 Release Highlights

- Starting from this release, the Operator changes its official name to **Percona Distribution for MongoDB Operator**. This new name emphasizes graduate changes which incorporated a collection of Percona's solutions to run and operate MongoDB Server, available separately as [Percona Distribution for MongoDB](#).
- It is now possible to restore backups from S3-compatible storage *to a new Kubernetes-based environment* with no existing Backup Custom Resources
- You can now customize Percona Server for MongoDB by *storing custom configuration* for Replica Set, mongos, and Config Server instances in ConfigMaps or in Secrets

31.1.2 New Features

- [K8SPSMDB-276](#): Restore backups *to a new Kubernetes-based environment* *<backups-restore>* with no existing Backup Custom Resource
- [K8SPSMDB-444](#), [K8SPSMDB-445](#): Allow storing custom configuration in ConfigMaps and Secrets

31.1.3 Improvements

- [K8SPSMDB-365](#): Unblock backups even if just a single Replica Set node is available by setting `allowUnsafeConfigurations` flag to true
- [K8SPSMDB-453](#): It is now possible to see the overall progress of the provisioning of MongoDB cluster resources and dependent components in Custom Resource status
- [K8SPSMDB-451](#), [K8SPSMDB-398](#): MongoDB cluster resource statuses in Custom Resource output (e.g. returned by `kubectl get psmdb` command) have been improved and now provide more precise reporting
- [K8SPSMDB-425](#): Remove `mongos.expose.enabled` option from Custom Resource and always expose mongos (with the `ClusterIP` `exposeType` by default)

- [K8SPSMDB-421](#): Secret object containing system users passwords is now deleted along with the Cluster if delete-psmdb-pvc finalizer is enabled
- [K8SPSMDB-411](#): Added options to specify custom memory and CPU requirements for Arbiter instances
- [K8SPSMDB-329](#): Reduced the number of various etcd and k8s object updates from the operator to minimize the pressure on the Kubernetes cluster

31.1.4 Bugs Fixed

- [K8SPSMDB-437](#): Fixed a bug where Labels were not set on Persistent Volume Claim objects when set on the respective Pods
- [K8SPSMDB-435](#): Fixed a bug that prevented adding custom Labels to mongos Pods
- [K8SPSMDB-423](#): Fixed a bug where unpause of a cluster did not work when `replsets.expose = LoadBalancer` because of provisioning new Load Balancers with different names (Thanks to Aliaksandr Karavai for reporting this issue)
- [K8SPSMDB-494](#): When upgrading MongoDB clusters with Smart Update, the statuses reported in Custom Resource are now reflecting the real state
- [K8SPSMDB-489](#): Fixed a bug where the status of successful backups could be set to error in case of a cluster crash
- [K8SPSMDB-462](#): Fixed a bug where psmdb-backup object could not be deleted if the backup was not successful
- [K8SPSMDB-456](#): Fixed a bug where Smart Update was not upgrading a MongoDB deployment with a replica set consisting of one node
- [K8SPSMDB-455](#): Fixed a bug that prevented major version downgrade to a specific version number when `upgradeOptions.setFCV` Custom Resource option was not updated to the new version
- [K8SPSMDB-485](#): Fixed TLS documentation that referenced incorrect Secrets names from the `cr.yaml` configuration file

31.1.5 Deprecation and Removal

- We are simplifying the way the user can customize MongoDB components such as `mongod` and `mongos`. *It is now possible* to set custom configuration through ConfigMaps and Secrets Kubernetes resources. The following options will be deprecated in Percona Distribution for MongoDB Operator v1.9.0+, and completely removed in v1.12.0+:
 - `sharding.mongos.auditLog.*`
 - `mongod.security.redactClientLogData`
 - `mongod.security.*`
 - `mongod.setParameter.*`
 - `mongod.storage.*`
 - `mongod.operationProfiling.mode`
 - `mongod.auditLog.*`
- The `mongos.expose.enabled` option has been completely removed from the Custom Resource as it was causing confusion for the users

31.2 Percona Kubernetes Operator for Percona Server for MongoDB 1.8.0

Date May 6, 2021

Installation [Installing Percona Kubernetes Operator for Percona Server for MongoDB](#)

31.2.1 Release Highlights

- The support for *Point-in-time recovery* added in this release. Users can now recover to a specific date and time from operations logs stored on S3
- It is now possible to perform a *major version upgrade* for MongoDB (for example, upgrade 4.2 version to 4.4) with no manual steps

31.2.2 New Features

- [K8SPSMDB-387](#): Add support for *point-in-time recovery* to recover to a specific date and time
- [K8SPSMDB-284](#): Add support for automated major version MongoDB upgrades

31.2.3 Improvements

- [K8SPSMDB-436](#): The `imagePullPolicy` option in the `deploy/cr.yaml` configuration file now is applied to init container as well
- [K8SPSMDB-400](#): Simplify secret change logic to avoid Pod restarts when user changes the credentials
- [K8SPSMDB-381](#): Get credentials directly from Secrets instead of the environment variables when initializing the Replica Set
- [K8SPSMDB-352](#): Restrict running run less than 5 Pods of Replica Sets with enabled arbiter unless the `allowUnsafeConfigurations` option is set to true
- [K8SPSMDB-332](#): Restrict running less than 3 Pods of Config Servers unless the `allowUnsafeConfigurations` option is set to true
- [K8SPSMDB-331](#): Restrict running less than 3 mongos Pods unless the `allowUnsafeConfigurations` option is set to true

31.2.4 Bugs Fixed

- [K8SPSMDB-384](#): Fix a bug due to which mongos Pods were failing readiness probes for some period of time during the cluster initialization
- [K8SPSMDB-434](#): Fix a bug due to which nil pointer dereference error was occurring when switching the `sharding.enabled` option from false to true (thanks to srteam2020 for contributing)
- [K8SPSMDB-430](#): Fix a bug due to which a stale apiserver could trigger undesired StatefulSet and PVC deletion when recreating the cluster with the same name (thanks to srteam2020 for contributing)
- [K8SPSMDB-428](#): Fix a bug which caused mongos to fail in case of the empty name field in `configsvrReplSet` section of the Custom Resource

- [K8SPSMDB-418](#): Fix a bug due to which `serviceAnnotations` changes in the `deploy/cr.yaml` file were not applied to the running cluster
- [K8SPSMDB-364](#): Fix a bug where liveness probe of a mongo container was always failing if the `userAdmin` password contained special characters
- [K8SPSMDB-43](#): Fix a bug due to which renaming Replica Set in the Custom Resource caused creating new Replica Set without deleting the old one

31.3 Percona Kubernetes Operator for Percona Server for MongoDB 1.7.0

Date March 8, 2021

Installation [Installing Percona Kubernetes Operator for Percona Server for MongoDB](#)

31.3.1 Release Highlights

- This release brings full support for the *Percona Server for MongoDB Sharding*. Sharding allows you to scale databases horizontally, distributing data across multiple MongoDB Pods, and so it is extremely useful for large data sets. By default of the `deploy/cr.yaml` configuration file contains only one replica set, but when you *turn sharding on*, you can add more replica sets with different names to the `replsets` section.
- It is now *possible* to clean up Persistent Volume Claims automatically after the cluster deletion event. This feature is off by default. Particularly it is useful to avoid leftovers in testing environments, where the cluster can be re-created and deleted many times. Support for *custom sidecar containers*. The Operator makes it possible now to deploy additional (*sidecar*) containers to the Pod. This feature can be useful to run debugging tools or some specific monitoring solutions, etc. The sidecar container can be added to *replsets*, *sharding.configsvrReplSet*, and *sharding.mongos* sections of the `deploy/cr.yaml` configuration file.

31.3.2 New Features

- [K8SPSMDB-121](#): Add support for *sharding* to scale MongoDB cluster horizontally
- [K8SPSMDB-294](#): Support for *custom sidecar container* to extend the Operator capabilities
- [K8SPSMDB-260](#): Persistent Volume Claims *can now be automatically removed* after MongoDB cluster deletion

31.3.3 Improvements

- [K8SPSMDB-335](#): Operator can now automatically remove old backups from S3 if *retention period* is set
- [K8SPSMDB-330](#): Add support for `runtimeClassName` Kubernetes feature for selecting the container runtime
- [K8SPSMDB-306](#): It is now possible to explicitly set the version of MongoDB for newly provisioned clusters. Before that, all new clusters were started with the latest MongoDB version if Version Service was enabled
- [K8SPSMDB-370](#): Fix confusing log messages about no backup / restore found which were caused by Percona Backup for MongoDB waiting for the backup metadata
- [K8SPSMDB-342](#): MongoDB container liveness probe will now use TLS to follow best practices and remove noisy log messages from mongod log

31.3.4 Bugs Fixed

- [K8SPSMDB-346](#): Fix a bug which prevented adding/removing labels to Pods without downtime
- [K8SPSMDB-366](#): Fix a bug which prevented enabling Percona Monitoring and Management (PMM) due to incorrect request for the recommended PMM Client image version to the Version Service
- [K8SPSMDB-402](#): running multiple replica sets without sharding enabled should be prohibited
- [K8SPSMDB-382](#): Fix a bug which caused mongos process to fail when using `allowUnsafeConfigurations=true`
- [K8SPSMDB-362](#): Fix a bug due to which changing secrets in a single-shard mode caused mongos Pods to fail

31.4 *Percona Kubernetes Operator for Percona Server for MongoDB* 1.6.0

Date December 22, 2020

Installation [Installing Percona Kubernetes Operator for Percona Server for MongoDB](#)

31.4.1 New Features

- [K8SPSMDB-273](#): Add support for mongos service to expose a single *shard* of a MongoDB cluster through one entry point instead of provisioning a load-balancer per replica set node. In the following release, we will add support for multiple shards.
- [K8SPSMDB-282](#): Official support for *Percona Monitoring and Management (PMM) v.2*

Note: Monitoring with PMM v.1 configured according to the [unofficial instruction](#) will not work after the upgrade. Please switch to PMM v.2.

31.4.2 Improvements

- [K8SPSMDB-258](#): Add support for Percona Server for MongoDB version 4.4
- [K8SPSMDB-319](#): Show Endpoint in the `kubectl get psmdb` command output to connect to a MongoDB cluster easily
- [K8SPSMDB-257](#): Store the Operator version as a `crVersion` field in the `deploy/cr.yaml` configuration file
- [K8SPSMDB-266](#): Use plain-text passwords instead of base64-encoded ones when creating *System Users* secrets for simplicity

31.4.3 Bugs Fixed

- [K8SPSMDB-268](#): Fix a bug affecting the support of TLS certificates issued by `cert-manager`, due to which proper rights were not set for the role-based access control, and Kubernetes versions newer than 1.15 required other certificate issuing sources
- [K8SPSMDB-261](#): Fix a bug due to which cluster pause/resume functionality didn't work in previous releases
- [K8SPSMDB-292](#): Fix a bug due to which not all clusters managed by the Operator were upgraded by the automatic update

31.4.4 Removal

- The `MMAPv1 storage engine` is no longer supported for all MongoDB versions starting from this version of the Operator. MMAPv1 was already deprecated by MongoDB for a long time. WiredTiger is the default storage engine since MongoDB 3.2, and MMAPv1 was completely removed in MongoDB 4.2.

Note: Upgrade of the Operator from 1.5.0 to 1.6.0 will fail if MMAPv1 is used, but MongoDB cluster will continue to run. It is recommended to migrate your clusters to WiredTiger engine before the upgrade.

31.5 *Percona Kubernetes Operator for Percona Server for MongoDB* 1.5.0

Date September 7, 2020

Installation [Installing Percona Kubernetes Operator for Percona Server for MongoDB](#)

31.5.1 New Features

- [K8SPSMDB-233](#): Automatic management of system users for MongoDB on password rotation via Secret
- [K8SPSMDB-226](#): Official Helm chart for the Operator
- [K8SPSMDB-199](#): Support multiple PSMDB minor versions by the Operator
- [K8SPSMDB-198](#): Fully Automate Minor Version Updates (Smart Update)

31.5.2 Improvements

- [K8SPSMDB-192](#): The ability to set the `mongod cursorTimeoutMillis` parameter in YAML (Thanks to user `xprt64` for the contribution)
- [K8SPSMDB-234](#): OpenShift 4.5 support
- [K8SPSMDB-197](#): Additional certificate SANs useful for reverse DNS lookups (Thanks to user `phin1x` for the contribution)
- [K8SPSMDB-190](#): Direct API quering with “curl” instead of using “kubectf” tool in scheduled backup jobs (Thanks to user `phin1x` for the contribution)
- [K8SPSMDB-133](#): A special Percona Server for MongoDB debug image which avoids restarting on fail and contains additional tools useful for debugging

- [CLOUD-556](#): Kubernetes 1.17 / Google Kubernetes Engine 1.17 support

31.5.3 Bugs Fixed

- [K8SPSMDB-213](#): Installation instruction not reflecting recent changes in git tags (Thanks to user geraintj for reporting this issue)
- [K8SPSMDB-210](#): Backup documentation not reflecting changes in Percona Backup for MongoDB
- [K8SPSMDB-180](#): Replset and cluster having “ready” status set before mongo initialization and replicaset configuration finished
- [K8SPSMDB-179](#): The “error” cluster status instead of the “initializing” one during the replset initialization
- [CLOUD-531](#): Wrong usage of `strings.TrimLeft` when processing `apiVersion`

31.6 *Percona Kubernetes Operator for Percona Server for MongoDB* 1.4.0

Date March 31, 2020

Installation [Installing Percona Kubernetes Operator for PSMDB](#)

31.6.1 New Features

- [K8SPSMDB-89](#): Amazon Elastic Container Service for Kubernetes (EKS) was added to the list of the officially supported platforms
- [K8SPSMDB-113](#): Percona Server for MongoDB 4.2 is now supported
- OpenShift Container Platform 4.3 is now supported

31.6.2 Improvements

- [K8SPSMDB-79](#): The health check algorithm improvements have increased the overall stability of the Operator
- [K8SPSMDB-176](#): The Operator was updated to use Percona Backup for MongoDB version 1.2
- [K8SPSMDB-153](#): Now the user can adjust `securityContext`, replacing the automatically generated `securityContext` with the customized one
- [K8SPSMDB-175](#): Operator now updates `observedGeneration` status message to allow better monitoring of the cluster rollout or backups/restore process

31.6.3 Bugs Fixed

- [K8SPSMDB-182](#): Setting the updateStrategy: OnDelete didn't work if was not specified from scratch in CR
- [K8SPSMDB-174](#): The inability to update or delete existing CRD was possible because of too large records in etcd, resulting in "request is too large" errors. Only 20 last status changes are now stored in etcd to avoid this problem.

Help us improve our software quality by reporting any bugs you encounter using [our bug tracking system](#).

31.7 *Percona Kubernetes Operator for Percona Server for MongoDB* 1.3.0

Percona announces the *Percona Kubernetes Operator for Percona Server for MongoDB* 1.3.0 release on December 11, 2019. This release is now the current GA release in the 1.3 series. [Install the Kubernetes Operator for Percona Server for MongoDB by following the instructions](#).

The Operator simplifies the deployment and management of the [Percona Server for MongoDB](#) in Kubernetes-based environments. It extends the Kubernetes API with a new custom resource for deploying, configuring and managing the application through the whole life cycle.

The Operator source code is available [in our Github repository](#). All of Percona's software is open-source and free.

31.7.1 New Features and Improvements

- [CLOUD-415](#): Non-default cluster domain can now be specified with the new ClusterServiceDNSSuffix Operator option.
- [CLOUD-395](#): The Percona Server for MongoDB images size decrease by 42% was achieved by removing unnecessary dependencies and modules to reduce the cluster deployment time.
- [CLOUD-390](#): Helm chart for Percona Monitoring and Management (PMM) 2.0 have been provided.

[Percona Server for MongoDB](#) is an enhanced, open source and highly-scalable database that is a fully-compatible, drop-in replacement for MongoDB Community Edition. It supports MongoDB protocols and drivers. Percona Server for MongoDB extends MongoDB Community Edition functionality by including the Percona Memory Engine, as well as several enterprise-grade features. It requires no changes to MongoDB applications or code.

Help us improve our software quality by reporting any bugs you encounter using [our bug tracking system](#).

31.8 *Percona Kubernetes Operator for Percona Server for MongoDB* 1.2.0

Percona announces the *Percona Kubernetes Operator for Percona Server for MongoDB* 1.2.0 release on September 20, 2019. This release is now the current GA release in the 1.2 series. [Install the Kubernetes Operator for Percona Server for MongoDB by following the instructions](#).

The Operator simplifies the deployment and management of the [Percona Server for MongoDB](#) in Kubernetes-based environments. It extends the Kubernetes API with a new custom resource for deploying, configuring and managing the application through the whole life cycle.

The Operator source code is available [in our Github repository](#). All of Percona's software is open-source and free.

31.8.1 New Features and Improvements

- A [Service Broker](#) was implemented for the Operator, allowing a user to deploy Percona XtraDB Cluster on the OpenShift Platform, configuring it with a standard GUI, following the Open Service Broker API.
- Now the Operator supports [Percona Monitoring and Management 2](#), which means being able to detect and register to PMM Server of both 1.x and 2.0 versions.
- Data-at-rest encryption is now enabled by default unless `EnableEncryption=false` is explicitly specified in the `deploy/cr.yaml` configuration file.
- Now it is possible to set the `schedulerName` option in the operator parameters. This allows using storage which depends on a custom scheduler, or a cloud provider which optimizes scheduling to run workloads in a cost-effective way.
- The resource constraint values were refined for all containers to eliminate the possibility of an out of memory error.

31.8.2 Fixed Bugs

- Oscillations of the cluster status between “initializing” and “ready” took place after an update.
- The Operator was removing other cron jobs in case of the enabled backups without defined tasks (contributed by [Marcel Heers](#)).

[Percona Server for MongoDB](#) is an enhanced, open source and highly-scalable database that is a fully-compatible, drop-in replacement for MongoDB Community Edition. It supports MongoDB protocols and drivers. Percona Server for MongoDB extends MongoDB Community Edition functionality by including the Percona Memory Engine, as well as several enterprise-grade features. It requires no changes to MongoDB applications or code.

Help us improve our software quality by reporting any bugs you encounter using [our bug tracking system](#).

31.9 *Percona Kubernetes Operator for Percona Server for MongoDB* 1.1.0

Percona announces the general availability of *Percona Kubernetes Operator for Percona Server for MongoDB* 1.1.0 on July 15, 2019. This release is now the current GA release in the 1.1 series. [Install the Kubernetes Operator for Percona Server for MongoDB by following the instructions](#). Please see the [GA release announcement](#).

The Operator simplifies the deployment and management of the [Percona Server for MongoDB](#) in Kubernetes-based environments. It extends the Kubernetes API with a new custom resource for deploying, configuring and managing the application through the whole life cycle.

The Operator source code is available [in our Github repository](#). All of Percona’s software is open-source and free.

31.9.1 New Features and Improvements

- Now the Percona Kubernetes Operator [allows upgrading](#) Percona Server for MongoDB to newer versions, either in semi-automatic or in manual mode.
- Also, two modes are implemented for updating the Percona Server for MongoDB `mongod.conf` configuration file: in *automatic configuration update* mode Percona Server for MongoDB Pods are immediately re-created to populate changed options from the Operator YAML file, while in *manual mode* changes are held until Percona Server for MongoDB Pods are re-created manually.
- [Percona Server for MongoDB data-at-rest encryption](#) is now supported by the Operator to ensure that encrypted data files cannot be decrypted by anyone except those with the decryption key.
- A separate service account is now used by the Operator's containers which need special privileges, and all other Pods run on default service account with limited permissions.
- [User secrets](#) are now generated automatically if don't exist: this feature especially helps reduce work in repeated development environment testing and reduces the chance of accidentally pushing predefined development passwords to production environments.
- The Operator [is now able to generate TLS certificates itself](#) which removes the need in manual certificate generation.
- The list of officially supported platforms now includes the [Minikube](#), which provides an easy way to test the Operator locally on your own machine before deploying it on a cloud.
- Also, Google Kubernetes Engine 1.14 and OpenShift Platform 4.1 are now supported.

[Percona Server for MongoDB](#) is an enhanced, open source and highly-scalable database that is a fully-compatible, drop-in replacement for MongoDB Community Edition. It supports MongoDB protocols and drivers. Percona Server for MongoDB extends MongoDB Community Edition functionality by including the Percona Memory Engine, as well as several enterprise-grade features. It requires no changes to MongoDB applications or code.

Help us improve our software quality by reporting any bugs you encounter using [our bug tracking system](#).

31.10 *Percona Kubernetes Operator for Percona Server for MongoDB* 1.0.0

Percona announces the general availability of *Percona Kubernetes Operator for Percona Server for MongoDB* 1.0.0 on May 29, 2019. This release is now the current GA release in the 1.0 series. [Install the Kubernetes Operator for Percona Server for MongoDB by following the instructions](#). Please see the [GA release announcement](#). All of Percona's software is open-source and free.

The Percona Kubernetes Operator for Percona Server for MongoDB automates the lifecycle of your Percona Server for MongoDB environment. The Operator can be used to create a Percona Server for MongoDB replica set, or scale an existing replica set.

The Operator creates a Percona Server for MongoDB replica set with the needed settings and provides a consistent Percona Server for MongoDB instance. The Percona Kubernetes Operators are based on best practices for configuration and setup of the Percona Server for MongoDB.

The Kubernetes Operators provide a consistent way to package, deploy, manage, and perform a backup and a restore for a Kubernetes application. Operators deliver automation advantages in cloud-native applications and may save time while providing a consistent environment.

The advantages are the following:

- Deploy a Percona Server for MongoDB environment with no single point of failure and environment can span multiple availability zones (AZs).

- Deployment takes about six minutes with the default configuration.
- Modify the Percona Server for MongoDB size parameter to add or remove Percona Server for MongoDB replica set members
- Integrate with Percona Monitoring and Management (PMM) to seamlessly monitor your Percona Server for MongoDB
- Automate backups or perform on-demand backups as needed with support for performing an automatic restore
- Supports using Cloud storage with S3-compatible APIs for backups
- Automate the recovery from failure of a Percona Server for MongoDB replica set member
- TLS is enabled by default for replication and client traffic using Cert-Manager
- Access private registries to enhance security
- Supports advanced Kubernetes features such as pod disruption budgets, node selector, constraints, tolerations, priority classes, and affinity/anti-affinity
- You can use either PersistentVolumeClaims or local storage with hostPath to store your database
- Supports a replica set Arbiter member
- Supports Percona Server for MongoDB versions 3.6 and 4.0

31.10.1 Installation

Installation is performed by following the documentation installation instructions [for Kubernetes](#) and [OpenShift](#).